



and metaverse processing. Designed in tune with advanced silicon geometry, the architecture solves high-performance computing needs in reliability, security, and power consumption at scale. It has been designed on cutting-edge 5nm process technology. The architecture offers a high level of scalability to fit seamlessly into multiple sectors such as data centres, AI supercomputing, automotive, robotics, metaverse processing, and life sciences.

Ceremorphic

www.ceremorphic.com

Ultra-low-power wireless modules

The INP1014 and INP1015 modules offer wireless connectivity and integrated microcontroller for edge-of-network IoT devices that require low



INP1014
(w/ PCB Antenna)



INP1015
(w/ U.FL Connector)

power consumption and a direct-to-cloud connection. The INP1014/1015 modules provide the industry's lowest power Wi-Fi connectivity with their unique, programmable, digital radio architecture, and include multi-protocol Wi-Fi and BLE5-Long Range for wireless data transfer. They can operate in stand-alone mode, in conjunction with an external MCU, or in a hybrid mode. The new modules offer 40% size reduction to provide greater design flexibility and extended battery life. The platform expedites the development of smart IoT products such as connected sensors, security cameras, asset tracking devices, health monitoring wearables, audio speakers, and many others.

InnoPhase

www.innophaseinc.com

Rugged tactical grade IMU

The Pulse-40 is a 6 degrees of Freedom inertial measurement unit (IMU) that offers unmatched performance in

harsh conditions in a miniaturised size for applications where precision and robustness matter in all conditions. It



integrates cutting-edge MEMS three axes accelerometers and gyroscopes in a unique redundant design that allows to shrink the system size while pushing performance level to its maximum. Thanks to sensors featuring extremely low vibration rectification error (VRE), the Pulse-40 can sustain high vibration environments up to 10g RMS.

SBG Systems

www.sbg-systems.com

Switching power supply ICs

Two new AEC-Q100 qualified, 1700-volt rated ICs that expand Power Integrations' InnoSwitch 3-AQ family are the industry's first automotive-qualified switching power supply ICs




to incorporate a silicon carbide (SiC) primary switching MOSFET. Delivering up to 70 watts of output power, the new ICs are targeted for use in 600- and 800-volt battery and fuel-cell electric passenger vehicles, as well as electric buses, trucks, and a wide range of industrial power applications. The ICs reduce the number of components required to implement a power supply by as much as 50%, saving significant circuit-board space. The ICs can be implemented across a broad range of consumer, computer, communications, industrial, and automotive applications.

Power Integrations

www.power.com

High-power SP4T switch

The MM5120 is a high-power single-pole/four-throw (SP4T) DC-to-18GHz switch that provides high performance,




reliability, and integration for RF switching applications. It offers ultra-low insertion loss, 25W power handling, and the highest linearity in the industry, significantly outperforming conventional solid-state switches and electro-mechanical relays. The MM5120 switch eliminates the compromises developers face when deciding between electromechanical relays or solid-state switches for RF designs. It reduces cost and simplifies the development of numerous RF systems, including RF filters and front ends, device interface boards for semiconductor test and beamforming antennas used in advanced radio architectures and radar systems.

Menlo Microsystems

www.menlomicro.com

Mini liquid flow sensor

With a footprint of only 10x10 mm², the liquid flow sensor LPG10 series provides outstanding performance and speed in



measuring liquid flow. It is a smart sensor solution that offers flow rates from the low microlitre-

per-minute range up to one millilitre per minute. The use of glass as the only wetted material ensures optimal compatibility with biological and pharmaceutical processes. Due to its highly compact integration into any fluidic manifold system, it is ideal for high-volume applications with strict space limitations.

Sensirion

www.sensirion.com