

enables configuration of a compact wireless charging system using the 13.56MHz frequency band to deliver up to 200mW. Using the transmitter and receiver modules as a pair can significantly reduce the development load for prototyping and evaluation.

ROHM Semiconductor

www.rohm.com

DC-DC converter

The BMR350 is a non-isolated DC-DC converter in a quarter brick format, rated at 860W continuous and 1200W



peak power. BMR350 is ideal as an intermediate bus converter

for powering processors and ASICs with peak power demands. The product features an input of 40-60V (80V/100ms) and a fully regulated output of 12V at 100A maximum, adjustable from 8V to 13.2V. An innovative transformer-coupled, non-isolated topology reduces component count and current stress and yields an efficiency level peaking at >97.8% at half load 48V input voltage. Derating for the BMR350 is characterised by the innovative 3D thermal data graphs, which specify available output power for given real-world pin and baseplate temperatures up to 100°C.

Flex Power Modules

www.flexpowermodules.com

LTE Cat 1 modules

The LARA-R6 is the smallest LTE Cat 1 module with global coverage on the market. The u-blox LENA-R8 includes



a global navigation satellite system (GNSS)

receiver based on the u-blox M10 platform. Together, the modules comprise five certified global, multi-regional, and regional product variants, simplifying logistics for product developers and increasing design flexibility. The modules offer device makers facing imminent 2G and 3G network sunsets a future-proof migration path to 4G

technology for data streaming applications.

u-blox

www.u-blox.com

Modules with 12th Gen processors

The 12th Gen Intel Core processor based computer-on-modules (COM) are available in two form factors—COM-HPC Client Type and



COM Express Type 6. ADLINK COMs with the Intel 12th Gen Intel Core processor family (Codename: Alder

Lake-H) allow for a unique design that can be adapted for single-thread or multithread performance. The advanced hybrid architecture can be used for stationary, mobile, and portable solutions. It also provides system integrators with future-proof design that supports both current and future best-in-class peripherals.

ADLINK Technology

www.adlinktech.com

AC-DC power supplies

The TPI 180 and TPP 180 are a set of encapsulated AC-DC power supplies coming as open frame and encased versions. They feature a reinforced



double I/O isolation (3000V AC) system according to the latest medical safety standards

(60601-1 3rd edition, 2 x MOPP). The leakage current is below 300µA and makes the units suitable for BF (body floating) applications. The excellent efficiency of up to 94% allows a high power-density and compact design (3" x 2" for open frame and 3.6" x 2.44" for encased version). High reliability is provided by using high-quality components and an excellent thermal management, making the TPI 180 and TPP 180 an ideal solution for industrial and medical devices, and for demanding safety and space critical applications.

TRACO Power

www.tracopower.com

Wi-Fi front-end module

QPF4730 is the first wideband Wi-Fi front-end module (FEM) covering the 5.1GHz to 7.1GHz bands for cus-



tomer premises equipment (CPE). It can provide full-frequency support for both Wi-Fi 6

and Wi-Fi 6E enterprise solutions. The QPF4730 enhances efficiency in Wi-Fi 6/Wi-Fi 6E architectures and is optimised for power over Ethernet (PoE), improving quality of service (QoS), range, and throughput. This solution maximises user capacity and leverages the full available spectrum. It also enables manufacturers to design smaller form factors than current gateways to meet user expectations for more compact, sleek and efficient designs.

Qorvo

www.qorvo.com

Safety relay module

The X90 control system by B&R now comes with an option board that allows floating-ground connection



of external safety devices, making mobile machines even safer. With the new

safety relay module, external safety components, such as drives or laser scanners, can now be connected to the X90 controller via a floating-ground emergency stop circuit. A safety level of PLe/SIL3 can be achieved. The option board is particularly suitable for autonomous agricultural and construction vehicles.

B&R Industrial Automation

www.br-automation.com

T&M SOLUTIONS

5G test platform

The new R&S CMX500 one-box tester provides extensive device testing capability, including support for all 5G NR deployments covering LTE, 5G NR FR1 and FR2 in non-standalone (NSA) and