

standalone (SA) mode, for both FDD and TDD, with an effortless setup and an outstanding performance. Manu-



facturers of cutting-edge 5G NR capable chipsets and devices as well as certification

providers can cover the entire product lifecycle with the R&S CMX500 one-box tester, from all early R&D design phases to end-to-end application testing, including device certification. Data-hungry enhanced mobile broadband (eMBB) applications like 8K video streaming or augmented and virtual reality can fulfil high data rates in uplink and downlink.

Rohde & Schwarz

www.rohde-schwarz.com

Calibration solutions

Existing and new customers of the PicoVNA 108 8.5GHz vector network analyser can now benefit from automated E-Cal calibration and TRL/TRM



calibration. The PicoVNA 108 achieves calibration automation through either male SMA or female

SMA E-Cal modules. Simply power the module, make a single connection of the E-Cal standard between the PicoVNA test ports and then initiate the automated procedure from within the PicoVNA 108 user interface. The TRL (Through Reflect Line) and TRM (Through Reflect Match) calibration typically measure substrate-mounted DUTs, for example surface-mounted networks or components on a PCB or ceramic.

Pico Technology

www.picotech.com

Enhanced mixed signal oscilloscope

With numerous enhancements, the 5 Series B mixed signal oscilloscope (MSO) delivers even more versatility while continuing to provide high-fidelity waveforms, unique spectrum analysis



capabilities, and flexible signal access. Built on the performance and integrity that engineers rely on with the original 5 Series MSO, the B version includes customer-centric updates led by a new auxiliary trigger input that lets users synchronise the oscilloscope to an external signal without consuming any of the 4, 6, or 8 full-capability input channels. For the optional, built-in arbitrary/function generator, the maximum frequency output increases from 50MHz to 100MHz, enabling higher frequency stimulus for Bode plots and impedance measurements.

Tektronix

www.tektronix.com

High-speed 800G test portfolio

To enable the optical transceiver ecosystem for improving the power efficiency of components and modules used in data centre equipment, Key-



sight's portfolio of high-speed digital 800G test solutions has

been expanded. These additions are new design and validation solutions that support multimode interfaces, which are critical for an energy-efficient data centre infrastructure. The 800G multimode test solutions uniquely support high-speed data interconnect speeds of up to 100 gigabit per second (Gbps). The extended portfolio supports 400G and 800G design validation from early research and development to manufacturing.

Keysight Technologies

www.keysight.com

SOFTWARE

Software for PCB design

Altair PollEx, an electronic system design (ESD) software tool for Altium



users, empowers printed circuit board (PCB) designers to predict and maximise overall PCB performance and verify manufacturability. Altair PollEx for

Altium is a free version of PollEx designed to support various electrical computer-aided design (ECAD) software products, the first of which is Altium Designer, as announced at AltiumLive. Altair PollEx for Altium will make board-level simulation and design verification features seamlessly accessible to Altium Designer users.

Altair

www.altair.com

NOR memories design tool

With the SEMPER Solutions Hub, a one-stop portal with all the building blocks needed to integrate SEMPER



NOR Flash into an application, developers can quickly design safety-critical

and inherently secured automotive, industrial, and communications systems. The SEMPER Solutions Hub provides the development edge needed to accelerate the design process. The web portal offers easy access to software development kits (SDKs) containing production-grade drivers and application code examples. Additionally, it offers hardware kits for prototyping with microcontroller (MCU) system boards from both Infineon and third-party suppliers, MCUs and available integrated development environments (IDEs).

Infineon Technologies

www.infineon.com

Data diagnosis software

The PCAN-OBD-2 Viewer offers an easy way to develop own applications



based on the OBD-2 communication standard. The tool and the API can be used with all PC-CAN interfaces from PEAK-System.

The PCAN-OBD-2 Viewer supports all OBD-2 services that are transmitted via CAN. A virtual cockpit displays the data graphically in analogue and digital instruments. Optionally, individual parameters can also be displayed as