


graphs, including the option of exporting graphs and data sets. In addition, diagnostic trouble codes and available test results are displayed.

PEAK System
www.peak-system.com

CHEMICALS & ADHESIVES

Recyclable static dissipative stretch film

A new recyclable speciality film, Eco-Sonic VpCl Static Dissipative Stretch Film, has been developed for applica-



tions where static discharge could result in dangerous packaging conditions, such as electronics and fer-

tilisers. The new stretch film meets the anti-static requirements under MIL-PR F-81705 E, while featuring multi-metal corrosion inhibitors and EDS protection. The stretch film reportedly eliminates the static discharge that can typically arise from the pressure and friction of stretch-wrapping applications, which cannot be dissipated by grounding. Additionally, the stretch film does not interfere with electrical, optical, or mechanical surface properties and does not require costly barrier packaging.

Cortec Laboratories
www.cortecvci.com

MANUFACTURING EQUIPMENT

Intelligent SMT component assembler

The new intelligent freeform feeder gives manufacturers a fast and effective alternative to taping loose components. It also serves to eliminate one process step and reduce the possibility of human error. The system comprises a pair of trays (one white, one black, to optimise optical contrast against the loose components), each featuring nine separate cells to hold differ-



ent components. These are simply dropped into the 25mm x 18mm cells without the need for any orientation or alignment. Using machine vision, advanced component recognition algorithms identify the devices held in each cell irrespective of angle, physical position, or polarity, allowing the placement machine to pick and place perfectly.

Europlacer
www.europlacer.com

Solder paste inspection equipment

The new dual-mode MRS sensor for the SE3000 SPI system provides maximum flexibility for dedicated



solder paste inspection applications, with one mode for high speed inspection and another mode for high resolution inspection. The

new sensor is an extension of the proprietary Multi-Reflection Suppression sensor portfolio that provides industry-leading performance in semiconductor and SMT markets. The SE3000 is ideal for measuring height, area, volume, registration, and bridging, as well as detecting insufficient paste, excess height, smear, offset, and more.

CyberOptics
www.cyberoptics.com

ENTERPRISE CLASS

Industrial grade PCs

The 38cm and 54.6cm (15-inch and 21.5-inch) SPC-1533-B1 and SPC-



2133-B1 rugged industrial-grade panel PCs offer significant improvement in water resistance and structure, which ensure

uninterrupted and efficient operation even in a rigorous operating environment. They meet the stringent requirements of the industrial automation market as they target IIoT applications in public utilities, maritime sector,

transportation, and industrial automation.

Avalue Technology
www.avalue-tech.com

Rackmount network appliance

The INA3600 is a highly reliable 1U rackmount network appliance



designed to handle complex and demanding networking tasks for both large and growing businesses. It delivers powerful networking performance optimised for high-density deployments in applications such as network security, SDN, NFV, SD-WAN, data management and analytics. The INA3600 high performance 1U-sized appliances are powered by 10th Gen Intel Core and Xeon W processors (codenamed Comet Lake) and support up to 14Gb Ethernet ports with IBASE proprietary network interface cards.

IBASE Technology
www.ibase.com.tw

Advanced thermostat and humidistat

The HyperStat is a device that senses temperature, humidity, CO₂, occu-



pancy, light, sound, volatile organic compounds (VOCs), and optional particulate matter, making it an

affordable one-stop device for WELL Building Standard support. Data from these sensors feed wirelessly into a real-time analytics package and inform 75F's built-in, Guideline 36-compliant control algorithms. In addition, the HyperStat comes packed with four analogue inputs, three analogue outputs, and six relays that leverage software-defined control capabilities for all types of standalone multi-stage and modulating packaged HVAC equipment found in commercial buildings.

75F
www.75f.io