

events, and characterising frequency agile signals.

Rohde and Schwarz

<https://www.rohde-schwarz.com>

ENTERPRISE CLASS

Fanless panel PC

MPPC1201PC from IBASE Technology is a fanless panel PC designed for intelligent railway transportation applications. Powered by an Intel



Atom x6425E processor, the module features an aluminium

cooling chassis with quick heat dissipation, enabling long-term operation in harsh environments. The device features a simple on-screen display interface and multiple expansion slots, which include a full-size mPCI-e slot and an M.2 E-Key 2230 socket provided for 4G and Wi-Fi modules for secure backup internet connection. The rugged PC comes with a water-tight M12 connector and IP65 certification, which makes it suitable to use in harsh weather conditions.

iBASE

<https://www.ibase.com.tw>

Air control for server rooms

BryShield by Bry-Air is an air filtration system and dehumidifier designed for small server rooms. The air-filtration



system can easily fit into any false ceiling and remove the gaseous contaminants

from the enclosed room. The dehumidifier can effectively prevent electronic corrosion and micro-corrosion caused due to gaseous contaminants. The BryShield is energy-efficient, compact, and lightweight, and can be controlled with a remote. It employs a honeycomb-shaped chemical filter, which contains easily replaceable macro-porous filters that come with a life span of more than a year. It can prevent server downtime and saves losses from server failures by preventing electronic corrosion in small server

rooms, control rooms, and electronic equipment rooms across diverse sectors like banks, IT companies, telecom sites, hospitals, R&D centres, laboratories, etc.

Bry-Air

<https://www.bryair.com>

BOARDS AND MODULES

Development board with sensors

PVL4m from iC-Haus is a development board that combines an angle sensor and a Hall sensor in the same module. The PVL4m employs a 26-bit encoder signal processor iC-TW29 with



an integrated EEPROM to evaluate both the sensors simultaneously. It also features a super capacitor which can enable non-disruptive revolution counting for several hours without requiring any external supply. The development board offers a small delay of 1.5µs, which is comparable to the delays present in the optical encoders, making it fast, precise, and reliable.

iC Haus

<https://www.ichaus.de>

Development board for energy harvesters

Trameto's Severn platform is a development board designed for the evaluation of ambient micro-energy harvesting. The Severn platform employs TM2040, which is a smart EH PMIC



with four inputs. It can use both a photovoltaic harvester and a thermoelectric generator as input. Furthermore, it can automatically adapt to the harvester type connected at the input to increase energy harvesting. The module can simultaneously take up to four energy harvesters of the same or mixed type as an input, without requiring any additional interfacing components.

The development platform can enable designers to design and validate their energy harvesting modules during the

proof of concept phase.

Trameto

<https://trameto.com>

Robust 800W power supply

COSEL AEA800F is a robust 800W power supply for demanding applications. The AEA800F can deliver up to 300% of its peak power for 30 seconds, making it suitable for power-



ing DC motors.

The power supply features a small and compact PCB

layout optimised for air cooling. The AEA800F is designed for critical applications requiring a high level of safety and reliability and comes with an EN62477-1OVC III certification. The module is suitable for use as a medical body floating application and other demanding industrial applications.

COSEL

<https://coselusa.com>

1500W AC/DC power supply

Mornsun has added a 1500W AC/DC power supply to its LMF1500-20Bxx series. The enclosed power supply offers high energy density and good EMC performance. The module offers



a variable fan speed control and has a power efficiency of up to 94%. The

power supply features a built-in active PFC function and can operate at a wide range of input voltage of up to 370V DC. This power supply module supports 3 + 1 parallel redundancy and current sharing. The compact size, high efficiency and wide range of operations make it suitable for application in the industrial control system, LED streetlight control, telecommunications, smart home, etc.

Mornsun

<https://www.mornsun-power.com>

High-capacity backhaul radio

Cambium Networks has introduced cnWave V3000, a backhaul radio that operates from 57GHz to 66GHz,