

ENABLING TECHNOLOGY EVERYWHERE

HARWIN
Connect with confidence



Scan here for more

Harwin's connector products are proven to perform in extreme conditions, with shock, vibration and temperature range rigorously tested.

Micro connectors start at 1.25mm pitch delivering 2A per contact, up to 8.5mm and 60A - covering a wide range of applications from charging infrastructure to battery management systems.

With our quality, service, support, and highly reliable products, you can depend on Harwin.

Connectors shown actual size



harwin.com

Once you
stop learning,
you start dying.

—Albert Einstein

Amaze Yourself!

Read Electronics For You

You'll realise how much you didn't know,
and didn't know that you didn't know!

To Subscribe:
<https://subscribe.efy.in>

Scan This Code




**DISPLAY
INDUSTRIAL SOLUTIONS
VISIONS**

- Excellent contrast 2000:1
- For environments -40...+80°C
- Extremely wide viewing angle 170°
- SPI, I²C Bus Interface
- Integrated character set
- Super fast, even at -40°C
- Text and graphic
- Super flat and sturdy
- With pins for easy mounting
- USB testboard
- Optional touch panel
- Ex stock available




OLED102



OLED128



OLED204



OLED128

OLED DISPLAYS

www lcd-module.com

