

- Real-time sampling rate up to 2GSa/s
- Record length up to 200Mpts
- Serial bus triggering and decoder, supports I2C, SPI, UART, CAN, LIN, CAN FD, FlexRay, I2S and MIL-STD-1553B
- Provide ten-bit mode, vertical and horizontal zoom
- Capacitive touchscreen supports multi-touch gestures

Siglent Technologies Co. Ltd
<https://int.siglent.com>

Digital colour meter

Minoo Impex has launched digital colour meter Metrix+ COL 45, which can measure the colour of a no lighting, non-fluorescent material in six colour



spaces, and also measure difference between two measured colours. This works according to tristimulus absorption and imitates human vision. This can be used to measure the colour

of no lighting and non-fluorescent samples such as textile, paper, leather, painting materials, etc. It can also be used for calculating colour differences between two colours in any of the six colour spaces. It is a useful tool for quality control and wide industrial applications.

minoo Impex
www.metrixinstrument.in

MISCELLANEOUS

Fixed cellular terminal

SIMADO GFX11 is a GSM fixed cellular terminal that offers accessibility of GSM/3G/4G networks for voice communications. It is a single-port device for GSM and FXS interface, which is ideal



for upgrading existing communication infrastructure. It empowers enterprise growth by offering connectivity convenience to new age networks and investment protection on existing PBX. Key features are:

- Allowed and denied lists
- Automatic number translation
- Hotline
- Multi-stage dialling
- Network selection
- Quad-band, LTE support
- Compact and sturdy
- CLI display
- Signal strength indication

Matrix Comsec
www.matrixcomsec.com

LED driver modules

RECOM has added to its offering of LED drivers with RCDE-48 series, a range of modules that can provide up to 350mA, 700mA or 1050mA constant current to drive strings of up to fifteen high bright-



ness LEDs with efficiency up to 97 per cent. Input voltage range is 6V DC to 60V DC to suit 12V, 24V or 48V nominal supply rails, and a zero to hundred per cent linear analogue or PWM dimming input is provided, which is compatible with 3.3V logic, making it ideal for Internet of Things (IoT) nodes or µC dimmers.

RECOM Asia Pte Ltd
<https://recom-power.com>

Ethernet transceiver

Ethernet is becoming more common in spacecraft to enable hardwired communication speed, support higher data rates, and facilitate interoperability between satellites and other spacecraft. As Ethernet in space applications continues to expand, Microchip Technology has announced the industry's first space-qualified Ethernet transceiver, a radiation-tolerant device based on a commercial-off-the-shelf (COTS) solution widely deployed in other industries now

offering reliable performance for applications ranging from launch vehicles to satellite constellations and space stations.

Microchip Technology Inc.
www.microchip.com

Processor platform

Texas Instruments has introduced the new Jacinto 7 processor platform. Built on the foundation of TI's decades of automotive systems and functional safety expertise, the new Jacinto processor platform brings enhanced deep learning capabilities and advanced networking to solve design challenges in advanced driver assistance systems (ADAS) and automotive gateway applications.

Texas Instruments
www.ti.com

Powerline communications device

Designers of ultra-low-power portables and wearables can shrink size of a power and communication interface to the charging dock by up to eighty per cent with MAX20340, the industry's smallest two-pin bi-directional DC powerline communications (PLC) device from Maxim Integrated Products. With power and communication on a single line, MAX20340 eliminates pins and discrete devices needed to communicate between a charging dock and a low-voltage end-product such as true wireless earbuds, rings and other small wearables. This simplifies the design process and saves up to 13mm² per earbud compared to the closest competitive solution.

Maxim Integrated Products Inc.
www.maximintegrated.com

Bluetooth mesh software stacks

With the release of Bluetooth mesh software stacks for BlueNRG family of Bluetooth Low Energy (BLE) chips and modules, STMicroelectronics demonstrates how BlueNRG mesh software and proven BLE-enabled wireless sensor platforms, together, enable to form pervasive and scalable networks of sensors and actuators that can support new use-cases extending throughout smart buildings and smart factories.

STMicroelectronics
www.st.com