

DC/DC Converter

Fixed input voltage			Wide input voltage			
SMD	≤1 Watt		2 to 3 Watts		1 to 3 Watts	
	F_XT-W2R3 • 0.2 Watt • 2000VAC Isolation • Continuous short circuit protection	A/B/F_XT-1WR2/R3 E_XT-1WR2/1WR3 • 1 Watt • 1500/3000VDC Isolation • Continuous short circuit protection	B/F_XT-2WR2 • 2 Watts • Unregulated dual/single outputs • 1500/3000VDC Isolation	WRA/B_S-1WR2/ WRE/F_S/P-3WR2 • 4.5-9, 9-18, 18-36, 36-75 VDC Input • 1500/3000VDC Isolation	VRB_LD-15WR3 VRA/B_LD-20WR3 • 9-18, 18-36, 36-75VDC Input • 1500VDC Isolation	VRB_LD-40WHR3 • 18-36, 36-75VDC Input • 1500VDC Isolation • Efficiency up to 91% • With heat sink
	B_XT-W2R2 • 0.25 Watt • Unregulated single output • 1500VDC Isolation • Continuous short circuit protection	IB_XT-W75R3 • 0.75 Watt • Regulated single output • 1500VDC Isolation • Continuous short circuit protection	IB_XT-1WR2 IF_XT-1WR2/R3 • 1 Watt • Regulated single output • 1500/3000VDC Isolation • Continuous short circuit protection	WRB_ST-1WR2/3WR2 WRB_SD-1WR2/3WR2 • 9-18, 18-36VDC input • SMD/DIP Package • 1500VDC Isolation	URE/F/H_P-6WR3 • 9-36, 18-75VDC Input • 3000/6000VDC Isolation	URB_S-6WR3/10WR3 • 9-36VDC Input • Single output • No-load power consumption as low as 0.12W
	A/B/E/F_S-1WR2/R3 G/H_S-1WR2 • 1 Watt • 1500/3000/6000VDC Isolation	B_LS-1WR2/R3 • 1 Watt • 1500VDC Isolation • Continuous short circuit protection	A/B/E/F/G/H_S-2WR2 • 2 Watts • Unregulated dual/single outputs • 1500/3000/6000VDC Isolation	WRA/B_ZP-3WR2 • 4.5-9, 9-18, 18-36, 36-75 VDC Input • 3000VDC Isolation	URB1D_LMD-10WR3/15WR3/20WR3 • 40-160VDC Input • Single output • 2250VDC Isolation	URA/B_LD-20WR3/30WR3 • 9-36, 18-75VDC Input • 1500VDC Isolation • Efficiency up to 90%
SIP	IB_S-W75R3 • 0.75 Watt • 1500/3000VDC Isolation • Continuous short circuit protection	IB_LS-1W/1WR3 IF_S-1W/1WR3 • 1 Watt • 1000/1500VDC Isolation • Continuous short circuit protection	B/F_S-3WR2 • 3 Watts • Unregulated single output • 1500/3000VDC Isolation	URB_MT-3WR3 • 9-36, 18-75VDC Input • 1500VDC Isolation • Efficiency up to 84%	URE/F_LP-10WR3 URF_LP-20WR3 • 9-36, 18-75VDC Input • 3000VDC Isolation • Efficiency up to 88%	VRB_J(M)D/T-6W URB_J(M)D/T-10/15W • 9-36, 18-75VDC/9-18, 18-36VDC Input • 1500VDC Isolation
	F_N-1WR3 • 1 Watt • 3000VDC Isolation • Continuous short circuit protection • International standard pin-out		A/B/E/F_D-2WR2 • 2 Watts • Unregulated dual/single outputs • 1500/3000VDC Isolation	V/URB_J(M)D/T-3W VRA_JMD-3W • 4.5-9, 9-36, 18-36VDC Input • 500VAC/1500VDC Isolation	75 to 200 Watts URF_QB-75W/100W/150W/200WR3 • 9-36, 18-75VDC Input • Efficiency up to 94% • 2250VDC Isolation	
DIP						

Photovoltaic Power Supply

PV10-27C
PV15-29C
PV45-29D
PV50-29D
PV60-27D
PV75-36D

 • 10/15/45/50/60/75 Watts
 • Dual/triple outputs

PV(05-200)-27B

 • 5/10/15/40/120/200 Watts
 • 100-1200VDC input
 • 4000VAC isolation
 • Single output

PV(15-200)-29B

 • 15/40/150/200 Watts
 • 200-1500VDC input
 • 4000VAC isolation
 • Single output

DC/DC Converter for IGBT Driver

QA01/02/03/04

 • ±10% Input
 • Ultra low isolation capacitance
 • 3000VAC Isolation
 • No-load operation allowed

QA01C

 • ±10% Input
 • 3500VAC Isolation
 • Designed for SiC Driver

QAW01/02

 • 9-18, 18-36VDC Input
 • 0.24-4.8 Watts
 • 3000VDC Isolation
 • Output over-voltage Protection

QA152D

 • ±10% Input
 • 3500VAC Isolation
 • Designed for SiC Driver

Non-isolated

K78L-500R3/1000R3

 • Open frame
 • Efficiency up to 95%
 • Ultra low no-load power consumption
 • Short circuit protection

K78T-500R3/1000R3

 • Efficiency up to 95%
 • Low no-load power consumption
 • Short circuit protection

K78-500/1000/2000R3
K78_W-500R3

 • Efficiency up to 96%
 • Pin-out compatible with LM78XX linear regulators
 • Short circuit protection

K78xxM-1000R3

 • Efficiency up to 96%
 • Low no-load power consumption
 • Short circuit protection

K12T-6/10/16A(-N/P)

 • POL power converter
 • Single output
 • Efficiency up to 94%

K78_JT-500R3

 • thickness ≤ 3.5mm
 • Single output
 • Efficiency up to 95%

Railway Power Supply

URB1D_YMD-6WR3
URB1D_LMD-10/15/20WR3
URB_URE1D_LD-20WR3
URF1D_LD-40WR3

 • 6-40 Watts
 • 40-160VDC input
 • Single output
 • 2250/3000VDC Isolation

URF1D_QB-50/75WR3
URF1D_QB-100/150/250WR3

 • 50/75/100/150/250 Watts
 • 43-160VDC Input
 • 3000VAC Isolation
 • Meet EN50155 standard

Optional Mountings

PCB Mounting

DIN-Rail Mounting

Chassis Mounting

For more information, please visit www.mornsun-power.com

MORNSUN®

MORNSUN Power
 Tel: 020-38601850 Fax: 020-38601272
 Email: info@mornsun.cn
www.mornsun-power.com

MORNSUN America, LLC
 Tel: +1 (978) 567 9610 / 293 3923
 Email: info@mornsun.cn
www.mornsunamerica.com
MORNSUN Power GmbH
 Tel: +49 (0) 89 / 693 350 20
 Email: info@mornsunpower.de
www.mornsunpower.de