

AC/ DC Converter

LHE Series			LDE Series	LM Series	LS Series	LI Series
Standard package		Low power consumption	Compact size	Enclosed	DIY type	DIN-Rail package
LHE(05-60)-20B • 5/10/15/20/25/40/60 Watts • 85-264VAC • 3000/4000VAC Isolation • Single output	LHE(05-20)-20A/C/D • 5/10/15/20 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation • Multiple outputs	LH15/25-20BxxMU • 15/25 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation • Meet EN60601-1/ANSI/AAMI ES60601-1(2xMOPP) Standards	LDE(03-60)-20B • 3/5/6/10/15/20/45/60 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation	LM(35-350)-20B LM(35-100)-10C/D • 85-264VAC Input • 35/50/75/100/150/200/350 Watts • Single/Dual/Triple outputs • Isolation up to 4000VAC	LS01/03/05-15B LS05/08/10-13B • 1/3/5/8/10 Watts • 85-305VAC/70-430VDC • 3000VAC Isolation • Efficiency up to 79%	LI(30-100)-20BxxPR2 LI120-20BxxR2 • 30/60/100/120 Watts • 4000VAC Isolation • 85(90)-264VAC
LH05/20-13B • 5/20 Watts • 80-305VAC/100-430VDC • 3000VAC	LHE(10-60)-23B • 10/15/25/40/60 Watts • 80-305VAC/100-430VDC • 4000VAC			LM(35-350)-22B • 165-264VAC Input • 35/50/75/100/150/200/350 Watts • Single outputs • Isolation up to 4000VAC	Three phase AC/DC power supply LS03-16B LS05-26B • 3/5 Watts • 90-528VAC/100-745VDC • 4000VAC Isolation • Output short circuit protection	LO Series Open frame LO(03-65)-10B • 3/5/15/30/45/65 Watts • 85-264VAC • 3000VAC Isolation
LDE02/05/10-23B • 2/5/10 Watts • 85-305VAC/120-430VDC • 4000VAC Isolation	LMF(75-320)-20B • 85-264VAC Input • 75/100/150/200/320 Watts • Active PFC • 4000VAC Isolation	Three phase AC/DC power supply LD10/20-26B • 10/20 Watts • 90-528VAC/100-745VDC • 4000VAC Isolation	LSC15-26M LSC20-26M • 15/20 Watts • 45-528VAC/85-264VAC • 5 years warranty			

Transceiver Module

Transceiver Module With built in isolated DC/DC Converter	
CAN	RS485
TD321/521DCAN TD321/521DCANH • 110 Nodes • Single output • Rate: 5K~1Mbps, 40K~1Mbps • TDx21DCAN: Two-port isolation (3000VDC) • TDx22DCAN: Two-port isolation (2500VDC), Channel isolation (1500VDC)	TD321/521D485(-L) TD321/521D485H(-A/E) • 64~255 Node • Single output • Rate: 0~19.2Kbps/0~500Kbps/ • 0~200Kbps options • Two-port isolation 3000VDC • (input and output are mutually isolated)
TD301/501MCANFD • 110 Nodes • Single output • Rate: 40K~5Mbps • Compact size	TD321/521S485(-L) • 64 Nodes • Compact size, SMD Package • Rate: 0~19.2Kbps • 2500/3000VDC Isolation
TD301/501CANHE • 110 Nodes • Single output • Rate: 20K~1Mbps • High surge protective type	TD322/522D485H-A • 32 Nodes • Dual outputs • Rate: 0~120Kbps
TD321/521SCAN • 110 Nodes • Compact size, SMD package • Rate: 5K~1Mbps • 3000VDC Isolation	TD331/531S485 TD331/531S485H(-A/E) • Small SMD12 size • Rate: up to 500Kbps
TD322/522DCAN • 110 Nodes • Dual outputs • Rate: 40K~1Mbps	RS232 TD531/331S232H • Small SMD12 size • Rate: 115200bps • Meet EIA/TIA-232-F standard
TD331/531SCANH/FD • Small SMD12 size • Rate: 5Mbps • 110 Nodes	

Automotive Power Supply	
 CF0505XT-1WR3 CFB0505X-1WR3 • 1 Watt • 3500/4200VDC Isolation • Continuous short-circuit protection • EN62368 approved	CVRC1215JD-6WR3 • 6 Watts • 3000VDC Isolation • Efficiency up to 82% • EN62368 approved

Build you own DC/DC converter With our ICs and transformers

ICs & Transformers	
SCM1201ATA • Control IC for DC/DC converter • Power: ≤1W • 4.5-8V input voltage • SOT-23-6 package	TTB05xx-1T • DC/DC transformer • Power: ≤1W • Vin: 4.5-5.5VDC • Vout: 5VDC/9VDC • SMD package • 3.6mm low profile

Low profile: 3.6mm

DC/DC CONVERTER

Recommended

For more information, please visit www.mornsun-power.com



mornsun website

MORNSUN®

SOLVE YOUR POWER PROBLEM
www.mornsun-power.com
 Facebook/Linkedin: Mornsun Power