

offering users industry-leading output power and receiver sensitivity.

Dialog Semiconductor

www.dialog-semiconductor.com

Battery protector

Littelfuse has announced the launch of ITV series, a three-terminal, surface-mountable li-ion battery protector, designed to guard against the damage caused by both overcurrent and overcharging. The innovative design provides fast response and reliable performance to interrupt the charging or discharging circuit before the battery pack becomes overcharged or overheated.

The ITV series helps to solve customer applications requiring current ratings from 12A to 45A. An embedded fuse element cuts off the circuit when overcurrent issues occur. A heater element, directly embedded under the fuse element, generates enough heat to blow the fuse once overcharging is detected by IC or FET.

The ITV series battery protectors are now available in five compact and surface-mount packages in current ratings of 12A, 15A, 30A and 45A.

Littelfuse

www.littelfuse.com

TEST & MEASUREMENT

Oscilloscope

Keysight Technologies has launched a new and enhanced family of oscilloscopes that has



up to 6GHz of bandwidth and 16GSa/s across eight channels. The MXR-series is an upgrade from previous versions in terms of ADC resolution. It also includes eight powerful instruments into one: real-time spectrum analyser (RTSA), oscilloscope, digital voltmeter (DVM), waveform generator, Bode plotter, counter, protocol analyser, and logic analyser.

The MXR series is equipped with fault hunter software, which automatically detects and captures signal issues with just two clicks, comparing them over time. This results in rapid problem

resolution for troubleshooting irregular, random, or spurious signals. The Pathwave Infiniium offline software allows remote access to the oscilloscope, enabling engineers to do extensive analysis and data manipulation of measurements from anywhere.

The series is offered in six models ranging from 500MHz to 6GHz with both 4 and 8 channels. It helps engineers to demodulate, analyse, and perform advanced analysis on complex signals for reliable measurements.

Keysight

www.keysight.com

Phase noise analyser

To help engineers and scientists make accurate measurements of frequency signals generated for 5G networks, data centres, commercial and military aircraft systems, space vehicles, communication satellites, and metrology applications, Microchip Technology has announced the new 53100A phase noise analyser.



This phase noise test instrument is capable of measuring radio frequency (RF) signals up to 200MHz. It is also capable of rapidly acquiring frequency signals and characterising the phase noise, jitter, Allan deviation (ADEV), and time deviation (TDEV) precisely within minutes.

The 53100A phase noise analyser enables a variety of configurations by allowing up to three separate devices to be tested simultaneously using a single reference, thus enabling higher capacity for stability measurements. It provides backward compatibility with Microchip's 51xxA test sets' command and data stream, which eliminates the need to redesign existing automated test equipment (ATE) infrastructure.

Microchip Technology

www.microchip.com

Pulse system source meter

Tektronix has announced the new 2601B-PULSE system source meter 10µs pulser/SMU instrument that integrates a high-speed current pulse with DC source and measurement functionalities in a single instrument. The

new system incorporates pulse meter technology for sourcing current pulses from 10µsec to 500µsec at 10A and 10V without manually tuning the output to match device impedance up to 3µH. This ensures that the current pulse has no overshoot or ringing, thus reducing device self-heating, which can result in erroneous measurements and potential damage to the test equipment. This results in fast rise time, accurate pulse output, and high fidelity.



The 2601B-PULSE system source meter simplifies the complications of testing vertical-cavity surface-emitting lasers (VCSELs), which are mission-critical for automotive light detection and ranging (LIDAR) applications. The instrument is ideal for testing VCSELs and LEDs, semiconductor device characterisation, fault power management testing, surge protection testing, and more.

Tektronix

www.in.tek.com

Signal generator

Keeping up with the excellent offering of test and measurement equipment, Siglent presents the new SSG5000X series of RF signal generators, an upgrade of the previous SSG3000X series in terms of the higher output frequency range.



They have a frequency range from 9kHz up to 4GHz or 6GHz, and feature industry-leading performance in phase noise, spectral purity, bandwidth, EVM, and output power. The internal IQ modulation generator and waveform playback function cover the most important RF band for digital wireless communications and include standard waveform files. The series is available in four variants: SSG5040X, SSG5060X, SSG5040X-V, and SSG5060X-V.

With its powerful functions and wide frequency range, SSG5000X has abundant application fields, such as receiver tests, amplifier tests, IP3 measurement, and radar and digital modulation tests, spur and harmonics measurement, ACPR tests, and cable loss compensation.

Siglent

www.siglent.com