

infrastructure, transmission, precision instrumentation, broadcasting, utility metering infrastructure, and more.

The company states that the OX7000 Series covers a frequency range from 5MHz to 40MHz with a power supply voltage of 3.3V at 150mA steady state. The OX7000 Series OCXO combines ultra-small size with an ultra-reliable frequency stability of ± 10 ppb.

Housed in a hermetically sealed package and with dimensions at 9mm x 7mm for improved reliability, the OX7000 series offers a quick warm-up time of three minutes, low phase noise, and HCMOS output levels.

Raltron

www.raltron.com

Power-saving IC

Here's an integrated zero-cross detection IC series that is optimised for home appliances such as vacuum cleaners, washing machines, and air-conditioners.

The integrated zero-cross detection IC, launched by ROHM, provides designers with a turn-key zero-cross detector,



eliminating any complex design using discrete components. Additionally, this integrated

solution does not use a photo-coupler. Therefore it further reduces standby current consumption and increases long-term reliability, claims the company.

The BM1Zxxx FJ series reduces standby power consumption of the zero-cross circuit to just 0.01W while continuously powering the system.

ROHM

www.rohm.com

Low-power microcontroller

STMicroelectronics has added a QFN48 package to its STM32WLE5 wireless System-on-Chip (SoC) portfolio, bringing the device's extensive feature integration, power efficiency, and multi-modulation flexibility to a wider variety of industrial wireless applications.

The STM32WLE5 combines the ultra-low-power microcontroller technology of STM32L4 and Semtech's

SX126x sub-GHz radio IP for fulfilling worldwide local radio-equipment regulations.

Its unique single-silicon-die integration helps save bill-of-materials (BOM) costs and simplifies the design of connected, smart devices



for applications involving metering, city management, agriculture, retail, logistics, smart buildings, and environmental management.

STMicroelectronics

www.st.com

Position sensor

TDK Corporation has expanded its Micronas masterHAL sensor family with the inclusion of HAL 3970, a new stray-field robust 3D HAL position sensor. The



sensor has highly accurate angular detection from 0 degrees to 360 degrees and linear position detection and uses short

PWM code frames (SPC) to transmit the calculated position information, making it suitable for automotive and industrial applications.

SPC is an enhancement of the standard SENT protocol according to SAE J2716. It enables data to be transmitted based on a trigger pulse sent by an external ECU and supports point-to-point connections as well as a single-wire bus mode with up to four sensors.

As per the company's press release, HAL 3970 uses a special array of Hall plates for high-accuracy measurement of vertical and horizontal magnetic-field components. Due to the sophisticated arrangement of these Hall plates, the sensor detects angles up to 360 degrees and suppresses external magnetic stray fields.

TDK Corporation

www.tdk.com

Bluetooth module

u-blox has announced the launch of the NORA-B1 Bluetooth module. Based on Nordic Semiconductor's latest nRF5340 Bluetooth low energy chipset (the first to host a powerful Arm Cortex M33

dual-core MCU), the NORA-B1 meets the needs of applications in areas such as industrial, medical, smart building, and smart city markets.

The company claims that NORA-B1 can handle performance-oriented applications and even drive a display without requiring an external host processor, thus enabling engineers to get the maximum value out of a single component.

With a low-power-optimised core dedicated to managing network connectivity and a second high-performance core exclusively running the device application, NORA-B1 enables smooth and uninterrupted operation with minimal processing latency.

u-blox

www.u-blox.com

High-performance integrated circuit

Power Integrations has announced the inclusion of a new member of the LYTSwitch-6 family of safety-isolated LED drivers for smart lighting applications—the LYT6078C. It



uses the company's PowiGaN gallium nitride (GaN) technology to deliver efficiency and performance benefits.

The PowiGaN-based LYT6078C IC incorporates a 750V power switch and delivers flicker-free output up to 90W, with other members of the family providing up to 110W. By including both the PFC stage and LYTSwitch-6 LED driver, the system attains an efficiency exceeding ninety per cent.

Housed in the miniature InSOP-24 surface-mount package, LYTSwitch-6 ICs are protected by an advanced thermal fold-back system.

Power Integrations

www.power.com

TEST & MEASUREMENT SOLUTIONS

Wafer probe system

FormFactor has launched CM300xi-ULN, a 300mm wafer probe system designed for highly accurate testing of flicker