

**Once
you stop
learning,
you start
dying.**

—Albert Einstein

**Amaze
Yourself!**

Read Electronics For You

You'll realise how much you
didn't know, and didn't
know that you didn't know!

To Subscribe:

<http://subscribe.efy.in>

Scan This Code



Automotive software

In order to quicken the prototyping of new automotive solutions, STMicroelectronics has introduced a new automotive development platform—the AutoDevKit. It provides huge flexibility in design for empowering designers to address new challenges during the development phase of a new electronic module for an automotive application, thus allowing rapid prototyping for a faster time-to-market.

The foundation of the AutoDevKit comprises a wide variety of hardware and software support, making the entire solution follow a 'Lego-like' approach where a variety of building blocks can be assembled in an application.

The flexibility to reuse existing hardware as well as applications developed with AutoDevKit allows removal of some building blocks (that had been used in previously released applications) and replace them with new ones.

STMicroelectronics

www.st.com

SENSORS

Digital magnetic sensor

Coto Technology, a provider of relays for switching and magnetic sensing solutions, has introduced the new RedRock RR122-1A22-511/512 wafer-based TMR (Tunneling Magnetoresistance) digital omnipolar sensors.

The RR122-1A22 series features an operating frequency of 10Hz, a voltage supply range of +1.7V to +5.5V, and an extremely strong magnetic sensitivity. With a low current drain (75nA) for an active magnetic sensor, the series is suited for performing 'wake up' or 'turn on' function for battery operated and power-sensitive applications.

The operating temperature range is from -40 degrees Celsius to +85 degrees Celsius. An upgraded version providing high temperatures of up to +125 degrees Celsius is also available.

Coto Technology

www.cotorelay.com



Optical sensor

Maxim Integrated has introduced MAXM86146, a dual-photodetector optical sensor solution. The sensor module includes built-in algorithms for heart rate and oxygen saturation (SpO₂) monitoring as well as advanced activity classification.



Its small size and ease of design allow innovative biosensing features

in less space and support the rapid development of accurate and continuous health-monitoring devices.

The MAXM86146 offers wearable product designers the ability to achieve a 45 per cent thinner optical design versus a discrete approach. Additionally, the module comes with biosensing algorithms that are verified by strict medical standards for measuring vital signs.

Maxim Integrated

www.maximintegrated.com

MISCELLANEOUS

Power Supply

RECOM has introduced a highly compact 230W innovative baseplate-cooled power supply for medical, household, industrial, and ITE applications.

The new, compact RACM230-G series power supplies from RECOM support up to 160W continuous output power and 230W for several seconds for loads with peak demands, without fan cooling. With forced air, depending on the model, line input, and ambient temperature, 230W is available continuously.



Outputs available are 12V, 24V, 36V, 48V, and 54V nominal with conversion efficiency up to 92 per cent and an operating temperature range of -40 degrees Celsius to +80 degrees Celsius.

RECOM, www.recom-power.com