

PRACTICE-2

1--

/*WAP to convert a given valid parenthesized infix arithmetic expression to prefix expression. The expression consists of single character operands and the binary operators + (plus), - (minus), * (multiply) and / (divide).
*/

```
#include<stdio.h>
#include<string.h>
int F(char symbol)
{
    switch(symbol)
    {
        case '+':
        case '-': return 1;
        case '*':
        case '/':return 3;
        case '^':
        case '$':return 6;
        case '(':return 9;
        case '#':return 0;
        default:return 8;
    }
}
int G(char symbol)
{
    switch(symbol)
    {
        case '+':
        case '-': return 2;
        case '*':
        case '/':return 4;
        case '^':
        case '$':return 5;
        case '(':return 0;
        case ')':return 9;
        default:return 7;
    }
}
void infix_prefix(char infix[],char prefix[])
{
    int top,i,j;
```

```

        char s[30],symbol;
        top=-1;
        s[++top]='#';
        j=0;
        strrev(infix);
        for(i=0;i<strlen(infix);i++)
        {
            symbol = infix[i];
            while(F(s[top])>G(symbol))
            {
                prefix[j]=s[top--];
                j++;
            }
            if(F(s[top])!=G(symbol))
                s[++top]=symbol;
            else
                top--;
        }
        while(s[top]!='#')
        {
            prefix[j++]=s[top--];
        }
        prefix[j]='\0';
        strrev(prefix);
    }
    int main()
    {
        char infix[20];
        char prefix[20];
        printf("Enter the valid infix expression\n");
        scanf("%s",infix);
        infix_prefix(infix,prefix);
        printf("The prefix expression is:\n");
        printf("%s\n",prefix);
    }

```

```

D:\coding files\CodeBlocks\c-programming\DS lab>p2-1
Enter the valid infix expression
A*B+C/D
The postfix expression is:
+*AB/CD
D:\coding files\CodeBlocks\c-programming\DS lab>

```

2--

/*WAP to demonstrate the Evaluation of postfix expression.*/

```


#include<stdio.h>
#include<math.h>
#include<string.h>
#include<ctype.h>
double compute(char symbol,double op1,double op2)
{
    switch(symbol)
    {
        case'+': return op1+op2;
        case'-': return op1-op2;
        case'*': return op1*op2;
        case'/': return op1/op2;
        case'$':
        case'^': return pow(op1,op2);
    }
}
void main()
{
    double s[20];
    double op1,op2;
    float res;
    int top,i;
    char postfix[20],symbol;
    printf("enter the postfix expression \n");
    scanf("%s",postfix);
    top=-1;
    for(i=0;i<strlen(postfix);i++)
    {

```

```

symbol=postfix[i];
if(isdigit(symbol))
s[++top]=symbol-'0';
else
{
    op2=s[top--];
    op1=s[top--];
    res=compute(symbol,op1,op2);
    s[++top]=res;
}
}
res=s[top--];
printf("result= %f\n",res);
}

```



```

D:\coding files\CodeBlocks\c-programming\DS lab>p2-2
enter the postfix expression
1*2+9/3
result=3.000000
D:\coding files\CodeBlocks\c-programming\DS lab>

```

3--

/*WAP to perform factorial of a number using Recursion*/

```


#include <stdio.h>
int fact(int n)
{
    if(n==0)
        return 1;
    else
        return n*fact(n-1);
}
void main()
{
    int n;

```

```

printf("enter the value of n \n");
scanf("%d",&n);
printf("the factorial of %d=%d\n",n,fact(n));
}

```



```

D:\coding files\CodeBlocks\c-programming\DS lab>p2-3
enter the value of n
7
the factorial of 7=5040
D:\coding files\CodeBlocks\c-programming\DS lab>

```


4--

/*WAP to perform GCD of two numbers using Recursion.*/

```

#include <stdio.h>
int gcd(int n, int m);
int main() {
    int n, m;
    printf("Enter two positive integers: ");
    scanf("%d %d", &n, &m);
    printf("G.C.D of %d and %d is %d.", n, m, gcd(n, m));
    return 0;
}
int gcd(int n, int m) {
    if (m != 0)
        return gcd(m, n % m);
    else
        return n;
}

```



```

D:\coding files\CodeBlocks\c-programming\DS lab>p2-4
Enter two positive integers: 8 12
G.C.D of 8 and 12 is 4.
D:\coding files\CodeBlocks\c-programming\DS lab>

```