Date=28/07/2020
Lecture By=Shubham Joshi
Subject ⇒ Sorting-2

| IN PREVIOUS LECTURE **(QUICK RECAP) Date-27/07/2020** | **In Today's Lecture (Overview)** |
|---|---|
| ⇒ Backtracking In python<br>⇒ Question That Are Based on BackTracking<br>⇒ Mcq's<br>⇒ Questions For Self Practice / CC For the Day | Merge Sort In Python<br>Question related Sort Merge<br>Mcqs<br>Questions For Self Practice |

# Merge Sort In Python

Merge Sort is a **Divide and Conquer** algorithm.

It divides the **input array in two halves**, calls itself for the two halves and then merges the two sorted halves.

Time complexity of Merge sort is **n(logn)**

"Click Here" to know more about It

For video Tutorial "Click Here"




# Question related Sort Merge

**Given 2 sorted arrays You Have to merge them using Sort Merge**

**Code**

```
def merge(l1, l2):
        p1 = 0
        p2 = 0

        merged_list = list()
        while p1 < len(l1) and p2 < len(l2):
                if l1[p1] < l2[p2]:
                        merged_list.append(l1[p1])
                        p1 += 1
                else:
                        merged_list.append(l2[p2])
                        p2 += 1
```

```
        while p1 < len(l1):
                merged_list.append(l1[p1])
                p1 += 1

        while p2 < len(l2):
                merged_list.append(l2[p2])
                p2 += 1

def merge(a, s1, e1, s2, e2):
        p1 = s1
        p2 = s2
        temp = list()
        while p1 <= e1 and p2 <= e2:
                if a[p1] < a[p2]:
                        temp.append(a[p1])
                        p1 += 1
                else:
                        temp.append(a[p2])
                        p2 += 1
        while p1 <= e1:
                temp.append(a[p1])
                p1 += 1

        while p2 <= e2:
                temp.append(a[p2])
                p2 += 1

        idx = 0
        while idx < len(temp):
                a[s1 + idx] = temp[idx]
                idx += 1


def mergeSort(a, l, r):
        if l >= r:
                return
        mid = (l + r) // 2
```

```
        mergeSort(a, l, mid)
        mergeSort(a, mid + 1, r)
        merge(a, l, mid, mid + 1, r)

if __name__ == '__main__':
        l = [5,2,1,33,44]        mergeSort(l, 0, len(l) - 1)
        print(l)
```

**Output**

```
E:\Study\Codes>C:/pyt
[1, 2, 5, 33, 44]
```

**We Only Discussed This Topic's One question as this topic is very important**

# Mcqs

**1.What is the worst time complexity of merge sort ?2**

**a.O(n)**

**b.O(nlogn)**

**c.O(1)**

**2.What will be the best time complexity to find intersection of 2 arrays ?**

**a.O(N)**

**b.O(N2)**

**c.O(NLOGN)**

**3.which does merge Works11?2**

**a.divide and conquer**

**b.recursion**

**4.what does extend do in a list ?**

**a.appends another list**

**b.makes it a matrix**

**c.appends an element**

# Questions For Self Practice

**Q1. Implement merge sort on your own and analyze its time complexity.**

**Q2. https://practice.geeksforgeeks.org/problems/merge-two-sorted-arrays/0**

**Q3. https://practice.geeksforgeeks.org/problems/sort-an-array-of-0s-1s-and-2s/0**