

**EXPERIMENT: 1****DATE: 26.07.2024****CREATION OF DATABASE AND DML OPERATIONS**

1. Create MY\_EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

Create table my\_employee(ID number(4),Last\_name varchar (25),First\_name varchar(25),userid varchar(25),salary number(9,2));

Column Name	Data Type	Nullable	Default	Primary Key
ID	NUMBER(4,0)	No	-	-
LAST_NAME	VARCHAR2(25)	Yes	-	-
FIRST_NAME	VARCHAR2(25)	Yes	-	-
USERID	VARCHAR2(25)	Yes	-	-
SALARY	NUMBER(9,2)	Yes	-	-
1 - 5				

2. Add the first and second rows data to MY\_EMPLOYEE table from the following sample data.

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbiri	1100
4	Newman	Chad	Cnewman	750
5	Ropebur	Audrey	aropebur	1550

```

insert into my_employee(Id,Last_name,First_name,userid,salary)
values(1,'patel','Ralph','rpatel',895);

insert into my_employee(Id,Last_name,First_name,userid,salary)
values (2,'dancs','betty','bdancs',860);

```

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860

3. Display the table with values

```

Select *from my_employee

```

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860

4. Populate the next two rows of data from the sample data. Concatenate the first letter of the first\_name with the first seven characters of the last\_name to produce Userid.

```

insert into my_employee(Id,Last_name,First_name,salary)
values (3,'Biri','Ben',1100);

insert into my_employee(Id,Last_name,First_name,salary)
values (4,'Newman','chad',750);

update my_employee
set userid= SUBSTR(first_name, 1, 1) || SUBSTR(last_name,1, 7)

```

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbri	1100
4	Newman	chad	Cnewman	750

4 rows returned in 0.01 seconds

[Download](#)

5. Delete Betty dancs from MY \_EMPLOYEE table.
6. delete from my\_employee where first\_name='Betty';

---

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
3	Biri	Ben	bbri	1100
4	Newman	chad	Cnewman	750

7. Empty the fourth row of the emp table.

delete from my\_employee where ID=4;

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
3	Biri	Ben	bbri	1100

8. Make the data additions permanent.

commit;

9. Change the last name of employee 3 to Drexler.

update my\_employee

set last\_name='Drexler' where ID=3;

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	895
3	Drexler	Ben	bbri	1100

10. Change the salary to 1000 for all the employees with a salary less than 900.

update my\_employee

set salary=1000 where salary<900;

ID	LAST_NAME	FIRST_NAME	USERID	SALARY
1	Patel	Ralph	rpatel	1000
3	Drexler	Ben	bbri	1100

**CSE(CYBER SECURITY)**