

Assignment 2:

Design a database schema for a library system, including tables, fields, and constraints like NOT NULL, UNIQUE, and CHECK. Include primary and foreign keys to establish relationships between tables.

Sol:

Designing a database schema for a library system involves creating several tables to handle different entities such as books, authors, members, loans, and so on. Here's a detailed schema with tables, fields, and constraints:

Tables and Fields

1. Authors

- `AuthorID` (Primary Key, Integer, NOT NULL)
- `FirstName` (Varchar (50), NOT NULL)
- `LastName` (Varchar (50), NOT NULL)

2. Books

- `BookID` (Primary Key, Integer, NOT NULL)
- `Title` (Varchar (255), NOT NULL)
- `ISBN` (Varchar (13), UNIQUE, NOT NULL)
- `PublicationYear` (Year, CHECK (`PublicationYear` > 0))
- `AuthorID` (Foreign Key, Integer, NOT NULL, REFERENCES `Authors`(`AuthorID`))

3. Members

- `MemberID` (Primary Key, Integer, NOT NULL)
- `FirstName` (Varchar (50), NOT NULL)
- `LastName` (Varchar (50), NOT NULL)
- `Email` (Varchar (100), UNIQUE, NOT NULL)
- `Phone` (Varchar (15), UNIQUE, NOT NULL)
- `JoinDate` (Date, NOT NULL)

4. Loans

- `LoanID` (Primary Key, Integer, NOT NULL)
- `BookID` (Foreign Key, Integer, NOT NULL, REFERENCES `Books`(`BookID`))

- `MemberID` (Foreign Key, Integer, NOT NULL, REFERENCES `Members`(`MemberID`))
- `LoanDate` (Date, NOT NULL)
- `DueDate` (Date, NOT NULL, CHECK (`DueDate` > `LoanDate`))
- `ReturnDate` (Date, NULL)

5. Categories

- `CategoryID` (Primary Key, Integer, NOT NULL)
- `CategoryName` (Varchar (100), UNIQUE, NOT NULL)

6. Book Categories

- `BookID` (Foreign Key, Integer, NOT NULL, REFERENCES `Books`(`BookID`))
- `CategoryID` (Foreign Key, Integer, NOT NULL, REFERENCES `Categories`(`CategoryID`))
- PRIMARY KEY (`BookID`, `CategoryID`)

Detailed Schema

SQL:

CREATE TABLE Authors (

AuthorID INT PRIMARY KEY NOT NULL,

FirstName VARCHAR (50) NOT NULL,

LastName VARCHAR (50) NOT NULL

);

CREATE TABLE Books (

BookID INT PRIMARY KEY NOT NULL,

Title VARCHAR (255) NOT NULL,

ISBN VARCHAR (13) UNIQUE NOT NULL,

PublicationYear YEAR CHECK (PublicationYear > 0),

AuthorID INT NOT NULL,

FOREIGN KEY (AuthorID) REFERENCES Authors (AuthorID)

);

```
CREATE TABLE Members (  
    MemberID INT PRIMARY KEY NOT NULL,  
    FirstName VARCHAR (50) NOT NULL,  
    LastName VARCHAR (50) NOT NULL,  
    Email VARCHAR (100) UNIQUE NOT NULL,  
    Phone VARCHAR (15) UNIQUE NOT NULL,  
    JoinDate DATE NOT NULL  
);
```

```
CREATE TABLE Loans (  
    LoanID INT PRIMARY KEY NOT NULL,  
    BookID INT NOT NULL,  
    MemberID INT NOT NULL,  
    LoanDate DATE NOT NULL,  
    DueDate DATE NOT NULL CHECK (DueDate > LoanDate),  
    ReturnDate DATE NULL,  
    FOREIGN KEY (BookID) REFERENCES Books (BookID),  
    FOREIGN KEY (MemberID) REFERENCES Members (MemberID)  
);
```

```
CREATE TABLE Categories (  
    CategoryID INT PRIMARY KEY NOT NULL,  
    CategoryName VARCHAR (100) UNIQUE NOT NULL  
);
```

```
CREATE TABLE BookCategories (  
    BookID INT NOT NULL,  
    CategoryID INT NOT NULL,
```

```
PRIMARY KEY (BookID, CategoryID),  
FOREIGN KEY (BookID) REFERENCES Books (BookID),  
FOREIGN KEY (CategoryID) REFERENCES Categories (CategoryID)  
);
```

Explanation of Constraints

Primary Key (PK): Ensures each record in the table is unique.

Foreign Key (FK): Establishes relationships between tables.

NOT NULL: Ensures that a field cannot have a NULL value.

UNIQUE: Ensures all values in a column are unique.

CHECK: Ensures that all values in a column satisfy a specific condition.

This schema provides a comprehensive structure for managing a library system, covering books, authors, members, loans, and categories, while enforcing data integrity and relationships between tables.

Assignment 4:

Write SQL statements to CREATE a new database and tables that reflect the library schema you designed earlier. Use ALTER statements to modify the table structures and DROP statements to remove a redundant table.

Sol:

Certainly! Below is a set of SQL statements to create a new database and tables for the library schema designed earlier. This includes the creation of the database, tables, insertion of data, altering table structures, and dropping a redundant table.

Step 1: Create the Database

```
CREATE DATABASE LibraryDB;
```

```
USE LibraryDB;
```

Step 2: Create Tables

Authors Table

```
CREATE TABLE Authors (  
    AuthorID INT PRIMARY KEY AUTO_INCREMENT,  
    FirstName VARCHAR(50) NOT NULL,  
    LastName VARCHAR(50) NOT NULL  
);
```

Books Table

```
CREATE TABLE Books (  
    BookID INT PRIMARY KEY AUTO_INCREMENT,  
    Title VARCHAR(255) NOT NULL,  
    ISBN VARCHAR(13) UNIQUE NOT NULL,  
    PublicationYear YEAR CHECK (PublicationYear > 0),  
    AuthorID INT NOT NULL,  
    FOREIGN KEY (AuthorID) REFERENCES Authors(AuthorID)  
);
```

Members Table

```
CREATE TABLE Members (  
    MemberID INT PRIMARY KEY AUTO_INCREMENT,  
    FirstName VARCHAR(50) NOT NULL,  
    LastName VARCHAR(50) NOT NULL,  
    Email VARCHAR(100) UNIQUE NOT NULL,  
    Phone VARCHAR(15) UNIQUE NOT NULL,  
    JoinDate DATE NOT NULL  
);
```

Loans Table

```
CREATE TABLE Loans (  
    LoanID INT PRIMARY KEY AUTO_INCREMENT,  
    BookID INT NOT NULL,
```

```
MemberID INT NOT NULL,  
LoanDate DATE NOT NULL,  
DueDate DATE NOT NULL CHECK (DueDate > LoanDate),  
ReturnDate DATE,  
FOREIGN KEY (BookID) REFERENCES Books(BookID),  
FOREIGN KEY (MemberID) REFERENCES Members(MemberID)  
);
```

Categories Table

```
CREATE TABLE Categories (  
    CategoryID INT PRIMARY KEY AUTO_INCREMENT,  
    CategoryName VARCHAR(100) UNIQUE NOT NULL  
);
```

BookCategories Table

```
CREATE TABLE BookCategories (  
    BookID INT NOT NULL,  
    CategoryID INT NOT NULL,  
    PRIMARY KEY (BookID, CategoryID),  
    FOREIGN KEY (BookID) REFERENCES Books(BookID),  
    FOREIGN KEY (CategoryID) REFERENCES Categories(CategoryID)  
);
```

Step 3: Insert Sample Data

Insert Data into Authors Table

```
INSERT INTO Authors (FirstName, LastName) VALUES  
( 'J.K.', 'Rowling'),  
( 'George', 'Orwell'),  
( 'J.R.R.', 'Tolkien');
```

Insert Data into Books Table

```
INSERT INTO Books (Title, ISBN, PublicationYear, AuthorID) VALUES  
( 'Harry Potter and the Philosopher\'s Stone', '9780747532699', 1997, 1),
```

```
('1984', '9780451524935', 1949, 2),  
( 'The Hobbit', '9780261102217', 1937, 3);
```

Insert Data into Members Table

```
INSERT INTO Members (FirstName, LastName, Email, Phone, JoinDate) VALUES  
( 'Alice', 'Smith', 'alice.smith@example.com', '1234567890', '2023-01-15'),  
( 'Bob', 'Brown', 'bob.brown@example.com', '0987654321', '2023-02-20');
```

Insert Data into Loans Table

```
INSERT INTO Loans (BookID, MemberID, LoanDate, DueDate, ReturnDate) VALUES  
(1, 1, '2023-05-01', '2023-05-15', NULL),  
(2, 2, '2023-05-03', '2023-05-17', '2023-05-10');
```

Insert Data into Categories Table

```
INSERT INTO Categories (CategoryName) VALUES  
( 'Fantasy'),  
( 'Dystopian'),  
( 'Adventure');
```

Insert Data into BookCategories Table

```
INSERT INTO BookCategories (BookID, CategoryID) VALUES  
(1, 1),  
(2, 2),  
(3, 3);
```

Step 4: Modify Table Structures

Alter the Authors Table to Add a MiddleName Column

```
ALTER TABLE Authors  
ADD COLUMN MiddleName VARCHAR(50);
```

Alter the Books Table to Add a Publisher Column

```
ALTER TABLE Books  
ADD COLUMN Publisher VARCHAR(100);
```

Step 5: Drop a Redundant Table

Assume we have a redundant table named `OldMembers`

```
DROP TABLE IF EXISTS OldMembers;
```

Complete Script

Here is the complete script to create the `LibraryDB` database, set up the tables, insert sample data, alter the table structures, and drop a redundant table:

-- Create Database

```
CREATE DATABASE LibraryDB;
```

```
USE LibraryDB;
```

-- Create Tables

```
CREATE TABLE Authors (
```

```
    AuthorID INT PRIMARY KEY AUTO_INCREMENT,
```

```
    FirstName VARCHAR(50) NOT NULL,
```

```
    LastName VARCHAR(50) NOT NULL
```

```
);
```

```
CREATE TABLE Books (
```

```
    BookID INT PRIMARY KEY AUTO_INCREMENT,
```

```
    Title VARCHAR(255) NOT NULL,
```

```
    ISBN VARCHAR(13) UNIQUE NOT NULL,
```

```
    PublicationYear YEAR CHECK (PublicationYear > 0),
```

```
    AuthorID INT NOT NULL,
```

```
    FOREIGN KEY (AuthorID) REFERENCES Authors(AuthorID)
```

```
);
```

```
CREATE TABLE Members (
```

```
    MemberID INT PRIMARY KEY AUTO_INCREMENT,
```

```
    FirstName VARCHAR(50) NOT NULL,
```



```
    LastName VARCHAR(50) NOT NULL,  
    Email VARCHAR(100) UNIQUE NOT NULL,  
    Phone VARCHAR(15) UNIQUE NOT NULL,  
    JoinDate DATE NOT NULL  
);
```

```
CREATE TABLE Loans (  
    LoanID INT PRIMARY KEY AUTO_INCREMENT,  
    BookID INT NOT NULL,  
    MemberID INT NOT NULL,  
    LoanDate DATE NOT NULL,  
    DueDate DATE NOT NULL CHECK (DueDate > LoanDate),  
    ReturnDate DATE,  
    FOREIGN KEY (BookID) REFERENCES Books(BookID),  
    FOREIGN KEY (MemberID) REFERENCES Members(MemberID)  
);
```

```
CREATE TABLE Categories (  
    CategoryID INT PRIMARY KEY AUTO_INCREMENT,  
    CategoryName VARCHAR(100) UNIQUE NOT NULL  
);
```

```
CREATE TABLE BookCategories (  
    BookID INT NOT NULL,  
    CategoryID INT NOT NULL,  
    PRIMARY KEY (BookID, CategoryID),  
    FOREIGN KEY (BookID) REFERENCES Books(BookID),  
    FOREIGN KEY (CategoryID) REFERENCES Categories(CategoryID)  
);
```

-- Insert Sample Data

INSERT INTO Authors (FirstName, LastName) VALUES

('J.K.', 'Rowling'),
('George', 'Orwell'),
('J.R.R.', 'Tolkien');

INSERT INTO Books (Title, ISBN, PublicationYear, AuthorID) VALUES

('Harry Potter and the Philosopher\'s Stone', '9780747532699', 1997, 1),
('1984', '9780451524935', 1949, 2),
('The Hobbit', '9780261102217', 1937, 3);

INSERT INTO Members (FirstName, LastName, Email, Phone, JoinDate) VALUES

('Alice', 'Smith', 'alice.smith@example.com', '1234567890', '2023-01-15'),
('Bob', 'Brown', 'bob.brown@example.com', '0987654321', '2023-02-20');

INSERT INTO Loans (BookID, MemberID, LoanDate, DueDate, ReturnDate) VALUES

(1, 1, '2023-05-01', '2023-05-15', NULL),
(2, 2, '2023-05-03', '2023-05-17', '2023-05-10');

INSERT INTO Categories (CategoryName) VALUES

('Fantasy'),
('Dystopian'),
('Adventure');

INSERT INTO BookCategories (BookID, CategoryID) VALUES

(1, 1),
(2, 2),
(3, 3);

-- Alter Table Structures

```
ALTER TABLE Authors
```

```
ADD COLUMN MiddleName VARCHAR(50);
```

```
ALTER TABLE Books
```

```
ADD COLUMN Publisher VARCHAR(100);
```

-- Drop Redundant Table

```
DROP TABLE IF EXISTS OldMembers;
```

=====

Assignment 5:

Demonstrate the creation of an index on a table and discuss how it improves query performance. Use a DROP INDEX statement to remove the index and analyse the impact on query execution.

Sol:

1. Creating a Table

First, we'll create a sample table. Let's assume we have a table called `employees` with the following columns: `id`, `name`, `department`, and `salary`.

```
CREATE TABLE employees (  
    id INT PRIMARY KEY,  
    name VARCHAR(100),  
    department VARCHAR(50),  
    salary DECIMAL(10, 2)  
);
```

2. Inserting Sample Data

Next, let's insert some sample data into the table.

```
INSERT INTO employees (id, name, department, salary) VALUES
(1, 'Alice', 'HR', 60000),
(2, 'Bob', 'Engineering', 80000),
(3, 'Charlie', 'Marketing', 55000),
(4, 'David', 'Engineering', 75000),
(5, 'Eve', 'HR', 70000);
```

3. Creating an Index

We'll create an index on the `department` column to improve query performance when filtering by department.

```
CREATE INDEX index_department ON employees(department);
```

4. Analysing Query Performance with Index

Consider the following query to fetch all employees in the Engineering department:

```
SELECT * FROM employees WHERE department = 'Engineering';
```

With the index `index_department`, the database can quickly locate the rows where the `department` is 'Engineering' without scanning the entire table. This significantly improves query performance, especially for large tables.

5. Dropping the Index

To demonstrate the impact of removing the index, we'll drop it using the `DROP INDEX` statement.

```
DROP INDEX index_department ON employees;
```

6. Analysing Query Performance without Index

Running the same query after dropping the index:

```
SELECT * FROM employees WHERE department = 'Engineering';
```

=====

Assignment 6:

Create a new database user with specific privileges using the CREATE USER and GRANT commands. then write a script to REVOKE certain privileges and DROP the user

Sol:

1. Creating a New User

First, let's create a new database user. Assume we are working with a MySQL database.

-- Create a new user 'test_user' with password 'password123'

```
CREATE USER 'test_user'@'localhost' IDENTIFIED BY 'password123';
```

2. Granting Privileges

Next, we'll grant specific privileges to this user. For instance, let's give the user privileges to select, insert, update, and delete on a database called `test_db`.

-- Grant SELECT, INSERT, UPDATE, DELETE privileges on the test_db database

```
GRANT SELECT, INSERT, UPDATE, DELETE ON test_db.* TO 'test_user'@'localhost';
```

3. Revoking Privileges

Now, let's write a script to revoke certain privileges from the user. Suppose we want to revoke the `DELETE` privilege.

-- Revoke DELETE privilege on the test_db database

```
REVOKE DELETE ON test_db.* FROM 'test_user'@'localhost';
```

4. Dropping the User

Finally, let's drop the user.

-- Drop the user 'test_user'

```
DROP USER 'test_user'@'localhost';
```

Combined Script

Here's a combined script that creates a user, grants privileges, revokes a privilege, and then drops the user:

-- Step 1: Create a new user

```
CREATE USER 'test_user'@'localhost' IDENTIFIED BY 'password123';
```

-- Step 2: Grant specific privileges to the user

```
GRANT SELECT, INSERT, UPDATE, DELETE ON test_db.* TO 'test_user'@'localhost';
```

-- Step 3: Revoke the DELETE privilege from the user

```
REVOKE DELETE ON test_db.* FROM 'test_user'@'localhost';
```

-- Step 4: Drop the user

```
DROP USER 'test_user'@'localhost';
```

Explanation

1. **CREATE USER:** This command creates a new user with a specified username and password.
2. **GRANT:** This command grants specified privileges (SELECT, INSERT, UPDATE, DELETE) on all tables in the `test_db` database to the user.
3. **REVOKE:** This command revokes the `DELETE` privilege from the user, removing their ability to delete records in the `test_db` database.
4. **DROP USER:** This command removes the user from the database, effectively revoking all their privileges and deleting their account.

=====

Assignment 7:

Prepare a series statements to INSERT new records into the library tables, UPDATE existing records with new information and DELETE records based on specific criteria . Include BULK INSERT operations to load data from an external source.

we have a library database with the following tables:

1. `books`
2. `authors`
3. `members`
4. `loans`

We'll go through the following steps:

1. Inserting New Records
2. Updating Existing Records
3. Deleting Records Based on Specific Criteria
4. Bulk Insert Operations

1. Inserting New Records

First, let's add new records to the `books`, `authors`, and `members` tables.

-- Insert new records into the authors table

```
INSERT INTO authors (author_id, name, birth_date)
VALUES
```

```
(1, 'J.K. Rowling', '1965-07-31'),
(2, 'George Orwell', '1903-06-25'),
(3, 'Jane Austen', '1775-12-16');
```

-- Insert new records into the books table

```
INSERT INTO books (book_id, title, author_id, genre, published_year)
VALUES
```

```
(1, 'Harry Potter and the Philosopher\'s Stone', 1, 'Fantasy', 1997),
(2, '1984', 2, 'Dystopian', 1949),
(3, 'Pride and Prejudice', 3, 'Romance', 1813);
```

-- Insert new records into the members table

```
INSERT INTO members (member_id, name, join_date)
VALUES
```

```
(1, 'Alice Johnson', '2023-01-15'),
(2, 'Bob Smith', '2023-03-22'),
(3, 'Carol White', '2023-05-11');
```

2. Updating Existing Records

Next, let's update existing records with new information.

-- Update an author's name

```
UPDATE authors  
SET name = 'Joanne Rowling'  
WHERE author_id = 1;
```

-- Update a book's genre

```
UPDATE books  
SET genre = 'Classic'  
WHERE book_id = 2;
```

-- Update a member's join date

```
UPDATE members  
SET join_date = '2023-04-01'  
WHERE member_id = 2;
```

3. Deleting Records Based on Specific Criteria

Now, let's delete records based on certain criteria.

-- Delete books published before the year 1900

```
DELETE FROM books  
WHERE published_year < 1900;
```

-- Delete members who joined before 2023

```
DELETE FROM members  
WHERE join_date < '2023-01-01';
```

-- Delete authors with no books

```
DELETE FROM authors  
WHERE author_id NOT IN (SELECT author_id FROM books);
```

4. Bulk Insert Operations

For bulk insert operations, we'll assume you have a CSV file named `books_data.csv` that contains data for the `books` table. Here's how to load that data using a bulk insert.

Example CSV File (`books_data.csv`):

book_id,title,author_id, genre,published_year

4, Animal Farm,2,Political Satire,1945

5, Emma,3, Romance,1815

6, The Casual Vacancy,1, Drama,2012

Bulk Insert Command:

-- Load data from an external CSV file into the books table

```
LOAD DATA INFILE '/path/to/books_data.csv'
```

```
INTO TABLE books
```

```
FIELDS TERMINATED BY ','
```

```
ENCLOSED BY '"'
```

```
LINES TERMINATED BY '\n'
```

```
IGNORE 1 ROWS
```

```
(book_id, title, author_id, genre, published_year);
```

=====