Technical Data Sheet

3mm Infrared LED , T-1

IR204-A



Features

- High reliability
- High radiant intensity
- Peak wavelength λp=940nm
- 2.54mm Lead spacing
- Low forward voltage
- This product itself will remain within RoHS compliant version.

Descriptions

- EVERLIGHT's Infrared Emitting Diode (IR204 –A) is a high intensity diode , molded in a blue plastic package.
- The device is spectrally matched with phototransistor , photodiode and infrared receiver module.


Applications

- Free air transmission system
- Infrared remote control units with high power requirement
- Smoke detector
- Infrared applied system

Device Selection Guide

LED Part No.	Chip Material	Lens Color
IR204-A	GaAlAs	Blue

Package Dimensions



Notes: 1.All dimensions are in millimeters
2.Tolerances unless dimensions ±0.25mm

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Units
Continuous Forward Current	I_F	100	mA
Peak Forward Current	I_{FP}	1.0	A
Reverse Voltage	V_R	5	V
Operating Temperature	T_{opr}	-40 ~ +85	℃
Storage Temperature	T_{stg}	-40 ~ +85	℃
Soldering Temperature	T_{sol}	260	℃
Power Dissipation at(or below) 25℃ Free Air Temperature	P_d	150	mW

Notes: *1:I_{FP} Conditions--Pulse Width≦100 μs and Duty≦1%.
*2:Soldering time≦5 seconds.

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Units
Radiant Intensity	Ee	I_F=20mA	4.0	7.8	--	mW/sr
		I_F=100mA Pulse Width≦100 μs ,Duty≦1%	--	38	--	
		I_F=1A Pulse Width≦100 μs ,Duty≦1%.	--	450	--	
Peak Wavelength	λp	I_F=20mA	--	940	--	nm
Spectral Bandwidth	Δλ	I_F=20mA	--	45	--	nm
Forward Voltage	V_F	I_F=20mA	--	1.2	1.5	V
		I_F=100mA Pulse Width≦100 μs ,Duty≦1%	--	1.4	1.8	
		I_F=1A Pulse Width≦100 μs ,Duty≦1%.	--	2.6	4.0	
Reverse Current	I_R	V_R=5V	--	--	10	μA
View Angle	2θ1/2	I_F=20mA	--	35	--	deg

Rank

Condition：I_F=20mA

Unit：mW/sr

Bin Number	K	L	M	N
Min	4.0	5.6	7.8	11.0
Max	6.4	8.9	12.5	17.6

Typical Electro-Optical Characteristics Curves

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 Spectral Distribution




Fig.3 Peak Emission Wavelength vs.Ambient Temperature





Fig.4 Forward Current vs. Forward Voltage



Typical Electro-Optical Characteristics Curves

Fig.5 Relative Intensity vs. Forward Current




Fig.6 Relative Radiant Intensity vs. Angular Displacement




Fig.7 Relative Intensity vs. Ambient Temperature(°C)





Fig.8 Forward Voltage vs. Ambient Temperature(°C)



Reliability Test Item And Condition

The reliability of products shall be satisfied with items listed below.

Confidence level：90%


LTPD：10%

NO.	Item	Test Conditions	Test Hours/ Cycles	Sample Sizes	Failure Judgement Criteria	Ac/Re
1	Solder Heat	TEMP.：260℃±5℃	10secs	22pcs	Ee≦L×0.8 V_F≦U U：Upper Specification Limit L：the initial test value	0/1
2	Temperature Cycle	H：+100℃ 15mins ↕ 5mins L：-40℃ 15mins	300Cycles	22pcs		0/1
3	Thermal Shock	H：+100℃ 5mins ↕ 10secs L：-10℃ 5mins	300Cycles	22pcs		0/1
4	High Temperature Storage	TEMP.：+100℃	1000hrs	22pcs		0/1
5	Low Temperature Storage	TEMP.：-40℃	1000hrs	22pcs		0/1
6	DC Operating Life	I_F=20mA	1000hrs	22pcs		0/1
7	High Temperature/ High Humidity	85℃ / 85% R.H	1000hrs	22pcs		0/1

Packing Quantity Specification

1. 1000PCS/1Bag,4Bag/1Box
2. 10Boxes/1Carton

Label Form Specification



CPN: Customer's Production Number
P/N : Production Number
QTY: Packing Quantity
CAT: Ranks
HUE: Peak Wavelength
REF: Reference
LOT No: Lot Number

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD.
Office: No 25, Lane 76, Sec 3, Chung Yang Rd, Tucheng, Taipei 236, Taiwan, R.O.C
Tel: 886-2-2267-2000, 2267-9936
Fax: 886-2267-6244, 2267-6189, 2267-6306
http:\\www.everlight.com