04 - Iteration Control Structures

For example:

Input	Result
20	1 2 4 5 10 20

Ex. No. : 4.1 **Date:**

Register No.: **Name:**

Factors of a number

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number)

```
number = 20
factors = []
for i in range(1, int(number**0.5) + 1):
    if number % i == 0:
        factors.append(i)
        if i != number // i:
            factors.append(number // i)
factors.sort()
print(factors)
```

For example:

Input	Result
292	1
1015	2
108	3
22	0

Ex. No. : 4.2 **Date:**

Register No.: **Name:**

Non Repeated Digit Count

Write a program to find the count of non-repeated digits in a given number N. The number will be passed to the program as an input of type int.
Assumption: The input number will be a positive integer number >= 1 and <= 25000.
Some examples are as below.
If the given number is 292, the program should return 1 because there is only 1 non--repeated digit '9' in this number
If the given number is 1015, the program should return 2 because there are 2 non-repeated digits in this number, '0', and '5'.
If the given number is 108, the program should return 3 because there are 3 non-repeated digits in this number, '1', '0', and '8'.
If the given number is 22, the function should return 0 because there are NO non--repeated digits in this number.

```
n = input().strip()
dcnt = {}
for d in n:
    if d in d_cnt:
        dcnt[d] += 1
    else:
        dcnt[d] = 1
nrcnt = 0
for d in d_cnt:
    if dcnt[d] == 1:
        nrcnt += 1

print(nrcnt)
```

Example1: if the given number N is 7, the method must return 2

Example2: if the given number N is 10, the method must return 1

For example:

Input	Result
7	2
10	1

Ex. No. : 4.3 **Date:**

Register No.: **Name:**

Prime Checking

Write a program that finds whether the given number N is Prime or not. If the number is prime, the program should return 2 else it must return 1.

Assumption: 2 <= N <=5000, where N is the given number.

```
n = int(input().strip())
is_prime = True
if n <= 1:
    is_prime = False
else:
    for i in range(2, int(n**0.5) + 1):
        if n % i == 0:
            is_prime = False
            break

if is_prime:
    print(2)
else:
    print(1)
```

Input Format:

Integer input from stdin.

Output Format:

Perfect square greater than N.

Example Input:

10

Output:

16

Ex. No. : 4.4 **Date:**

Register No.: **Name:**

Next Perfect Square

Given a number N, find the next perfect square greater than N.

```
import math
n = int(input().strip())
ns = (math.isqrt(n) + 1) ** 2
print(ns)
```

NOTE: Fibonacci series looks like –

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . and so on.

i.e. Fibonacci series starts with 0 and 1, and continues generating the next number as the sum of the previous two numbers.

- first Fibonacci number is 0,
- second Fibonacci number is 1,
- third Fibonacci number is 1,
- fourth Fibonacci number is 2,
- fifth Fibonacci number is 3,
- sixth Fibonacci number is 5,
- seventh Fibonacci number is 8, and so on.

For example:

Input:

7

Output

8

Ex. No. : 4.5 **Date:**

Register No.: **Name:**

Nth Fibonacci

Write a program to return the nth number in the fibonacci series. The value of N will be passed to the program as input.

```
n = int(input().strip())

fibonacci = [0, 1]

for i in range(2, n + 1):

    fibonacci.append(fibonacci[i - 1] + fibonacci[i - 2])

print(fibonacci[n])
```

Input Format:

Single Integer Input from stdin.

Output Format:

Yes or No.

Example Input:

175

Output:

Yes

Explanation

1^1 + 7^2 +5^3 = 175

Example Input:

123

Output:

No

For example:

Input	Result
175	Yes
123	No

Ex. No. : 4.6 **Date:**

Register No.: **Name:**

Disarium Number

A Number is said to be Disarium number when the sum of its digit raised to the power of their respective positions becomes equal to the number itself. Write a program to print number is Disarium or not.

```
n = input().strip()

def is_disarium(number):

    length = len(number)

    total = 0

    for i in range(length):

        total += int(number[i]) ** (i + 1)

    return total == int(number)

if is_disarium(n):

    print("Yes")

else:

    print("No")
```

Sample Test Cases

Test Case 1

Input

4

Output

1234

Explanation:

as input is 4, have to take 4 terms.

1 + 11 + 111 + 1111

Test Case 2

Input

6

Output

123456

For example:

Input	Result
3	123

Ex. No. : 4.7 **Date:**

Register No.: **Name:**

Sum of Series

Write a program to find the sum of the series 1 +11 + 111 + 1111 + . . . + n terms (n will be given as input from the user and sum will be the output)

```
a=int(input())
t=1
s=0
for i in range(1,a+1):
    s=s+t
    t=t*10+1
print(s)
```

For example:

Input	Result
292	2
1015	3

Ex. No. : 4.8 **Date:**

Register No.: **Name:**

Unique Digit Count

Write a program to find the count of unique digits in a given number N. The number will be passed to the program as an input of type int.
Assumption: The input number will be a positive integer number >= 1 and <= 25000.
For e.g.
If the given number is 292, the program should return 2 because there are only 2 unique digits '2' and '9' in this number
If the given number is 1015, the program should return 3 because there are 3 unique digits in this number, '1', '0', and '5'.

```
a=int(input())
c=0
n=[]
r=[]

while a>0:
    re=a%10
    n.append(re)
    a=a//10
l=len(n)

for i in range(l):
    if (n[i] not in r):
        r.append(n[i])

print(len(r))
```

Input Format:

Single Integer input.

Output Format:

Output displays Yes if condition satisfies else prints No.

Example Input:

14

Output:

Yes

Example Input:

13

Output:

No

Input Format:

Single integer input.

Output Format:

Yes or No.

Example Input:

24

Output:

Yes

Example Input:

26

Output:

No

For example:

Input	Result
24	Yes

Ex. No. : 4.10 **Date:**

Register No.: **Name:**

Perfect Square After adding One

Given an integer N, check whether N the given number can be made a perfect square after adding 1 to it.

```
n = int(input().strip())
if (n + 1) ** 0.5 % 1 == 0:
    print("Yes")
else:
    print("No")
```