DATA STRUCTURES AND ALGORITHMS

23CSE203

Submitted by	
Name	JASHTI HEMENDRA
Roll No	AV.SC.U4CSE25116
Year/sem/section	2nd year/sem-3/CSE-B
Credits	5

Submitted to	
Name	DR. RAJKUMAR BATCHU
Department	School of computing
Designation	Asst. professor (SI. Grade)

SNO	TITLE	PAGE NO	REMARKS
1	WEEK 1: 1a. Recursive countdown from n to Launch.1b. Recursive calculation of compound growth factor.1c. Recursive search for employee ID in list.1d. Recursive factorial calculation for parcel arrangements.1e. Recursive Fibonacci series generation.	4–14	
2	WEEK 2: 2a. Write a python program to perform linear search on the give input. 2b. Write a python program to perform binary search on the given. Verify by taking sorted array as an input. 2c. Write a python program to perform binary search on the given. Verify by taking unsorted array as an input.	15–22	
3	WEEK-3: 3a.write a python program to perform bubblesort on the given input 3b. write a python program to perform insertion_sort on the given input 3c. write a python program to perform selection sort by taking given input 3d.write a python program to perform merge sort by taking the given input . 3e. write a python program to perform quick sort by taking given input	23–37	
4	Week-4: 4a.write a python program to perform linked list operations by taking the input from the user	38–70	

	4b. write a python program to perform double linked list operations by taking input from the user 4c. write a python program to perform circular linked list operations by taking input from the user		
5	Week-5: 5a write a python program to implement the stack by using arrays. 5b. write a python program to implement stack using the linked list	71–80	
6	Week-6: 6a and b.Write a python program to implement stack operations such as push, pop, peek, display using an array and a linked list.	81–84	
7	Week-7: 7a . Write a Python program to implement Queue using Array and Linked List. Provide a main menu to select the implementation and perform Enqueue, Dequeue, Peek, and Display operations. 7b. Write a Python program to implement Circular Queue using Array and Linked List. Provide a main menu to select the implementation and perform Enqueue, Dequeue, Peek, and Display operations.	85–90	
8	(8A & B) write a python program to implement a binary tree with its operations using an array and a linked list	90-95	
9	9A write a python program to implement a binary search tree with its operation and traversals	96-98	

WEEK-1

1A. AIM: A Rocket launch system displays a countdown before launch. Instead of suing a loop, implement the countdown using recursion. Write a recursive python program to display a countdown from n to 1 followed by “launch”.

Code:



Output:



Explanation

Condition 1: Positive Input (n > 0)

- The function checks whether n == 0.
- Since n is positive, the condition is **False**.
- It executes:
  - print(n) → prints the current value of n.

- countdown(n-1) → calls the same function again with n-1.
- This process continues until n becomes 0.
- When n == 0, the condition becomes **True**.
- It prints **launch**.
- The return statement stops that function call.
- Then the recursive calls return one by one.
- Since there is no value returned by the function, it returns **None**.

Condition 2: Zero Input (n == 0)

- The function checks if n == 0.
- The condition is immediately **True**.
- It prints **launch**.
- The return statement stops the function.
- No recursive call takes place.
- The function returns **None**.

Condition 3: Negative Input (n < 0)

- The condition n == 0 is **False**.
- It prints the negative value.
- Then it calls itself with n-1, making the value even more negative.
- Therefore, it will **never reach 0**.
- The recursion continues indefinitely.
- Eventually, Python raises a **RecursionError** because the maximum recursion depth is exceeded

Error table:


s.no	Error obtained	Rectification
1	Negative input in countdown	Add a condition to handle negative numbers before recursion.

1B. Aim: Banks calculate the growth of an investment using compound interest. The formula requires calculating powers, which can be implemented recursively. Write a recursive program to calculate p(n) where p=principal growth, n= no. of years.

Code:



Output:



Explanation

Condition 1: n > 0

- The function compound_interest(p, n) is called with the principal amount p and number of years n.
- The function checks whether n == 0.
- Since n is greater than 0, the condition is **False**.
- It executes the else block.
- It calculates:
  - p * compound_interest(p, n-1)
- The function calls itself recursively with n-1.
- This process continues until n becomes 0.
- Each recursive call multiplies p one more time.
- Therefore, the function calculates $\mathbf{p^n}$.

Condition 2: n == 0

- When n becomes 0, the condition n == 0 becomes **True**.

- The function returns 1.
- This 1 acts as the **base case** for the multiplication.
- The recursive calls then return one by one.
- Each returned value is multiplied by p.
- Finally, the result is printed using print(compound_interest(p,n))

Error table:

s.no	Error obtained	rectification
1	Wrong indentation	Maintain proper indentation.

1C. AIM . An Hr department stores employee IDs in a list .Develop a recursive program to search for a given employee ID write a recursive function to search for an employee ID in a list.

Code:



Output:

```
Enter employee IDs: 101 102 103 104 105
Enter employee ID to search: 104
Employee ID found
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> ^C
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe
  "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week1/3.py"
Enter employee IDs: 101 102 103 104 105
Enter employee ID to search: 106
Employee ID not found
```

Explanation

Condition 1: index == len(emp_list)

- The function checks whether index has reached the length of the employee list.
- If index == len(emp_list), it means we have checked **all employee IDs**.
- The employee ID was not found.
- The function returns **False**.
- No further recursion takes place.

Condition 2: emp_list[index] == emp_id

- The function checks whether the current employee ID is equal to the ID we are searching for.
- If both IDs are equal, the condition becomes **True**.
- The function returns **True**.
- The recursion stops because the employee ID has been found.

Condition 3: Employee ID does not match

- If the current employee ID is not equal to emp_id, the condition is **False**.
- The function calls itself recursively with:
  - index + 1
- This moves to the **next employee ID** in the list.
- The process continues until:
  - The employee ID is found, or
  - The entire list is checked.

Error table:

s.no	Error obtained	Rectification
1	Missing return statement	Add the required return statement

1D. AIM. In a logistics company , the no . of possible ways to arrange in different parcels is calculated using the factorial formula (n!). Develop a recursive program to calculate the factorial of a given number.

Code:

```python
#JASHTI HEMENDRA

def factorial(num):
    if num < 0:
        return "Factorial is not defined for negative numbers"

    if num == 0:
        return 1

    return num * factorial(num - 1)


n = int(input("Enter a number: "))

result = factorial(n)
print("Factorial =", result)

```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe
 "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week1/4.py"
Enter a number: 6
Factorial = 720
PS C:\AMRITA\2nd year\1 SEMESTER\DSA>
```

Explanation

Condition 1: Negative Input (n < 0)

- The program first checks whether n < 0.
- If n is negative, the condition is **True**.

- Factorial is not defined for negative numbers.
- It prints:
  Factorial is not defined for negative numbers.
- The factorial() function is **not called**.

Condition 2: Base Case (n == 0 or n == 1)

- Inside the factorial() function, it checks:
  n == 0 or n == 1
- If n is 0 or 1, the condition is **True**.
- The function returns **1**.
- This is the **base case** of the recursion.
- It stops further recursive calls.

Condition 3: n > 1

- If n is greater than 1, the condition n == 0 or n == 1 is **False**.
- The else block is executed.
- It returns:
  n * factorial(n - 1)
- The function calls itself with n - 1.
- This continues until n becomes 1.
- Then the returned values are multiplied together

Error table:

s.no	Error obtained	Rectification
1	Wrong recursive value	Updated the recursive value correctly

1E. AIM. Write a recursive program to print the first n terms of the fibonacci series

Code:

```python
#JASHTI HEMENDRA


def fibonacci(n):
    if n < 0:
        return "Invalid input"

    if n <= 1:
        return n

    return fibonacci(n - 1) + fibonacci(n - 2)


terms = int(input("Enter the number of terms: "))

print("Fibonacci Series:")

for i in range(terms):
    print(fibonacci(i), end=" ")
```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe
  "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week1/5.py"
Enter the number of terms: 5
Fibonacci Series:
0 1 1 2 3
```

Explanation

Condition 1: n == 0

- The function checks whether n == 0.
- If the condition is **True**, the function returns 0.
- This is the **first base case**.
- No further recursive call takes place.

Condition 2: n == 1

- If n is not 0, the function checks whether n == 1.
- If the condition is **True**, the function returns 1.
- This is the **second base case**.

- No further recursive call takes place

Condition 3: n > 1

- If n is neither 0 nor 1, both conditions are **False**.
- The else block is executed.
- The function calls itself **two times**:
  - fibonacci(n - 1)
  - fibonacci(n - 2)
- The two returned values are added together.
- This process continues until the base cases n == 0 and n == 1 are reached.

Error table:

s.no	Error obtained	Rectification
1	Incorrect Fibonacci recursion	Use fibonacci(n-1) + fibonacci(n-2).

2a. AIM: Write a python program to perform linear search on the give input.

Code:

```
dsa lab > week2 > 1.py > ...
1   #JASHTI HEMENDRA
2
3   def linear_search(numbers, target):
4       for index in range(len(numbers)):
5           if numbers[index] == target:
6               return index
7       return -1
8
9
10  n = int(input("Enter the number of elements: "))
11
12  numbers = []
13
14  for _ in range(n):
15      numbers.append(int(input("Enter the element: ")))
16
17  target = int(input("Enter the search element: "))
18
19  result = linear_search(numbers, target)
20  print(result)
```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe
 "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week2/1.py"
Enter the number of elements: 5
Enter the element: 21
Enter the element: 23
Enter the element: 54
Enter the element: 45
Enter the element: 65
Enter the search element: 65
4
```

Explanation

Condition 1: Element is Found (arr[i] == k)

- The function linear_search(arr, k) receives the array arr and the search element k.
- The for loop starts from the first element of the array.
- It checks each element one by one using:
  arr[i] == k
- If the current element is equal to k, the condition becomes **True**.
- The function immediately returns the **index i**.

- Since the function returns the index, the loop stops immediately.
- The remaining elements are not checked.

Condition 2: Element is Not Found


- The loop checks every element in the array.
- If none of the elements is equal to k, the if condition is always **False**.
- After the loop finishes, the statement return -1 is executed.
- -1 indicates that the search element is **not present** in the array.

Error table:


s.no	Error obtained	Rectification
1	Wrong loop range	Use range(n) to process exactly n elements.

2b. AIM: Write a python program to perform binary search on the given. Verify by taking sorted array as an input.

Code:



Output:



Explanation

Condition 1: k == arr[mid] — Element Found

- The function binary_search(arr, k) receives the array and the search element.
- low is initialized to 0, which represents the first index.
- high is initialized to len(arr)-1, which represents the last index.
- The while loop runs as long as low <= high.
- mid is calculated using:
  mid = (low + high) // 2
- The middle element is compared with the search element k.
- If k == arr[mid], the element is found.
- The function returns the **index mid** and stops searching.

Condition 2: k < arr[mid] — Search Left Half

- If k is smaller than the middle element, the condition is **True**.
- This means the search element can only be present in the **left half**.
- Therefore:
  high = mid - 1
- The right half is eliminated.
- The process continues with the remaining left half

Condition 3: k > arr[mid] — Search Right Half

- If k is greater than the middle element, the elif condition is **False**.
- The else block is executed.
- This means the search element can only be present in the **right half**.

- Therefore:
  low = mid + 1
- The left half is eliminated.
- The process continues with the remaining right half.

Condition 4: low > high — Element Not Found

- The while loop continues until low <= high becomes **False**.
- When low > high, there are no elements left to search.
- This means the search element is not present in the array.
- The function returns **-1**.

Error table:

s.no	Error obtained	Rectification
	Wrong index in binary search	Use high = mid - 1 for the left half and low = mid + 1 for the right half.

2c.Aim: write a python program to perform a bianry search on the given input verify by Taking unsorted array as input

Code:

```python
#JASHTI HEMENDRA

def binary_search(arr, target):
    low = 0
    high = len(arr) - 1

    while low <= high:
        mid = (low + high) // 2

        if arr[mid] == target:
            return mid
        elif target < arr[mid]:
            high = mid - 1
        else:
            low = mid + 1

    return -1


n = int(input("Enter the number of elements: "))

arr = []

for i in range(n):
    arr.append(int(input("Enter the element: ")))

target = int(input("Enter the search element: "))

# Sort the unsorted array
arr.sort()

print("Sorted array:", arr)

result = binary_search(arr, target)

if result != -1:
    print("Element found at index:", result)
else:
    print("Element not found")
```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week2/3.py"
Enter the number of elements: 3
Enter the element: 1
Enter the element: 2
Enter the element: 3
Enter the search element: 3
Sorted array: [1, 2, 3]
Element found at index: 2
```

Explanation

Condition 1: arr[mid] == key — Element Found

- The function first calculates the middle index using mid = (low + high) // 2.
- It compares the middle element arr[mid] with the search element key.
- If arr[mid] == key, the condition is **True**.
- The element is found.
- The function returns the index mid.
- The search stops.

Condition 2: key < arr[mid] — Search Left Half

- If key is smaller than arr[mid], the condition is **True**.
- This means the required element may be present in the **left half**.
- The right half is ignored.
- high is changed to mid - 1.
- The search continues in the left half.

Condition 3: key > arr[mid] — Search Right Half

- If key is greater than arr[mid], the previous conditions are **False**.
- The element may be present in the **right half**.
- The left half is ignored.
- low is changed to mid + 1.
- The search continues in the right half.

Condition 4: low > high — Element Not Found

- The while low <= high loop continues until there are elements left to search.
- When low > high, the loop stops.
- This means the element is not present in the array.
- The function returns -1.
- The program prints **"Element not found."**

Condition 5: Array is Already Sorted

- The program checks whether the given array is already sorted.
- It uses:
  arr == sorted(arr)

- If the condition is **True**, it prints:
  "Array is already sorted."
- The array is directly used for binary search.

Condition 6: Array is Unsorted

- If arr == sorted(arr) is **False**, the array is unsorted.
- The program prints:
  "Array is unsorted."
- It then uses arr.sort() to sort the array.
- The sorted array is displayed.
- Binary search is then performed on the sorted array.

Error table:

s.no	Error obtained	Rectification
1	Binary search on unsorted array	sort the array first using arr.sort() or provide a sorted array.

Week-3

3a.Aim.Write a python program to sort the elements using a bubble sort technique. Take an input elements from the user.

Code:

```python
#JASHTI HEMENDRA

def bubble_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        for j in range(n - i - 1):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]

    return arr


n = int(input("Enter the number of elements: "))

arr = []

for _ in range(n):
    arr.append(int(input("Enter the element: ")))

print("Before sorting:", arr)

bubble_sort(arr)

print("After sorting:", arr)
```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week3/1.py"
Enter the number of elements: 5
Enter the element: 45
Enter the element: 34
Enter the element: 23
Enter the element: 12
Enter the element: 21
Before sorting: [45, 34, 23, 12, 21]
After sorting: [12, 21, 23, 34, 45]
```

Explanation

Condition 1: arr[j] > arr[j+1] — Elements Need to Be Swapped

- The function bubble_sort(arr) receives the array as an argument.
- The outer for loop runs from 0 to n-1 and controls the number of passes.

- The inner for loop runs from 0 to n-2 and compares adjacent elements.
- The condition arr[j] > arr[j+1] checks whether the current element is greater than the next element.
- If the condition is **True**, the two elements are in the wrong order.
- Therefore, the two elements are swapped using:
- Arr[j],arr[j+1]=arr[j+1],arr[j]
- After the swap, the smaller element moves toward the left and the larger element moves toward the right.

Condition 2: arr[j] <= arr[j+1] — No Swap Required

- If arr[j] > arr[j+1] is **False**, it means the current element is smaller than or equal to the next element.
- Therefore, the elements are already in the correct ascending order.
- No swapping is performed.
- The inner loop continues to compare the next pair of adjacent elements.

Condition 3: for i in range(n) — Repeated Passes

- The outer loop repeats the comparison process for all the elements.
- After each complete pass, the **largest unsorted element moves to the end of the array**.
- The process is repeated until all elements are arranged in ascending order.
- Finally, the function returns the sorted array using:

Error table:

sno	Error obtained	Rectification
1	IndexError: list index out of range	Use correct loop range

3b.Aim. write a python program to sort the elements using a insertion sort technique. Take an input elements from the user.

Code:

```python
#JASHTI HEMENDRA

def insertion_sort(arr):
    for i in range(1, len(arr)):
        key = arr[i]
        j = i - 1

        while j >= 0 and arr[j] > key:
            arr[j + 1] = arr[j]
            j -= 1

        arr[j + 1] = key


n = int(input("Enter the number of elements: "))

arr = []

for _ in range(n):
    arr.append(int(input("Enter the element: ")))

print("Before sorting:", arr)

insertion_sort(arr)

print("After sorting:", arr)
```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week3/2.py"
Enter the number of elements: 4
Enter the element: 34
Enter the element: 32
Enter the element: 21
Enter the element: 43
Before sorting: [34, 32, 21, 43]
After sorting: [21, 32, 34, 43]
```

Explanation:

Condition 1: for i in range(1, len(arr)) — Selecting Element

- The loop starts from the **second element**.
- The first element is considered already sorted.
- i represents the element that needs to be placed correctly.

Condition 2: key = arr[i] — Storing Element

- The current element is stored in key.

key = arr[i]

- This element will be compared with the elements before it.

Condition 3: j = i - 1 — Getting Previous Position

- j points to the element just before the current element.

```
j = i - 1
```

Condition 4: while j >= 0 and key < arr[j] — Comparing Elements

- The current element is compared with the previous elements.
- If the previous element is greater than key, it is moved one position to the right.

```
while j >= 0 and key < arr[j]:
    arr[j + 1] = arr[j]
    j -= 1
```

- This creates space for the current element.

Condition 5: arr[j + 1] = key — Inserting Element

- The key is placed in its correct position.

```
arr[j + 1] = key
```

- The elements before the current position are now sorted.

Condition 6: return arr — Returning Sorted Array

- After all elements are processed, the function returns the sorted array.

```
return arr
```

error table:

sno	Error obtained	Rectification
1	Elements not sorted correctly	Shift elements before insertion

3c.write a python program to sort the elements using selection sort technique . take an input from the user.

Code:

```python
def selection_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        smallest = i

        for j in range(i + 1, n):
            if arr[j] < arr[smallest]:
                smallest = j

        arr[i], arr[smallest] = arr[smallest], arr[i]


n = int(input("Enter the number of elements: "))

arr = []


for _ in range(n):
    arr.append(int(input("Enter the element: ")))

print("Before sorting:", arr)

selection_sort(arr)

print("After sorting:", arr)
```

Output:



Explanation:

Condition 1: for i in range(n) — Selecting Position

- The loop goes through each position in the array.
- i represents the current position where the smallest element will be placed.

Condition 2: mini = i — Assuming Minimum

- Initially, the element at index i is assumed to be the smallest.

Condition 3: for j in range(i+1,n) — Finding Minimum

- The loop checks all elements after position i.
- It searches for the smallest element.

Condition 4: if arr[mini] > arr[j] — Comparing

- Compares the current minimum with arr[j].
- If arr[j] is smaller, mini is updated.

Condition 5: mini = j — Updating Minimum

- Stores the index of the newly found smallest element.

Condition 6: arr[mini], arr[i] = arr[i], arr[mini] — Swapping

- The smallest element is swapped with the element at position i.
- This places the smallest element in its correct position.

Condition 7: return arr — Returning Result

- Returns the completely sorted array.

Error table:

Sno	Error obtained	Rectification
1	Wrong minimum value	Update min_index properly

3d.write a python program to sort the elements using the merge sort technique . take an input from the user.

Code:

dsa lab > week3 > 4.py > ...

```python
def merge_sort(arr):
    if len(arr) <= 1:
        return arr

    mid = len(arr) // 2

    left = merge_sort(arr[:mid])
    right = merge_sort(arr[mid:])

    result = []
    i = 0
    j = 0

    while i < len(left) and j < len(right):
        if left[i] <= right[j]:
            result.append(left[i])
            i += 1
        else:
            result.append(right[j])
            j += 1

    result.extend(left[i:])
    result.extend(right[j:])

    return result


n = int(input("Enter the number of elements: "))

arr = []

for _ in range(n):
    arr.append(int(input("Enter the element: ")))


print("Before sorting:", arr)

sorted_arr = merge_sort(arr)

print("After sorting:", sorted_arr)

```

Output:



Explanation:

Condition 1: if len(arr) <= 1 — Checking the Base Condition

- The function first checks whether the array contains **one or zero elements**.

if len(arr) <= 1:

return arr

- If the array has one or zero elements, it is already sorted.
- No further division or comparison is required.
- The function returns the array as it is:

return arr

Condition 2: mid = len(arr) // 2 — Finding the Middle

- The array is divided into two parts.
- The middle position is calculated using:

mid = len(arr) // 2

- len(arr) gives the total number of elements.
- // 2 performs integer division and finds the middle index.

Condition 3: left = arr[:mid] — Creating the Left Part

- The elements before the middle position are stored in left.

left = arr[:mid]

Condition 4: right = arr[mid:] — Creating the Right Part

- The elements from the middle position to the end are stored in right.

right = arr[mid:]

Condition 5: merge_sort(left) and merge_sort(right) — Sorting Both Parts

- The left and right parts are recursively sorted.

merge_sort(left)

merge_sort(right)

- The array continues to be divided until each part contains only **one element**.
- A single element is already sorted.
- The smaller sorted parts are then merged together.

Condition 6: i = j = k = 0 — Initializing Indexes

- Three variables are initialized:

```
i = j = k = 0
```

- i keeps track of the current element in the **left array**.
- j keeps track of the current element in the **right array**.
- k keeps track of the position in the **original array** where the element will be placed.

Condition 7: while i < len(left) and j < len(right) — Comparing Both Parts

- The program compares elements from the left and right arrays.

```
while i < len(left) and j < len(right):
```

- The loop continues as long as both arrays still have elements to compare.
- This allows the program to select the smaller element and place it into the original array.

Condition 8: if left[i] < right[j] — Comparing Elements

- The current elements of the left and right arrays are compared.

```
if left[i] < right[j]:
```

- If the left element is smaller than the right element, it is placed into the original array.

```
arr[k] = left[i]
```

- Then i is increased:

```
i += 1
```

- This moves to the next element of the left array.

Condition 9: else — Taking the Right Element

- If the right element is smaller than or equal to the left element, the right element is placed into the original array.

```
else:
    arr[k] = right[j]
```

- Then j is increased:

j += 1

- This moves to the next element of the right array.

Condition 10: k += 1 — Moving to the Next Position

- After placing an element into the original array, k is increased.

k += 1

Condition 11: while i < len(left) — Copying Remaining Left Elements

- Sometimes the right array becomes empty before the left array.

while i < len(left):

- Any remaining elements in the left array are copied into the original array.

arr[k] = left[i]

- Then both i and k are increased:

i += 1

k += 1

- The remaining elements are already sorted, so no comparison is needed.

Condition 12: while j < len(right) — Copying Remaining Right Elements

- Sometimes the left array becomes empty before the right array.

while j < len(right):

- Any remaining elements in the right array are copied into the original array.

arr[k] = right[j]

- Then j and k are increased:

j += 1

k += 1

- This completes the merging process.

Error table:

sno	Error obtained	Rectification
1	Recursive error	Use if len(arr) <= 1
2	IndexError	Check left/right array indices

Bottom of Form

3e. Aim. Write a python program to sort the elements using a quick sort technique . take an input elements from the user

Code:

dsa lab > week3 > 5.py > quick_sort

```python
def quick_sort(arr):
    if len(arr) <= 1:
        return arr

    pivot = arr[-1]

    smaller = []
    greater = []

    for value in arr[:-1]:
        if value <= pivot:
            smaller.append(value)
        else:
            greater.append(value)

    return quick_sort(smaller) + [pivot] + quick_sort(greater)


n = int(input("Enter the number of elements: "))

arr = []

for _ in range(n):
    arr.append(int(input("Enter the element: ")))

print("Before sorting:", arr)

sorted_arr = quick_sort(arr)

print("After sorting:", sorted_arr)

```

Output:

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe "c:/AMRITA/2nd year/1 SEMESTER/DSA/d
sa lab/week3/5.py"
Enter the number of elements: 5
Enter the element: 221
Enter the element: 232
Enter the element: 212
Enter the element: 222
Enter the element: 2123
Before sorting: [221, 232, 212, 222, 2123]
After sorting: [212, 221, 222, 232, 2123]
```

Explanation

Condition 1: if arr[j] < pivot — Element Smaller Than Pivot

- The function partition(arr, low, high) is used to divide the array into two parts.
- pivot = arr[high] selects the **last element** of the array as the pivot.
- i = low - 1 is initialized to keep track of the position where elements smaller than the pivot should be placed.
- The for loop checks each element from index low to high-1.
- The condition arr[j] < pivot checks whether the current element is smaller than the pivot.
- If the condition is **True**, i is increased by 1.
- The current element is then swapped with the element at index i:

arr[i], arr[j] = arr[j], arr[i]

- This places all elements smaller than the pivot toward the left side.

Condition 2: arr[j] >= pivot — No Swap Required

- If arr[j] < pivot is **False**, it means the current element is greater than or equal to the pivot.
- No swapping is performed.
- The loop continues to check the next element.
- These elements will remain on the right side of the pivot after partitioning.

Condition 3: arr[i+1], arr[high] = arr[high], arr[i+1] — Placing the Pivot

- After all elements have been checked, the pivot is placed in its correct position.
- The pivot is swapped with the element at index i+1:

arr[i+1], arr[high] = arr[high], arr[i+1]

- After this operation:
  - Elements smaller than the pivot are on the **left**.
  - The pivot is in its **correct position**.
  - Elements greater than or equal to the pivot are on the **right**.
- The function returns the pivot position:

return i+1

Condition 4: if low < high — Continue Quick Sort

- The function quick_sort(arr, low, high) is used to sort the array.
- The condition low < high checks whether the current part of the array contains more than one element.
- If the condition is **True**, the array needs to be sorted.
- The partition() function is called:

pi = partition(arr, low, high)

- pi stores the final position of the pivot.

Condition 5: quick_sort(arr, low, pi-1) — Sort Left Part

- After partitioning, the elements on the left side of the pivot are sorted separately.
- This is done using:

quick_sort(arr, low, pi-1)

- The pivot itself is not included because it is already in its correct position.

Condition 6: quick_sort(arr, pi+1, high) — Sort Right Part

- The elements on the right side of the pivot are sorted separately.
- This is done using:

quick_sort(arr, pi+1, high)

- Again, the pivot is not included because it is already correctly positioned.

Input Section

- n = int(input("enter the no of elements:")) takes the number of elements from the user.
- arr = [] creates an empty list to store the elements.
- The for loop runs n times and takes each element from the user:
- for i in range(n):

arr.append(int(input("enter the elements:")))

- Each entered value is converted into an integer and added to the array using append().

Calling the Quick Sort Function

quick_sort(arr, 0, n-1)

- This calls the quick_sort() function.
- 0 represents the first index of the array.

- n-1 represents the last index of the array.
- The complete array is therefore passed for sorting.

.

Error table:

sno	Error obtained	Rectification
1	IndexError	Check i, j, and pivot boundaries
2	Wrong swapping conditions	By shifting to the correct spaces

WEEK-4

AIM: write a python program to implement a single linked list which could perform the below operations by taking an input from the user

I .create a linked list

ii. insert at beginning

iii. insert at end

iv. insert at specific index

v. delete by value

vi. delete at beginning

vii. delete at the end

viii. count no of nodes

ix. display or travsere

x. exit

code:

dsa lab > week4 > cll.py > Node

```python
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


class CircularLinkedList:
    def __init__(self):
        self.head = None
        self.tail = None

    # i. Create linked list
    def create(self):
        n = int(input("Enter number of nodes: "))

        for _ in range(n):
            value = int(input("Enter value: "))
            self.insert_end(value)

    # ii. Insert at beginning
    def insert_beginning(self, value):
        new_node = Node(value)

        if self.head is None:
            self.head = new_node
            self.tail = new_node
            new_node.next = self.head
        else:
            new_node.next = self.head
            self.head = new_node
            self.tail.next = self.head

    # iii. Insert at end
    def insert_end(self, value):
        new_node = Node(value)

        if self.head is None:
            self.head = new_node
            self.tail = new_node
            new_node.next = self.head
        else:
            new_node.next = self.head
            self.tail.next = new_node
```

```
    # iv. Insert at specific index
    def insert_at_index(self, value, index):
        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            self.insert_beginning(value)
            return

        if self.head is None:
            print("Index out of range")
            return

        current = self.head
        position = 0

        while position < index - 1 and current != self.tail:
            current = current.next
            position += 1

        if position != index - 1:
            print("Index out of range")
            return

        new_node = Node(value)
        new_node.next = current.next
        current.next = new_node

        if current == self.tail:
            self.tail = new_node

    # v. Delete by value
    def delete_by_value(self, value):
        if self.head is None:
            print("List is empty")
            return

        current = self.head
        previous = self.tail

```

```
87          while True:
88              if current.data == value:
89                  break
90
91              previous = current
92              current = current.next
93
94              if current == self.head:
95                  print("Value not found")
96                  return
97
98          # Only one node
99          if self.head == self.tail:
100             self.head = None
101             self.tail = None
102             return
103
104         # Delete head
105         if current == self.head:
106             self.head = self.head.next
107             self.tail.next = self.head
108             return
109
110         # Delete other node
111         previous.next = current.next
112
113         # Delete tail
114         if current == self.tail:
115             self.tail = previous
116
117     # vi. Delete at beginning
118     def delete_beginning(self):
119         if self.head is None:
120             print("List is empty")
121             return
122
123         if self.head == self.tail:
124             self.head = None
125             self.tail = None
```

```
        else:
            self.head = self.head.next
            self.tail.next = self.head

    # vii. Delete at end
    def delete_end(self):
        if self.head is None:
            print("List is empty")
            return

        if self.head == self.tail:
            self.head = None
            self.tail = None
            return

        current = self.head

        while current.next != self.tail:
            current = current.next

        current.next = self.head
        self.tail = current

    # viii. Count nodes
    def count_nodes(self):
        if self.head is None:
            return 0

        count = 0
        current = self.head

        while True:
            count += 1
            current = current.next
```

```
            if current == self.head:
                break

        return count

    # ix. Display / Traverse
    def display(self):
        if self.head is None:
            print("List is empty")
            return

        current = self.head

        while True:
            print(current.data, end=" -> ")
            current = current.next

            if current == self.head:
                break

        print("(Head)")

    # x. Display head and tail
    def display_head_tail(self):
        if self.head is None:
            print("List is empty")
            return

        print("Head:", self.head.data)
        print("Tail:", self.tail.data)
        print("Tail points to:", self.tail.next.data)


cll = CircularLinkedList()
```

```python
while True:

    print("\n----- CIRCULAR LINKED LIST -----")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete at beginning")
    print("7. Delete at end")
    print("8. Count nodes")
    print("9. Display / Traverse")
    print("10. Display Head and Tail")
    print("11. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        cll.create()

    elif choice == 2:
        value = int(input("Enter value: "))
        cll.insert_beginning(value)

    elif choice == 3:
        value = int(input("Enter value: "))
        cll.insert_end(value)

    elif choice == 4:
        value = int(input("Enter value: "))
        index = int(input("Enter index: "))
        cll.insert_at_index(value, index)

    elif choice == 5:
        value = int(input("Enter value to delete: "))
        cll.delete_by_value(value)

    elif choice == 6:
        cll.delete_beginning()

    elif choice == 7:
        cll.delete_end()
```

```
    elif choice == 8:
        print("Number of nodes:", cll.count_nodes())

    elif choice == 9:
        cll.display()

    elif choice == 10:
        cll.display_head_tail()

    elif choice == 11:
        print("Program exited.")
        break

    else:
        print("Invalid choice")

```

Output:

Creating a linked list

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 1
Enter number of nodes: 3
Enter value: 1
Enter value: 2
Enter value: 3
```

Inserting at the begininnig

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 2
Enter value: 6
```

Insertion at the end:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 3
Enter value: 5
```

Insertion at specific index:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 4
Enter value: 2
Enter index: 2
```

Delete at beginning:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 6
```

Delete at the end:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 7
```

Delete at the specific index:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 5
```

Number of nodes:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 8
Number of nodes: 3
```

Display all the nodes:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 9
1 -> 2 -> 2 -> None
```

Exiting the program:

```
----- SINGLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 10
Program exited.
```

Explanation:

1. A **singly linked list** is a collection of nodes where each node contains **two parts**: data and a link to the next node.
2. Each node contains:
   - **Data** – stores the value.
   - **Next (next)** – stores the reference/address of the next node.
3. The program maintains two references:
   - **Head** – points to the first node.
   - **Tail** – points to the last node.
4. Initially, when the list is empty, both head and tail are set to None.
5. A **Node class** is used to create individual nodes and store the data and reference to the next node.
6. During **creation of the linked list**, the user enters the number of nodes and their data. The nodes are created one by one and added to the list.
7. For the first node, both **head and tail** point to the same node, and the next of the tail is None.
8. During **insertion at the beginning**, a new node is created and placed before the current head. The new node's next points to the current head, and the new node becomes the new head.
9. During **insertion at the end**, the new node is added after the current tail. The current tail's next points to the new node, and the new node becomes the new tail.
10. During **insertion at a specific index**, the list is traversed until the required position is reached. The new node is inserted between the appropriate nodes by adjusting their next links.
11. During **deletion by value**, the list is searched for the node containing the given value. The node is removed by making the previous node point to the node after the deleted node.
12. If the node to be deleted is the **head**, the next node becomes the new head.
13. If the node to be deleted is the **tail**, the previous node becomes the new tail and its next is set to None.
14. If the list contains only one node and that node is deleted, both **head and tail are set to None**.
15. During **deletion at the beginning**, the head node is removed and the next node becomes the new head.

16. During **deletion at the end**, the list is traversed to find the node before the tail. That node becomes the new tail and its next is set to None.
17. The **count operation** traverses the list from the head to the end and counts the total number of nodes.
18. The **display/traverse operation** starts from the head and moves through the list using the next link until None is reached.
20. The program continues to execute until the user selects the **Exit** option.

Error table:

sno	Error obtained	rectification
1	Infinite loop or incomplete traversal due to not updating current	Move to the next node using temp = temp.next
2	Forgetting to update head while inserting/deleting at the beginning	Update head to point to the new first node using head = new_node or head = head.next

AIM: write a python program to implement a double linked list which could perform the below operations by taking an input from the user

I .create a linked list

ii. insert at beginning

iii. insert at end

iv. insert at specific index

v. delete by value

vi. delete at beginning

vii. delete at the end

viii. count no of nodes

ix. display or travsere

x. exit

code:

```python
class Node:
    def __init__(self, data):
        self.data = data
        self.prev = None
        self.next = None


class DoublyLinkedList:
    def __init__(self):
        self.head = None

    # i. Create linked list
    def create(self):
        n = int(input("Enter number of nodes: "))

        for _ in range(n):
            value = int(input("Enter value: "))
            self.insert_end(value)

    # ii. Insert at beginning
    def insert_beginning(self, value):
        new_node = Node(value)

        if self.head is not None:
            new_node.next = self.head
            self.head.prev = new_node

        self.head = new_node

    # iii. Insert at end
    def insert_end(self, value):
        new_node = Node(value)

        if self.head is None:
            self.head = new_node
            return

        current = self.head

        while current.next:
            current = current.next

        current.next = new_node
        new_node.prev = current

    # iv. Insert at specific index
    def insert_at_index(self, value, index):
        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            self.insert_beginning(value)
```

```
        current = self.head

        for _ in range(index - 1):
            if current is None:
                print("Index out of range")
                return
            current = current.next

        if current is None:
            print("Index out of range")
            return

        new_node = Node(value)

        new_node.next = current.next
        new_node.prev = current

        if current.next is not None:
            current.next.prev = new_node

        current.next = new_node

    # v. Delete by value
    def delete_by_value(self, value):
        if self.head is None:
            print("List is empty")
            return

        current = self.head

        while current and current.data != value:
            current = current.next

        if current is None:
            print("Value not found")
            return

        if current.prev is not None:
            current.prev.next = current.next
        else:
            self.head = current.next

        if current.next is not None:
            current.next.prev = current.prev

    # vi. Delete at beginning
    def delete_beginning(self):
        if self.head is None:
            print("List is empty")
            return
```

```
        self.head = self.head.next

        if self.head is not None:
            self.head.prev = None

    # vii. Delete at end
    def delete_end(self):
        if self.head is None:
            print("List is empty")
            return

        current = self.head

        while current.next:
            current = current.next

        if current.prev is None:
            self.head = None
        else:
            current.prev.next = None

    # viii. Count nodes
    def count_nodes(self):
        count = 0
        current = self.head

        while current:
            count += 1
            current = current.next

        return count

    # ix. Display / Traverse
    def display(self):
        if self.head is None:
            print("List is empty")
            return

        current = self.head

        while current:
            print(current.data, end=" <-> ")
            current = current.next

        print("None")


dll = DoublyLinkedList()
```

```python

while True:

    print("\n----- DOUBLY LINKED LIST -----")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete at beginning")
    print("7. Delete at end")
    print("8. Count nodes")
    print("9. Display / Traverse")
    print("10. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        dll.create()

    elif choice == 2:
        value = int(input("Enter value: "))
        dll.insert_beginning(value)

    elif choice == 3:
        value = int(input("Enter value: "))
        dll.insert_end(value)

    elif choice == 4:
        value = int(input("Enter value: "))
        index = int(input("Enter index: "))
        dll.insert_at_index(value, index)

    elif choice == 5:
        value = int(input("Enter value to delete: "))
        dll.delete_by_value(value)

    elif choice == 6:
        dll.delete_beginning()

    elif choice == 7:
        dll.delete_end()

    elif choice == 8:
        print("Number of nodes:", dll.count_nodes())

    elif choice == 9:
        dll.display()

    elif choice == 10:
        print("Program exited.")
        break

    else:
        print("Invalid choice")

```

Output:

Creating a linked list:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 1
Enter number of nodes: 3
Enter value: 1
Enter value: 2
Enter value: 3
```

Inserting at the beginning:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 2
Enter value: 6
```

Insert at the end:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 3
Enter value: 8
```

Insert at the specific index:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 4
Enter value: 44
Enter index: 4
```

Delete By value

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 44
```

Delete at the beginning:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 6
```

Delete at the end:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 7
```

Number of nodes:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 8
Number of nodes: 3
```

Display the nodes:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 9
1 <-> 2 <-> 3 <-> None
```

Exiting the program:

```
----- DOUBLY LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Exit
Enter your choice: 10
Program exited.
```

Explanation:

1. A **doubly linked list** is a collection of nodes where each node contains **three parts**: data, a link to the previous node, and a link to the next node.
2. Each node has:
   - **Data** – stores the value.
   - **Previous (prev)** – points to the previous node.
   - **Next (next)** – points to the next node.
3. The program maintains two references:
   - **Head** – points to the first node.
   - **Tail** – points to the last node.

4. Initially, when the list is empty, both head and tail are set to None.
5. A **Node class** is used to create individual nodes and maintain the data, prev, and next references.
6. During **creation of the linked list**, the user enters the number of nodes and their data. The nodes are added one by one at the end of the list.
7. For the first node, both **head and tail** point to the same node. The prev of the head and the next of the tail are None.
8. During **insertion at the beginning**, a new node is created and placed before the current head. The new node becomes the head, its next points to the previous head, and the previous head's prev points back to the new node.
9. During **insertion at the end**, the new node is placed after the current tail. The new node's prev points to the old tail, the old tail's next points to the new node, and the new node becomes the tail.
10. During **insertion at a specific index**, the list is traversed until the required position is reached. The new node is inserted between the previous and next nodes, and both prev and next links are updated.
11. During **deletion by value**, the list is searched for the node containing the given value. Once found, its previous and next nodes are connected to each other, removing the selected node from the list.
12. If the node to be deleted is the **head**, the next node becomes the new head and its prev is set to None.
13. If the node to be deleted is the **tail**, the previous node becomes the new tail and its next is set to None.
14. If the list contains only one node and that node is deleted, both **head and tail are set to None**.
15. During **deletion at the beginning**, the head node is removed and the next node becomes the new head. The new head's prev is set to None.
16. During **deletion at the end**, the tail node is removed and the previous node becomes the new tail. The new tail's next is set to None.
17. The **count operation** traverses the list from the head to the tail and counts the total number of nodes.
18. The **display/traverse operation** starts from the head and moves forward using the next link to display all the nodes.
19. Since it is a doubly linked list, the program can also traverse the list **backwards**, starting from the tail and using the prev links.

20. The program displays the **head and tail** values to show the starting and ending nodes of the list.

21. The important relationships maintained in a doubly linked list are:

head.prev = None

tail.next = None

22. The overall structure of a doubly linked list is:

None ← [10] ⇄ [20] ⇄ [30] ⇄ [40] → None

↑ ↑

HEAD TAIL

23. The arrows in both directions allow the list to be traversed **forward as well as backward**.

24. The program is **menu-driven**, allowing the user to perform creation, insertion, deletion, counting, displaying, and other operations repeatedly until the **Exit** option is selected.

Error table:

Sno	Error obtained	Rectification
1	Forgetting to update the prev pointer	Update both prev and next pointers whenever a node is inserted
2	Incorrect head.prev	Maintain head.prev = None

AIM: write a python program to implement a circular linked list which could perform the below operations by taking an input from the user

I .create a linked list

ii. insert at beginning

iii. insert at end

iv. insert at specific index

v. delete by value

vi. delete at beginning

vii. delete at the end

viii. count no of nodes

ix. display or travsere

x: display the head and tail

xi. exit

code:

```python
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


class LinkedList:
    def __init__(self):
        self.head = None

    # i. Create linked list
    def create(self):
        n = int(input("Enter number of nodes: "))

        for i in range(n):
            value = int(input("Enter value: "))
            self.insert_end(value)

    # ii. Insert at beginning
    def insert_beginning(self, value):
        new_node = Node(value)
        new_node.next = self.head
        self.head = new_node

    # iii. Insert at end
    def insert_end(self, value):
        new_node = Node(value)

        if self.head is None:
            self.head = new_node
            return

        current = self.head

        while current.next:
            current = current.next

        current.next = new_node

    # iv. Insert at specific index
    def insert_at_index(self, value, index):
        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            self.insert_beginning(value)
            return

        current = self.head

        for _ in range(index - 1):
            if current is None:
                print("Index out of range")
                return
            current = current.next

        if current is None:
            print("Index out of range")
            return

        new_node = Node(value)
        new_node.next = current.next
        current.next = new_node
```

```python
    # v. Delete by value
    def delete_by_value(self, value):
        if self.head is None:
            print("List is empty")
            return

        if self.head.data == value:
            self.head = self.head.next
            return

        current = self.head

        while current.next and current.next.data != value:
            current = current.next

        if current.next is None:
            print("Value not found")
        else:
            current.next = current.next.next

    # vi. Delete at beginning
    def delete_beginning(self):
        if self.head is None:
            print("List is empty")
            return

        self.head = self.head.next

    # vii. Delete at end
    def delete_end(self):
        if self.head is None:
            print("List is empty")
            return

        if self.head.next is None:
            self.head = None
            return

        current = self.head

        while current.next.next:
            current = current.next

        current.next = None

    # viii. Count number of nodes
    def count_nodes(self):
        count = 0
        current = self.head

        while current:
            count += 1
            current = current.next

        return count

    # ix. Display / Traverse
    def display(self):
        if self.head is None:
            print("List is empty")
            return

        current = self.head
```

```python
while True:

    print("\n----- SINGLY LINKED LIST -----")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete at beginning")
    print("7. Delete at end")
    print("8. Count nodes")
    print("9. Display / Traverse")
    print("10. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        linked_list.create()

    elif choice == 2:
        value = int(input("Enter value: "))
        linked_list.insert_beginning(value)

    elif choice == 3:
        value = int(input("Enter value: "))
        linked_list.insert_end(value)

    elif choice == 4:
        value = int(input("Enter value: "))
        index = int(input("Enter index: "))
        linked_list.insert_at_index(value, index)

    elif choice == 5:
        value = int(input("Enter value to delete: "))
        linked_list.delete_by_value(value)

    elif choice == 6:
        linked_list.delete_beginning()

    elif choice == 7:
        linked_list.delete_end()

    elif choice == 8:
        print("Number of nodes:", linked_list.count_nodes())

    elif choice == 9:
        linked_list.display()

    elif choice == 10:
        print("Program exited.")
        break

    else:
        print("Invalid choice")

```

Output:

Creating a linked list:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 1
Enter number of nodes: 3
Enter value: 1
Enter value: 2
Enter value: 3
```

Inserting at the beginning:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 2
Enter value: 4
```

Insert at the end:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 3
Enter value: 5
```

Insert at the specific index:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 4
Enter value: 3
Enter index: 2
```

Delete by value:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 5
Enter value to delete: 10
Value not found
```

Delete at the beginning:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 6
```

Delete at the end:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 7
```

Number of nodes:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 8
Number of nodes: 4
```

Display all the nodes:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 9
1 -> 3 -> 2 -> 3 -> (Head)
```

Display the head and the tail

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 10
Head: 1
Tail: 3
Tail points to: 1
```

Exit: the program:

```
----- CIRCULAR LINKED LIST -----
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete at beginning
7. Delete at end
8. Count nodes
9. Display / Traverse
10. Display Head and Tail
11. Exit
Enter your choice: 11
Program exited.
```

Explanation :

1. A **circular singly linked list** is a collection of nodes where each node contains **data** and a **link to the next node**.
2. In a circular linked list, the **last node points back to the first node (head)** instead of pointing to None.
3. The program uses two references:
   - **Head** – points to the first node.
   - **Tail** – points to the last node.
4. Initially, when the list is empty, both head and tail are set to None.
5. A **Node class** is used to create individual nodes and store the data and reference to the next node.
6. During **creation of the linked list**, the user enters the number of nodes and their data. Each new node is inserted at the end of the list.
7. If the list is empty, the first node becomes both the **head and tail**, and its next points back to itself.
8. During **insertion at the beginning**, the new node is placed before the current head. The new node becomes the head, and the tail is connected to the new head.
9. During **insertion at the end**, the new node is added after the current tail. The new node becomes the tail, and its next points to the head.
10. During **insertion at a specific index**, the list is traversed until the required position is reached, and the new node is inserted between two existing nodes.
11. During **deletion by value**, the list is searched for the node containing the given value. The node is removed by connecting its previous node directly to its next node.
12. If the node to be deleted is the **head**, the next node becomes the new head and the tail is connected to it.

13. If the node to be deleted is the **tail**, the previous node becomes the new tail and its next is connected to the head.
14. During **deletion at the beginning**, the head node is removed and the next node becomes the new head.
15. During **deletion at the end**, the node before the tail is found and made the new tail.
16. The **count operation** traverses the list and counts all the nodes. Traversal stops when the head is reached again.
17. The **display/traverse operation** starts from the head and visits every node until it reaches the head again.
18. Since the list is circular, traversal does not use current != None. Instead, it stops when current becomes equal to head.
19. The program also displays the **head, tail, and tail.next** to show the circular connection.
20. The program is **menu-driven**, so the user can repeatedly perform different operations until the **Exit** option is selected.
21. The most important property maintained throughout the program is:

tail.next = head

22. Thus, the structure of the circular linked list is:

HEAD → Node → Node → Node → TAIL

↑ |

|_____|

This ensures that the linked list remains **circular after every insertion and deletion operation**.

Error table:

sno	Error obtained	Rectification
1	Using temp != None as the traversal condition	Stop traversal when temp == head
2	Forgetting to update tail.next when the head changes	After changing the head, update tail.next = head

WEEK-5:

5A.

Aim: write a python program to implement the stack using the arrays. And also implement stack operations such as push, pop, peek and also display the stack elements.

Code:

dsa lab > week5 > 1.py > Stack

```python
class Stack:
    def __init__(self, size):
        self.stack = []
        self.size = size

    # Push operation
    def push(self, value):
        if len(self.stack) == self.size:
            print("Stack Overflow")
        else:
            self.stack.append(value)
            print(value, "pushed into stack")

    # Pop operation
    def pop(self):
        if len(self.stack) == 0:
            print("Stack Underflow")
        else:
            value = self.stack.pop()
            print("Popped element:", value)

    # Peek operation
    def peek(self):
        if len(self.stack) == 0:
            print("Stack is empty")
        else:
            print("Top element:", self.stack[-1])

    # Display operation
    def display(self):
        if len(self.stack) == 0:
            print("Stack is empty")
        else:
            print("Stack elements:")

            for i in range(len(self.stack) - 1, -1, -1):
                print(self.stack[i])


size = int(input("Enter stack size: "))
s = Stack(size)

while True:
    print("\n----- STACK MENU -----")
    print("1. Push")
    print("2. Pop")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        value = int(input("Enter value: "))
        s.push(value)

    elif choice == 2:
        s.pop()

    elif choice == 3:
        s.peek()

    elif choice == 4:
        s.display()
```

```python
    elif choice == 3:
        s.peek()

    elif choice == 4:
        s.display()

    elif choice == 5:
        print("Program exited.")
        break

    else:
        print("Invalid choice")
```

OUTPUT:

Pushing an element into the stack

```
======== RESTART: C:/Users/SREEHAAS/OneDrive/Desktop/dsa lab/week5/1.py ========
Enter stack size: 5

----- STACK MENU -----
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter value: 2
2 pushed into stack
```

Popping an element from the stack

```
----- STACK MENU -----
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 2
Popped element: 2
```

Peek element

```
----- STACK MENU -----
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 3
Stack is empty
```

Display all the elements in the stack

```
----- STACK MENU -----
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 4
Stack elements:
3
2
```

Exiting the program

```
----- STACK MENU -----
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program exited.
```

Explanation:

1. Class and Initialization

- A class named Stack is created.
- The __init__() method acts as the constructor.
- An empty list self.stack is created to store stack elements.
- The stack follows the **LIFO (Last In, First Out)** principle.

2. Push Operation

- The push() method is used to insert an element into the stack.
- The append() function adds the element to the end of the list.
- The newly inserted element becomes the **top element**.
- A message is displayed after the element is inserted.

3. Pop Operation

- The pop() method is used to remove the top element.
- The program first checks whether the stack is empty.
- If the stack is empty, **Stack Underflow** is displayed.
- Otherwise, the pop() function removes the last element.
- The removed element is displayed.

4. Peek Operation

- The peek() method is used to view the top element.
- The program checks whether the stack is empty.
- If the stack is empty, **Stack is empty** is displayed.
- Otherwise, self.stack[-1] is used to access the top element.
- The top element is displayed without removing it.

5. Display Operation

- The display() method is used to display all stack elements.
- The program first checks whether the stack is empty.
- If empty, **Stack is empty** is displayed.
- Otherwise, a for loop is used to traverse the stack.
- The elements are displayed from **top to bottom**.

6. Count Operation

- The count() method is used to find the number of elements in the stack.
- The len() function returns the number of elements.
- The count is displayed to the user.

Error table:

sno	Error obtained	Error rectification
1	Stack underflow	Check whether the stack is empty before poping
2	Name error	Define the class before creating the object

5b.

Aim: write a python program to implement the stack using the linked list. And also implement stack operations such as push, pop, peek,count and also display the stack elements.

Code:

dsa lab > week5 > 2.py > Node

```python
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


class Stack:
    def __init__(self):
        self.top = None
        self.count = 0

    # Push operation
    def push(self, value):
        new_node = Node(value)

        new_node.next = self.top
        self.top = new_node
        self.count += 1

        print(value, "pushed into stack")

    # Pop operation
    def pop(self):
        if self.top is None:
            print("Stack Underflow")
            return

        value = self.top.data
        self.top = self.top.next
        self.count -= 1

        print("Popped element:", value)

    # Peek operation
    def peek(self):
        if self.top is None:
            print("Stack is empty")
        else:
            print("Top element:", self.top.data)

    # Count operation
    def count_nodes(self):
        print("Number of elements:", self.count)

    # Display operation
    def display(self):
        if self.top is None:
            print("Stack is empty")
            return

        current = self.top

        print("Stack elements:")

        while current:
            print(current.data)
            current = current.next


stack = Stack()

```

Output:

Pushing an element into the stack

```
======== RESTART: C:/Users/SREEHAAS/OneDrive/Desktop/dsa lab/week5/2.py =====

----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 1
Enter value: 2
2 pushed into stack
```

Poping an element from the stack

```
----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 2
Popped element: 5
```

Peek element

```

----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 3
Top element: 3
```

Display all the elements in the stack

```
----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 5
Stack elements:
3
2
```

count

```
----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 4
Number of elements: 2
```

Exiting the program

```
----- STACK USING LINKED LIST -----
1. Push
2. Pop
3. Peek
4. Count
5. Display
6. Exit
Enter your choice: 6
Program exited.
```

Explanation:

1. Node Class

- A class named Node is created to represent each element of the linked list.
- The __init__() method initializes a node.
- self.data stores the value of the node.
- self.next stores the reference to the next node.
- Initially, self.next is set to None.

2. Stack Class

- A class named Stack is created to implement the stack operations.

- The __init__() method initializes the stack.
- self.top = None indicates that the stack is initially empty.
- The top variable stores the reference to the top node of the stack.

3. Push Operation

- The push() method is used to insert an element into the stack.
- A new node is created using Node(data).
- The new node is connected to the current top node using:

new_node.next = self.top

- The new node is then made the top node using:

self.top = new_node

- The inserted element is displayed.
- The operation follows the **LIFO (Last In, First Out)** principle.

4. Pop Operation

- The pop() method is used to remove the top element.
- The program first checks whether self.top is None.
- If self.top is None, the stack is empty and **Stack Underflow** is displayed.
- Otherwise, the data of the top node is stored in data.
- The top is moved to the next node using:

self.top = self.top.next

- The removed element is displayed.

5. Peek Operation

- The peek() method is used to view the top element without removing it.
- The program checks whether the stack is empty.
- If the stack is empty, **Stack is empty** is displayed.
- Otherwise, self.top.data is used to display the top element.
- The stack remains unchanged after the peek operation.

6. Display Operation

- The display() method is used to display all the elements of the stack.
- The program first checks whether the stack is empty.

- A temporary variable current is initialized with self.top.
- A while loop is used to traverse the linked list.
- current.data displays the value of each node.
- current = current.next moves to the next node.
- The elements are displayed from **top to bottom**.

7. Count Operation

- The count() method is used to find the number of elements in the stack.
- A variable count is initialized to 0.
- A temporary variable current starts from self.top.
- The linked list is traversed using a while loop.
- The count value is increased for every node.
- The total number of elements is displayed.

Error table:

sno	Error obtained	Error rectification
1	Incorrect push	Set new_node.next = self.top before updating self.top
2	Infinte loop	Use break when choice == 6

WEEK-6

A) AIM: Write a python program to implement stack operations such as push, pop, peek, display using an array and a linked list.

Program using Array:

```python
# Stack using Array
stack = []
MAX = 5
def push():
    if len(stack) == MAX:
        print("Stack Overflow")
    else:
        value = int(input("Enter element: "))
        stack.append(value)
        print("Element pushed successfully.")
def pop():
    if len(stack) == 0:
        print("Stack Underflow")
    else:
        value = stack.pop()
        print("Popped element:", value)
def peek():
    if len(stack) == 0:
        print("Stack is empty")
    else:
        print("Top element:", stack[-1])
def display():
    if len(stack) == 0:
        print("Stack is empty")
    else:
        print("Stack elements:")
        for i in range(len(stack) - 1, -1, -1):
            print(stack[i])
while True:
    print("\n===== STACK USING ARRAY =====")
    print("1. Push")
    print("2. Pop")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")
    choice = int(input("Enter your choice: "))
    if choice == 1:
        push()
    elif choice == 2:
        pop()
    elif choice == 3:
        peek()
    elif choice == 4:
        display()

    elif choice == 5:
        print("Program ended.")
        break
    else:
        print("Invalid choice.")
```

Output:

```
===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element: 12
Element pushed successfully.

===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element: 11
Element pushed successfully.

===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element: 54
Element pushed successfully.

===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 2
Popped element: 54

===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 4
Stack elements:
11
12
```

```
===== STACK USING ARRAY =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program ended.
```

Explanation:

This Python program implements a **Stack using an array (list)** and performs the operations **Push, Pop, Peek, and Display**. The stack follows the **LIFO (Last In, First Out)** principle, where the last inserted element is removed first. An empty list called stack is used to store the elements and MAX defines the maximum stack size. The **Push** operation adds a new element

using append() and checks for stack overflow. The **Pop** operation removes the top element using pop() and checks for stack underflow. The **Peek** operation displays the top element without removing it using stack[-1]. The **Display** operation prints all elements starting from the top. The program uses a **menu-driven approach**, allowing the user to repeatedly perform stack operations until the Exit option is selected.

6B Program using Linkedlist:

Code:

```
# Stack using Linked List
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
class Stack:
    def __init__(self):
        self.top = None
    # Push operation
    def push(self):
        value = int(input("Enter element: "))
        new_node = Node(value)
        new_node.next = self.top
        self.top = new_node
        print("Element pushed successfully.")
    # Pop operation
    def pop(self):
        if self.top is None:
            print("Stack Underflow")
        else:
            value = self.top.data
            self.top = self.top.next
            print("Popped element:", value)
    # Peek operation
    def peek(self):
        if self.top is None:
            print("Stack is empty")
        else:
            print("Top element:", self.top.data)
    # Display operation
    def display(self):
        if self.top is None:
            print("Stack is empty")
        else:
            temp = self.top
            print("Stack elements:")
            while temp is not None:
                print(temp.data)
                temp = temp.next
```

```
# Main Program
stack = Stack()
while True:
    print("\n===== STACK USING LINKED LIST =====")
    print("1. Push")
    print("2. Pop")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")
    choice = int(input("Enter your choice: "))
    if choice == 1:
        stack.push()
    elif choice == 2:
        stack.pop()
    elif choice == 3:
        stack.peek()
    elif choice == 4:
        stack.display()
    elif choice == 5:
        print("Program ended.")
        break
    else:
        print("Invalid choice.")
```

Output:

```
===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element: 21
Element pushed successfully.

===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 23
Invalid choice.

===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 25
Invalid choice.

===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 3
Top element: 21

===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 4
Stack elements:
21
```

```
===== STACK USING LINKED LIST =====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program ended.
```

Explanation:

This Python program implements a **Stack using a Linked List** and performs the operations **Push, Pop, Peek, and Display**. The stack follows the **LIFO (Last In, First Out)** principle. The Node class represents each node and contains data and next, while the Stack class uses the top pointer to point to the top node. The **Push** operation creates a new node and places it at the top of the stack. The **Pop** operation removes the top node and moves the top pointer to the next node. The **Peek** operation displays the data of the top node without removing it. The **Display** operation traverses the linked list from the top and prints all elements. The program uses a **menu-driven approach**, allowing the user to perform different stack operations repeatedly until the Exit option is selected.

Error Table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified
3.	Errors in push and pop operations	Rectified
4.	Errors in top pointer handling	Rectified
5.	Errors in display operation	Rectified

WEEK 7

7 a Write a Python program to implement Queue using Array and Linked List. Provide a main menu to select the implementation and perform Enqueue, Dequeue, Peek, and Display operations.

Code

dsa lab > week7 > 7a.py > ...

```python
# Queue Implementation using Array and Linked List

# Node class for Linked List
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


# Queue class
class Queue:

    def __init__(self):
        # Array Queue
        self.queue = []

        # Linked List Queue
        self.front = None
        self.rear = None

    # ================ ARRAY QUEUE ================

    def array_enqueue(self):
        data = int(input("Enter element: "))
        self.queue.append(data)
        print("Element inserted successfully.")

    def array_dequeue(self):
        if len(self.queue) == 0:
            print("Queue is empty.")
        else:
            data = self.queue.pop(0)
            print("Deleted element:", data)

    def array_peek(self):
        if len(self.queue) == 0:
            print("Queue is empty.")
        else:
            print("Front element:", self.queue[0])

    def array_display(self):
        if len(self.queue) == 0:
            print("Queue is empty.")
        else:
            print("Queue elements:")
            for element in self.queue:
                print(element, end=" ")
            print()

```

dsa lab > week7 > 7a.py > ...

```
class Queue:
    # ================ LINKED LIST QUEUE ================

    def linked_enqueue(self):
        data = int(input("Enter element: "))

        new_node = Node(data)

        if self.front is None:
            self.front = new_node
            self.rear = new_node
        else:
            self.rear.next = new_node
            self.rear = new_node

        print("Element inserted successfully.")

    def linked_dequeue(self):
        if self.front is None:
            print("Queue is empty.")
        else:
            data = self.front.data

            self.front = self.front.next

            if self.front is None:
                self.rear = None

            print("Deleted element:", data)

    def linked_peek(self):
        if self.front is None:
            print("Queue is empty.")
        else:
            print("Front element:", self.front.data)

    def linked_display(self):
        if self.front is None:
            print("Queue is empty.")
        else:
            temp = self.front

            print("Queue elements:")

            while temp is not None:
                print(temp.data, end=" ")
                temp = temp.next

            print()
```

dsa lab > week7 > 7a.py > ...

```
    # ================ ARRAY MENU ================

    if choice == 1:

        while True:

            print("\n------ QUEUE USING ARRAY ------")
            print("1. Enqueue")
            print("2. Dequeue")
            print("3. Peek")
            print("4. Display")
            print("5. Back to Main Menu")
            print("--------------------------------")

            option = int(input("Enter your choice: "))

            if option == 1:
                q.array_enqueue()

            elif option == 2:
                q.array_dequeue()

            elif option == 3:
                q.array_peek()

            elif option == 4:
                q.array_display()

            elif option == 5:
                break

            else:
                print("Invalid choice.")

    # ================ LINKED LIST MENU ================

    elif choice == 2:

        while True:

            print("\n--- QUEUE USING LINKED LIST ---")
            print("1. Enqueue")
            print("2. Dequeue")
            print("3. Peek")
            print("4. Display")
            print("5. Back to Main Menu")
            print("--------------------------------")

            option = int(input("Enter your choice: "))

            if option == 1:
                q.linked_enqueue()

            elif option == 2:
                q.linked_dequeue()

            elif option == 3:
                q.linked_peek()

            elif option == 4:
                q.linked_display()

            elif option == 5:
                break


            else:
                print("Invalid choice.")

    # ================ EXIT ================

    elif choice == 3:
        print("Program ended.")
        break

    else:
```

Output


PS C:\AMRITA\2nd year\1 SEMESTER\DSA> C:\Use
========== MAIN MENU ==========
1. Queue using Array
2. Queue using Linked List
3. Exit
==============================
Enter your choice: 1
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu

Enter your choice: 1
Enter element: 23
Element inserted successfully.
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu

Enter your choice: 1
Enter element: 234
Element inserted successfully.
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu

Enter your choice: 34
Invalid choice.
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu

Enter your choice: 1
Enter element: 34
Element inserted successfully.
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue

```
------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
------------------------------
Enter your choice: 1
Enter element: 43
Element inserted successfully.


------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
------------------------------
Enter your choice: 2
Deleted element: 23

------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
------------------------------
Enter your choice: 3
Front element: 234

------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
------------------------------
Enter your choice: 4
Queue elements:
234 34 43

------ QUEUE USING ARRAY ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
------------------------------
Enter your choice: 5

========== MAIN MENU ==========
1. Queue using Array
2. Queue using Linked List
3. Exit
==============================
Enter your choice: 2
```



Expalnation

This program implements a Queue using Array and Linked List.

- Node class: Creates nodes for the linked list.
- Queue class: Contains all queue operations.
- Array Queue: Uses a Python list for storing elements.
- Linked List Queue: Uses front and rear pointers.
- Enqueue: Inserts an element at the rear.
- Dequeue: Removes an element from the front.

- Peek: Displays the front element.
- Display: Shows all queue elements.
- Main Menu: Allows the user to select Array or Linked List implementation.
- Exit: Terminates the program.

Simple Operation Flow

Start

↓

Main Menu

↓

Choose Array / Linked List

↓

Choose Operation

↓

Enqueue / Dequeue / Peek / Display

↓

Perform Operation

↓

Back to Menu

↓

Exit

Simple Code Examples

Enqueue:

queue.append(10)

Dequeue:

queue.pop(0)

Peek:

print(queue[0])

Linked List Enqueue:

rear.next = new_node

rear = new_node

Linked List Dequeue:

front = front.next

The queue follows FIFO (First In, First Out).

Error Table

Error	Cause	Solution
NameError	Variable or object is not defined	Create the object before using it
ValueError	User enters non-numeric input	Enter a valid integer
AttributeError	Incorrect attribute or method name	Check the class and method names
Queue is empty	Dequeue or Peek is performed on an empty queue	Insert an element first
IndexError	Trying to access an invalid list index	Check whether the queue is empty
IndentationError	Incorrect indentation in Python	Maintain proper indentation
SyntaxError	Incorrect Python syntax	Check brackets, colons, and statements

7b Write a Python program to implement Circular Queue using Array and Linked List. Provide a main menu to select the implementation and perform Enqueue, Dequeue, Peek, and Display operations.

Code

dsa lab > week7 > 7b.py > ...

```python
# Circular Queue using Array and Linked List


# Node class for Linked List
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


# Circular Queue Class
class CircularQueue:

    def __init__(self, size):
        # Array Queue
        self.size = size
        self.queue = [None] * size
        self.front = -1
        self.rear = -1

        # Linked List Queue
        self.ll_front = None
        self.ll_rear = None

    # ================ ARRAY CIRCULAR QUEUE ================

    def array_enqueue(self):
        data = int(input("Enter element: "))

        # Check if queue is full
        if (self.rear + 1) % self.size == self.front:
            print("Queue is full")
            return

        # First element
        if self.front == -1:
            self.front = 0
            self.rear = 0

        else:
            self.rear = (self.rear + 1) % self.size

        self.queue[self.rear] = data

        print("Element inserted successfully")

    def array_dequeue(self):

        if self.front == -1:
            print("Queue is empty")
            return

        data = self.queue[self.front]
```

```
        self.queue[self.front] = None

        print("Deleted element:", data)

        # Only one element
        if self.front == self.rear:
            self.front = -1
            self.rear = -1

        else:
            self.front = (self.front + 1) % self.size

    def array_peek(self):

        if self.front == -1:
            print("Queue is empty")
        else:
            print("Front element:", self.queue[self.front])

    def array_display(self):

        if self.front == -1:
            print("Queue is empty")
            return

        print("Queue elements:")

        i = self.front

        while True:
            print(self.queue[i], end=" ")

            if i == self.rear:
                break

            i = (i + 1) % self.size

        print()

    # ================ LINKED LIST CIRCULAR QUEUE ================

    def linked_enqueue(self):
        data = int(input("Enter element: "))

        new_node = Node(data)

        # Queue is empty
        if self.ll_front is None:

            self.ll_front = new_node
            self.ll_rear = new_node
```

```
    def linked_enqueue(self):
            # Point rear to front
            self.ll_rear.next = self.ll_front

        else:

            # Insert new node after rear
            new_node.next = self.ll_front
            self.ll_rear.next = new_node

            # Move rear
            self.ll_rear = new_node

        print("Element inserted successfully")

    def linked_dequeue(self):

        if self.ll_front is None:
            print("Queue is empty")
            return

        data = self.ll_front.data

        print("Deleted element:", data)

        # Only one node
        if self.ll_front == self.ll_rear:

            self.ll_front = None
            self.ll_rear = None

        else:

            self.ll_front = self.ll_front.next
            self.ll_rear.next = self.ll_front

    def linked_peek(self):

        if self.ll_front is None:
            print("Queue is empty")
        else:
            print("Front element:", self.ll_front.data)

    def linked_display(self):

        if self.ll_front is None:
            print("Queue is empty")
            return

        print("Queue elements:")

        temp = self.ll_front
```

```python
# ================ MAIN PROGRAM ================

size = int(input("Enter size of Array Circular Queue: "))

q = CircularQueue(size)


while True:

    print("\n========== MAIN MENU ==========")
    print("1. Circular Queue using Array")
    print("2. Circular Queue using Linked List")
    print("3. Exit")
    print("==============================")

    choice = int(input("Enter your choice: "))


    # ================ ARRAY MENU ================

    if choice == 1:

        while True:

            print("\n------ ARRAY CIRCULAR QUEUE ------")
            print("1. Enqueue")
            print("2. Dequeue")
            print("3. Peek")
            print("4. Display")
            print("5. Back to Main Menu")
            print("----------------------------------")

            option = int(input("Enter your choice: "))

            if option == 1:
                q.array_enqueue()

            elif option == 2:
                q.array_dequeue()

            elif option == 3:
                q.array_peek()

            elif option == 4:
                q.array_display()

            elif option == 5:
                break

            else:
                print("Invalid choice")

```

```python

    # ================ LINKED LIST MENU ================

    elif choice == 2:

        while True:

            print("\n--- LINKED LIST CIRCULAR QUEUE ---")
            print("1. Enqueue")
            print("2. Dequeue")
            print("3. Peek")
            print("4. Display")
            print("5. Back to Main Menu")
            print("-----------------------------------")

            option = int(input("Enter your choice: "))

            if option == 1:
                q.linked_enqueue()

            elif option == 2:
                q.linked_dequeue()

            elif option == 3:
                q.linked_peek()

            elif option == 4:
                q.linked_display()

            elif option == 5:
                break

            else:
                print("Invalid choice")


    # ================ EXIT ================

    elif choice == 3:

        print("Program ended")
        break

    else:

        print("Invalid choice")
```

Output

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users\hemsj\AppData\Local\Python\pythoncore-3.14-64\python.exe "c:/AMRITA/2nd year/1 SEMESTER/DSA/dsa lab/week7/7b.py"
Enter size of Array Circular Queue: 4

========== MAIN MENU ==========
1. Circular Queue using Array
2. Circular Queue using Linked List
3. Exit
================================
Enter your choice: 1

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
---------------------------------
Enter your choice: 1
Enter element: 234
Element inserted successfully

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
---------------------------------
Enter your choice: 1
Enter element: 343
Element inserted successfully

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
---------------------------------
Enter your choice: 2
Deleted element: 234

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
---------------------------------
Enter your choice: 3
Front element: 343

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
```

```
PS C:\AMRITA\2nd year\1 SEMESTER\DSA> & C:\Users

------ ARRAY CIRCULAR QUEUE ------
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 5

========== MAIN MENU ==========
1. Circular Queue using Array
2. Circular Queue using Linked List
3. Exit
==============================
Enter your choice: 2

--- LINKED LIST CIRCULAR QUEUE ---
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 1
Enter element: 23
Element inserted successfully

--- LINKED LIST CIRCULAR QUEUE ---
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 2
Deleted element: 23

--- LINKED LIST CIRCULAR QUEUE ---
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 3
Queue is empty

--- LINKED LIST CIRCULAR QUEUE ---
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 4
Queue is empty
```

```
--- LINKED LIST CIRCULAR QUEUE ---
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Back to Main Menu
----------------------------------
Enter your choice: 5

========== MAIN MENU ==========
1. Circular Queue using Array
2. Circular Queue using Linked List
3. Exit
==============================
Enter your choice: 3
Program ended
PS C:\AMRITA\2nd year\1 SEMESTER\DSA>
```

Expalnation :

Code Explanation

This program implements a Circular Queue using Array and Linked List.

- Node class: Creates nodes for the linked list.
- Circular Queue class: Contains both array and linked list operations.
- Array Queue: Uses an array and front and rear positions.
- Linked List Queue: Uses nodes with front and rear pointers.
- Enqueue: Inserts an element at the rear.
- Dequeue: Removes an element from the front.
- Peek: Displays the front element.

- Display: Shows all elements in the queue.
- Circular connection: After reaching the last position, the queue can return to the first position.
- Main Menu: Allows the user to select Array or Linked List implementation.
- Exit: Terminates the program.

Simple Operation Flow

Start

↓

Enter Array Size

↓

Main Menu

↓

Choose Array / Linked List

↓

Choose Operation

↓

Enqueue / Dequeue / Peek / Display

↓

Perform Operation

↓

Back to Main Menu

↓

Exit

Simple Code Examples

Circular movement in Array:

rear = (rear + 1) % size

This moves rear to the next position. If it reaches the last position, it returns to the first position.

Circular movement of Front:

front = (front + 1) % size

Circular Linked List:

rear.next = front

This connects the last node back to the first node.

Check if Array Queue is Full:

(rear + 1) % size == front

Check if Array Queue is Empty:

front == -1

Example

For a queue of size 5:

Enqueue: 10 20 30 40 50

[10] [20] [30] [40] [50]

↑ ↑

front rear

After deleting 10 and 20, the empty positions can be reused:

[60] [70] [30] [40] [50]

↑ ↑

rear front

The circular queue follows FIFO (First In, First Out) while allowing unused positions to be reused.

Error Table

Error	Cause	Solution
NameError: name 'q' is not defined	q object was not created before using it	Create q = CircularQueue(size) before the main menu
ValueError: invalid literal for int()	A non-number was entered for size/data/choice	Enter only integer values
AttributeError	Wrong method or variable name was used	Check method and variable names

Error	Cause	Solution
Queue is Empty	Dequeue or Peek was selected before inserting data	Enqueue an element first
Queue is Full	Array circular queue has no free space	Dequeue an element and then enqueue
Linked List Empty	Dequeue/Peek/Display was selected before insertion	Insert an element first
Wrong Circular Position	front or rear was updated incorrectly	Use (position + 1) % size for circular movement
Infinite loop in Linked List Display	Circular link was not handled correctly	Stop when the pointer reaches ll_front again

WEEK 8

(8) write a python program to implement a binary tree with its operations using a array and a linked list

AIM: to write a python program to implement a binary tree with its operations using a array and a linked list

Using Array

Program:

```python
# BINARY TREE USING ARRAY REPRESENTATION
class BinaryTreeArray:
    def __init__(self, size):
        self.tree = [None] * size
        self.size = size

# Insert root
    def set_root(self, data):
        self.tree[0] = data
# Set left child
    def set_left(self, parent_index, data):
        child_index = 2 * parent_index + 1

        if child_index < self.size:
            self.tree[child_index] = data
        else:
            print("Index out of range!")
# Set right child
    def set_right(self, parent_index, data):
        child_index = 2 * parent_index + 2

        if child_index < self.size:
            self.tree[child_index] = data
        else:
            print("Index out of range!")
# Preorder Traversal
    def preorder(self, index=0):

        if index >= self.size or self.tree[index] is None:
            return

        print(self.tree[index], end=" ")

        self.preorder(2 * index + 1)
        self.preorder(2 * index + 2)

# Inorder Traversal
    def inorder(self, index=0):

        if index >= self.size or self.tree[index] is None:
            return

        self.inorder(2 * index + 1)

        print(self.tree[index], end=" ")

        self.inorder(2 * index + 2)
# Postorder Traversal
    def postorder(self, index=0):

        if index >= self.size or self.tree[index] is None:
            return
```

```python
class BinaryTreeArray:
    def postorder(self, index=0):

        self.postorder(2 * index + 1)
        self.postorder(2 * index + 2)

        print(self.tree[index], end=" ")
# Level-order Traversal
    def level_order(self):

        for value in self.tree:

            if value is not None:
                print(value, end=" ")
# Display Array
    def display(self):
        print("\nArray Representation:")

        for i in range(self.size):
            print(f"Index {i}: {self.tree[i]}")
# MAIN PROGRAM
tree = BinaryTreeArray(7)
# Create the tree
tree.set_root('A')
# Children of A
tree.set_left(0, 'B')
tree.set_right(0, 'C')
# Children of B
tree.set_left(1, 'D')
tree.set_right(1, 'E')
# Right child of C
tree.set_right(2, 'F')
# Display tree
tree.display()
# Traversals
print("\nPreorder: ", end="")
tree.preorder()
print("\nInorder: ", end="")
tree.inorder()
print("\nPostorder: ", end="")
tree.postorder()
print("\nLevel-order: ", end="")
tree.level_order()
```


Output:

```
Array Representation:
Index 0: A
Index 1: B
Index 2: C
Index 3: D
Index 4: E
Index 5: None
Index 6: F

Preorder: A B D E C F
Inorder: D B E A C F
Postorder: D E B F C A
Level-order: A B C D E F
```

Using Linked List

Program



```
class Node:
    def __init__(self, data):
        self.data = data
        self.left = None
        self.right = None

class BinaryTree:
    def __init__(self):
        self.root = None

    # Insert a node
    def insert(self, value):
        new_node = Node(value)

        if self.root is None:
            self.root = new_node
            return

        queue = [self.root]

        while queue:
            current = queue.pop(0)

            if current.left is None:
                current.left = new_node
                return
            else:
                queue.append(current.left)

            if current.right is None:
                current.right = new_node
                return
            else:
                queue.append(current.right)

    # Search a node
    def search(self, value):
        if self.root is None:
            return False

        queue = [self.root]

        while queue:
            current = queue.pop(0)

            if current.data == value:
                return True

            if current.left:
                queue.append(current.left)

            if current.right:
                queue.append(current.right)

    def inorder(self, node):
            self.inorder(node.left)
            print(node.data, end=" ")
            self.inorder(node.right)

    # Preorder Traversal
    def preorder(self, node):
        if node is not None:
            print(node.data, end=" ")
            self.preorder(node.left)
            self.preorder(node.right)

    # Postorder Traversal
    def postorder(self, node):
        if node is not None:
            self.postorder(node.left)
            self.postorder(node.right)
            print(node.data, end=" ")

    # Level Order Traversal
    def level_order(self):
        if self.root is None:
            return

        queue = [self.root]

        while queue:
            current = queue.pop(0)

            print(current.data, end=" ")

            if current.left:
                queue.append(current.left)

            if current.right:
                queue.append(current.right)


# Main program
bt = BinaryTree()

bt.insert(25)
bt.insert(15)
bt.insert(40)
bt.insert(10)
bt.insert(20)
bt.insert(30)
bt.insert(50)

print("Inorder:")
bt.inorder(bt.root)
```

```
print("Inorder:")
bt.inorder(bt.root)

print("\nPreorder:")
bt.preorder(bt.root)

print("\nPostorder:")
bt.postorder(bt.root)

print("\nLevel Order:")
bt.level_order()

print("\n\nSearching for 30:")

if bt.search(30):
    print("30 found")
else:
    print("30 not found")
```

Output:

```
Inorder:
10 15 20 25 30 40 50
Preorder:
25 15 10 20 40 30 50
Postorder:
10 20 15 30 50 40 25
Level Order:
25 15 40 10 20 30 50

Searching for 30:
30 found
```

Short Explanation

1. Binary Tree Using an Array:
The program stores tree nodes in an array. The root is stored at index 0, and the left and right children are calculated using 2*i+1 and 2*i+2. It supports insertion, display, and preorder traversal.

2. Binary Tree Using a Linked List:
The program creates nodes using a Node class, where each node contains data and references to its left and right children. It supports insertion and preorder, inorder, and postorder traversals.

Error Table

S. No.	Error / Condition	Reason	Correction
1	Index Error	Array index exceeds its size.	Increase array size.
2	Parent does not exist	Parent node is empty.	Insert the parent first.
3	Root already exists	Root is already occupied.	Use the existing root.
4	Left child already exists	Left child position is occupied.	Select an empty position.
5	Right child already exists	Right child position is occupied.	Select an empty position.
6	Incorrect traversal output	Traversal order is incorrect.	Follow the correct traversal sequence.

Week 9

(9) write a python program to implement a binary search treee with its operation and traversals

AIM: to write a python program to implement a binary search treee with its operation and traversals

Code:

week9 > 9.py > ...

```python
class Node:
    def __init__(self, data):
        self.data = data
        self.left = None
        self.right = None


class BST:
    def insert(self, root, data):
        if root is None:
            return Node(data)

        if data < root.data:
            root.left = self.insert(root.left, data)
        elif data > root.data:
            root.right = self.insert(root.right, data)

        return root

    def search(self, root, key):
        if root is None or root.data == key:
            return root

        if key < root.data:
            return self.search(root.left, key)
        return self.search(root.right, key)

    def inorder(self, root):
        if root:
            self.inorder(root.left)
            print(root.data, end=" ")
            self.inorder(root.right)

    def preorder(self, root):
        if root:
            print(root.data, end=" ")
            self.preorder(root.left)
            self.preorder(root.right)

    def postorder(self, root):
        if root:
            self.postorder(root.left)
            self.postorder(root.right)
            print(root.data, end=" ")


bst = BST()
root = None

for value in [50, 30, 70, 20, 40, 60, 80]:
    root = bst.insert(root, value)

print("Inorder Traversal:")
bst.inorder(root)


print("\nPreorder Traversal:")
bst.preorder(root)

print("\nPostorder Traversal:")
bst.postorder(root)

key = 40
if bst.search(root, key):
    print("\nElement", key, "found")
else:
    print("\nElement", key, "not found")

```

Output:



Short Explanation

A Binary Search Tree (BST) is a binary tree in which smaller values are stored in the left subtree and larger values are stored in the right subtree.

- **Node(): Creates a node with data and left and right references.**
- **insert(): Inserts an element in the correct position.**
- **search(): Searches for a specified element.**
- **inorder(): Visits left subtree, root, and right subtree. It displays values in ascending order for a BST.**
- **preorder(): Visits root, left subtree, and right subtree.**
- **postorder(): Visits left subtree, right subtree, and root.**

Error Table

S. No.	Error / Condition	Reason	Correction
1	RecursionError	Excessively deep recursion in an unbalanced tree.	Use a balanced BST or iterative methods.
2	Element not found	The search value is not present in the tree.	Check the inserted values and search key.
3	Incorrect output	Traversal order is implemented incorrectly.	Follow the correct traversal sequence.
4	Duplicate element ignored	The program does not insert duplicate values.	Add duplicate-handling logic if required.
5	AttributeError	An invalid node reference is accessed.	Check whether the node is None before accessing its data.