

Centre No: _____

Centre Name: _____

Code: _____

Subject: _____

Candidate Number: _____

Candidate Name: Henry

Signature: _____

Do not
write in
this
margin

Q1 (a) INTEGER

REAL

CHAR

BOOLEAN

(b) 2nd Place is invalid as number shouldn't be the first character
 first place valid camel
 while is invalid, it stands for while loop
 studentName is valid camel

(c) HelloWorld

print() will output on the same line

println will output on separated lines automatically

Q2 (a) 22

(b) a

(c) Information

(d) Information I

(e) 12

(f) error, string "xyz" doesn't exist

(g) ~~IN~~ INFORMATION TECHNOLOGY

(h) Computer Technology

Q3	Line	x	y (n)	y (L)	Output
	1	5	2	1	/
	2	8	2	10	/
	3	5	2	10	/
	4	8	2	10	"Inside update 1/2 8"
	5	5			

Q3	Line	x (G)	y (G)	y (L)	Output
	1	8	2	10	Inside update(): 8 10
	2	8	2	13	Inside modify(): 8 13
	03	8	2	1	Outside: 8 2

(b) y printed inside update is a new ^{local} variable different from global variable printed in main

Q4

(a) variable score isn't defined in increaseScore(). It is a new local variable, so score + 10 doesn't make sense

```

static void increaseScore() {
    score = score + 10;
}

```

Final score: 10

Q5 ~~DECLARE~~ studentScore: ~~INTEGER~~ INTEGER

DECLARE studentAverage: REAL

DECLARE studentGrade: CHAR

DECLARE studentName: ~~STR~~ STRING

DECLARE ~~it~~ ifPass: BOOLEAN

studentScore ← 90

studentAverage ← 80.5

studentGrade ← B

studentName ← Alex

student ifPass ← TRUE

~~OUTPUT~~ OUTPUT (studentName + " get" + "studentScore" +
"in the exam".

Centre No:

Centre Name:

Code: Subject:

Candidate Number: Candidate Name: Henry

Signature:

Do not
write in
this
margin

~~Q6/1 OUTPUT (MID (2, 8, 16)) = MID (10, 6, 7)~~

16/ OUTPUT (MID (2, 8))

6/ OUTPUT (MID (10, 16))

16/ OUTPUT (UCASE (MID (2, 16)))

Q6/ 16/ OUTPUT (MID (full Name (2, 16)))

16/ OUTPUT (MID (full Name, 2, 8))

6/ OUTPUT (MID (full Name, 10, 16))

16/ OUTPUT (UCASE (MID (2, full Name (2, 16)))

6/ OUT

[illegible]