A local hyperbolic shift with exact scri nullness

Spherical prototype, boundary closure, and qualification failures

Numerical formulation note

27 October 2026

Abstract

We replace the elliptic shift by an auxiliary Gamma driver while retaining the full variable-metric spherical Z4c equations. Algebraic elimination enforces the normal nullness relation at every Runge–Kutta stage and accepted state. Across the initial 31 bounded runs the maximum relative nullness error is one binary64 machine epsilon. A source-restored candidate exhibits approximately second-order spatial self-convergence and fourth-order timestep convergence in short regular-center tests. Subsequent three-grid puncture tests reach $3M$ with decreasing errors, but duration extensions fail near $8M$. It is not qualified for the persistent $100M$ target. Exact nullness therefore succeeds as a discrete gauge identity without establishing full boundary compatibility, puncture regularity, or improved robustness over the elliptic formulation.

1 Preserved baseline and proposed driver

The reference is commit `a9214bccf` of the isolated elliptic-shift checkout. Its tracked state, jobs, and historical evidence were left untouched. The new branch is `codex/hyperboloidal-hyperbolic-shift`. The reference $N = 1025$ wormhole evolution reached coordinate $t = 500$ with final relative apparent-horizon mass error 1.14804×10^{-6}; that single-grid result is a duration certificate, not a convergence proof.

Use $\Omega = (1-r^2)/2$, $A = (1+r^2)/2$, $u = \alpha - A$, $p = K_{\rm phys} - 2\Theta_{\rm phys}$, and $\mathcal{D}_t = \partial_t - \beta\partial_r$. The twice-conformal spatial metric has components $(g, r^2 g^{-1/2}, r^2 g^{-1/2})$. Both g and the independent Z4 connection Λ^r evolve. The metric-built connection is

$$V^r = \frac{g'}{g^2} + \frac{2}{r}(\sqrt{g} - g^{-1}), \qquad Z_r = \frac{g}{2}(\Lambda^r - V^r). \tag{1}$$

It is a diagnostic; Λ^r is never replaced by V^r in the bulk.

The retained lapse and relaxation flux are

$$\mathcal{D}_t\alpha = r^2 + \frac{-F(p+3) + r(\alpha\beta + r) - 2\xi\alpha u + 16\Omega^4 r^2 u/A}{\Omega} + \eta\chi\left[wB' + (w' + 2w/r)B\right], \tag{2}$$

$$\tau\mathcal{D}_t B = \kappa w u' - B, \qquad F = \alpha^2 + 4\Omega^2\alpha, \quad \eta = \frac{(1+\epsilon)\alpha}{\alpha + \epsilon A}. \tag{3}$$

Here $\kappa = 0.005$, $\tau = 0.02$, $\epsilon = 10^{-4}$, and $\xi = 1 + 2(1-r^2)^4$. The baseline window w equals one at the puncture and vanishes for $r \geq 0.8$, with transition width 0.24. The attenuation multiplies the flux outside its divergence. The disclosed Appendix-C scalar-Θ source modification and constant Z4 damping $(\kappa_1, \kappa_2) = (4, -0.99)$ are retained.

With a separate shift auxiliary D, the candidate is

$$\mathcal{D}_t\beta = -r + \mu D - \xi_\beta \frac{\beta + r}{\Omega}, \tag{4}$$

$$\mathcal{D}_t D = \mathcal{D}_t \Lambda^r - \eta_D D, \qquad \eta_D = 1, \tag{5}$$

$$\mu = \frac{3}{4}\lambda\chi\left(F + g\eta\kappa w^2/\tau\right), \qquad \lambda = 2. \tag{6}$$

The analytic source $-r$ cancels the reference shift advection at Minkowski equilibrium. No numerical Einstein-equation RHS is subtracted. The first candidate used $\xi_\beta = 0$; the stronger tested candidate uses $\xi_\beta = 4$. This is a hyperboloidal adaptation of the auxiliary Gamma-driver family discussed in Vañó-Viñuales and Husa (2018), with a different speed choice and exact algebraic nullness closure.

2 Exact nullness and compatible boundary variables

Let $n_i = -\partial_i\Omega$ point outward, since Ω is positive inside the domain, and let $\bar{\gamma}_{ij} = \tilde{\gamma}_{ij}/\chi$ be the regular spatial metric. With $\partial_t\Omega = 0$,

$$\bar{g}^{ab}\Omega_a\Omega_b = \bar{\gamma}^{ij}n_i n_j - \frac{(\beta^i n_i)^2}{\alpha^2} = 0. \tag{7}$$

Defining $s_i = n_i/(\bar{\gamma}^{jk}n_j n_k)^{1/2}$ gives the future branch $\beta^i s_i = -\alpha$. A boundary representation is

$$\beta^i = \beta^i_T - \alpha s^i, \qquad s_i\beta^i_T = 0. \tag{8}$$

Nullness determines one normal component. Tangential coordinate choices remain separate. For fixed Ω_i, the moving-normal rate is

$$\partial_t s_i = \frac{1}{2}s_i s^k s^l \partial_t \bar{\gamma}_{kl}, \qquad s_i\partial_t\beta^i = -\partial_t\alpha - \beta^i\partial_t s_i. \tag{9}$$

Thus evolving the metric cannot be omitted when differentiating the condition.

In spherical symmetry the dependent shift endpoint is reconstructed directly:

$$\beta_1 = -\alpha_1\sqrt{\chi_1/g_1}, \qquad \dot{\beta}_1 = \beta_1\left(\frac{\dot{\alpha}_1}{\alpha_1} + \frac{\dot{\chi}_1}{2\chi_1} - \frac{\dot{g}_1}{2g_1}\right). \tag{10}$$

The lapse clock is $\alpha_1 = 1$, $\dot{\alpha}_1 = 0$. Every stage reconstructs β_1 before spatial derivatives, and every accepted state is reconstructed again. The differentiated relation alone would not enforce the discrete identity.

Writing $v = \beta + r$, the regular limit of the restoring term is $+\xi_\beta v'_1$ when $v_1 = 0$. The same boundary datum determines the auxiliary trace through the first driver equation:

$$D_1 = \frac{\dot{\beta}_1 - \beta_1\beta'_1 + 1 - \xi_\beta v'_1}{\mu_1}. \tag{11}$$

There is no second independently prescribed value for D. Its endpoint storage slot is eliminated. Interior D and Λ^r remain independent. This changes a gauge boundary closure; it does not project the Hamiltonian, momentum, or Z4 constraints. The derivative stencil in Eq. (11) is the same one used in the shift equation.

All geometric equations are reevaluated using the unreduced tensor kernel, as $q_t = R_q + S_q/\Omega$. At actual scri the candidate uses $R_q - S'_q$, with S' obtained from the complete variable-metric numerator. Neither the elliptic relation for β' nor its $g = 1$ endpoint equations are substituted. No floor is applied to Ω.

The retained weak regularity residuals are

$$\mathcal{C} = \big(\chi - g,\ 0,\ A_{rr} - g'/6 + 2\chi'/3,\ p+3,\ \Theta,\ \Lambda^r - V^r,\ 0\big)\,. \tag{12}$$

They select the same clock-compatible asymptotic phase, allowing the endpoint value of g to evolve. The endpoint rates receive $4S_q/h_{\rm end} - 8\mathcal{C}_q/h_{\rm end}$. The restoring numerator $-\xi_\beta v$ is monitored separately. These traces do not enforce the entire derivative hierarchy: on this phase, for example, $S_\Lambda = 0$ also requires $2p' + \Theta' = 6A_{rr}/g$. Neither all numerators nor the raw lapse-clock rate are imposed exactly. The clock override and finite penalties therefore still require a stability and compatibility assessment.

3 Characteristic audit and its limits

An interior first-order normal reduction uses

$$U = (\chi', g', A_{rr}, \delta p/\Omega, \Theta/\Omega, \Lambda^r, \alpha', \beta', B', D). \tag{13}$$

For $\mathcal{D}_t U = P\partial_r U$, exact symbolic factorization gives

$$\det(zI - P) = z^2(z^2 - c_P^2)^2(z^2 - c_L^2)(z^2 - c_S^2), \tag{14}$$

where

$$c_P^2 = \alpha^2\chi/g, \quad c_L^2 = F\chi/g + \eta\chi\kappa w^2/\tau, \quad c_S^2 = 4\mu/(3g) = \lambda c_L^2. \tag{15}$$

Coordinate speeds are $-\beta$, twice, together with $-\beta \pm c_P$, each twice, $-\beta \pm c_L$, and $-\beta \pm c_S$. Native tensor coefficient checks agree with this scalar symbol to 8.4×10^{-12} or better.

At normalized scri $(\alpha, \chi, g, \beta) = (1, 1, 1, -1)$ and $w = 0$. For $\lambda = 2$ the scalar reduction has one incoming mode, six outgoing modes, and three tangent modes. Exact eigenspaces are complete there. The incoming shift mode motivates one normal gauge datum. For $\lambda < 1$ there is no incoming shift mode; adding an independent Dirichlet datum would require a different compatibility argument. For $\lambda = 1$, the light-speed eigenvalues each have algebraic multiplicity four but geometric multiplicity three: this driver choice is defective and was not adopted.

The real speeds in Eq. (14) alone are not a proof of strong hyperbolicity. Numerical positive-geometry samples and exact normalized-scri eigenspaces support the scalar candidate, but a uniform symmetrizer for arbitrary geometry has not been constructed. The p/Ω reduction is itself singular at scri, so its finite limiting matrix does not prove well-posedness of the actual boundary equations. At the exact collapsed limit $\alpha = \chi = 0$, the displayed matrix is nonzero and nilpotent of index two, hence defective. No uniform puncture estimate follows from a positive lapse floor. The full three-dimensional vector and tensor sectors, including a direction-independent telegrapher extension, remain to be qualified.

4 Numerical implementation and short-time evidence

The complete spherical tensor equations evolve g, A_{rr}, p, Θ, and Λ^r freely. Only determinant and trace-free algebraic identities are built into the spherical tensor representation. Seven-point finite differences, biased advection, KO8 strength 0.5 with the baseline radial taper, and classical RK4 are used. Regular-center tests use half cells at the center and an actual scri node. Their KO8 acts on stored deviations; it is distinct from the historical regular-center KO6 filter on rescaled tensor coefficients. The matched elliptic controls use the same full tensor kernel and numerical settings. Their coordinate profiles need not match those of the hyperbolic gauge.

The finite lapse pulse is a compact smooth bump of amplitude 0.01, centered at $r = 0.4$ with half-width 0.12. With $\xi_\beta = 4$, grids $N = 65, 129, 257$ reach $t = 1$. The mixed-field self-differences, interpolated with seven-point polynomials to the coarse grid, are 1.38688×10^{-5} and 3.42764×10^{-6}, giving approximate order 2.02. This is an observed short-test order, not sixth-order accuracy of the complete scheme. At fixed $N = 65$ and $t = 0.15$, halving the timestep twice gives differences 8.22131×10^{-10} and 5.12329×10^{-11}, or order 4.00. Boundary and bulk accuracy are not interchangeable.

Gauge and resolution at $t = 1$	$\|H\|_{r^2dr}$	$\|M_r\|_{r^2dr}$	scri pole
Hyperbolic, $N = 65$	4.31×10^{-4}	7.08×10^{-4}	3.22×10^{-5}
Hyperbolic, $N = 129$	2.47×10^{-4}	3.54×10^{-4}	1.21×10^{-5}
Hyperbolic, $N = 257$	7.80×10^{-5}	9.23×10^{-5}	5.07×10^{-6}
Elliptic, $N = 129$	2.23×10^{-5}	3.51×10^{-5}	8.27×10^{-8}

The new gauge has larger constraint errors than the matched elliptic control. Radial-weighted constraint norms are useful consistency diagnostics, but their finite-error values are gauge dependent. Apparent-horizon mass supplies the invariant puncture comparison below.




Figure 1: Finite pulse with $\xi_\beta = 4$. Constraint errors decrease under refinement. The lower panels illustrate different coordinate responses, without interpreting their difference as physical error.

5 Failures, puncture treatment, and qualification decision

Without restoring, the $N = 65$ pulse violates the predeclared exploratory scri-numerator threshold 10^{-2} at $t = 0.248062$. Varying the speed ratio, increasing auxiliary damping, or halving KO strength did not remove that failure. With $\xi_\beta = 1$, $N = 65$ and 257 reach $t = 1$, but $N = 129$ fails at $t = 0.249027$. This nonmonotonic behavior is preserved rather than called convergence. The stronger source succeeds in the regular-center refinement sequence above.

Linearized method-of-lines spectra at Minkowski, $N = 33, 65$, have negative spectral abscissae for the three tested restoring strengths. Thus these spectra do not explain the nonlinear pulse failures as an already demonstrated exponentially growing linear eigenmode. Nonnormal amplification, nonlinear boundary compatibility, and finite-resolution coupling remain possible mechanisms. Exact nullness is maintained even in every failed trajectory.




Figure 2: Failed controls and a surviving regular-center candidate. Crosses mark actual stop states. The nullness diagnostic accumulates over all RK stages and accepted states; it does not imply cancellation of the other scri numerators.

The wormhole trials preserve $M = 1/3$ and the baseline matched isotropic initial slice. They retain the radial map with stretch 16, positive-node stencils, reference-weighted positive variables, and physical lapse floor 10^{-10}. All positive-radius nodes evolve; none are excised. The RK lapse variable is the total conformal lapse. Accepted increments use compensated accumulation. A separate total-value tensor adapter avoids subtracting small lapse, conformal factor, and physical trace from reference values. The initial shift is matched to the elliptic datum; subsequent stages use only the local driver.

The coefficient endpoint is rederived for $g = 1 + g_1 r + \cdots$ and $\beta = b_1 r + b_2 r^2 + \cdots$. In particular,

$$\partial_t \Lambda_0 = 2b_1\Lambda_0 - 4b_1 g_1 + \frac{16}{3} b_2, \qquad \partial_t g_1 = b_1 g_1 + \frac{4}{3} b_2. \tag{16}$$

The leading logarithmic χ and lapse rates remain $2b_1$ and $2b_1 - 6 + 2\xi(0)$. Independent tensor evaluations approaching $r = 0$ converge to these coefficient limits. This checks the leading expansion, not a uniformly accurate puncture evolution.

Fresh trials use $\xi_\beta = 4$ and $\Delta t \le 0.0125h$. At $N = 129$ the scri guard stops the evolution at $t = 0.19423828125$; $N = 257$ reaches its short target $t = 0.2$. The final relative errors with respect to analytic M are 7.7463×10^{-4} and 3.9726×10^{-6}, respectively. Maximum mass changes relative to each numerical initial horizon mass are 1.1975×10^{-3} and 1.2846×10^{-5}. Two unequal-duration grids do not establish puncture convergence or wormhole-to-trumpet relaxation.

For exterior constraints, the mask uses the instantaneous apparent horizon and the RMS is normalized by the sum of exterior radial quadrature weights. The full interior diagnostics are retained separately. At the final saved states the interior maximum $|H|$ is 0.449 and 0.00164. The largest used-minus-original rate differences are in Λ^r near $r = 3.65 \times 10^{-8}$ and 1.60×10^{-8}, of order 4.64×10^4 and 2.01×10^4. These include the finite-difference advection and dissipation modifications, not an independent continuum residual. They prevent an accuracy claim near the puncture. The floor activates only inside $r \simeq 6.29 \times 10^{-7}$.

The independently evaluated raw lapse-clock rates at the final endpoints are 0.0276 and -0.00438, despite the imposed $\alpha_t = 0$. These compatibility defects, together with the scri numerators, are a reason to revisit the boundary closure. They do not identify a unique cause of failure. The later bounded duration probes below reassess this short-test decision; no 3D run has been launched.




Figure 3: Short puncture tests. The dashed elliptic reference is $N = 1025$, so this is not a matched-resolution superiority comparison. Mass errors include the initial discretization error; changes from the numerical initial mass are reported separately in the text.

6 Bounded extensions toward the persistent $100M$ target

The duration target is $t/M = 100$, or coordinate $t = 100/3$ for the retained $M = 1/3$. The goal remains active. The predeclared criteria require three nested grids to reach that duration, decreasing exterior constraints and mass errors, positive-order field self-convergence, a separate timestep check, and continued positivity on every positive-radius node. A small horizon-mass error alone cannot certify a

usable evolution.

At coordinate $t = 1 = 3M$, grids $N = 257, 513, 1025$ all complete with $\Delta t = 0.05h$. Comparing $\Delta t = 0.05h$ against $0.0125h$ at $N = 257$ changes the final conformal lapse by at most 3.5×10^{-13} and the horizon mass by 2.1×10^{-14}. This bounds the measured time sensitivity; two stepsizes do not establish a new temporal order.

N	exterior H RMS	exterior M_r RMS	$\lvert M_{\mathrm{AH}}/M - 1\rvert$	peak scri numerator
257	9.49×10^{-3}	1.86×10^{-2}	2.92×10^{-5}	4.90×10^{-3}
513	9.81×10^{-4}	9.12×10^{-4}	1.10×10^{-6}	2.99×10^{-3}
1025	4.33×10^{-4}	5.37×10^{-5}	5.81×10^{-8}	1.77×10^{-3}

The full radial-weighted mixed-field self-differences are 1.7606×10^{-2} and 1.3080×10^{-2}, giving only order 0.43 at this time. The independently evolved connection dominates this mixed norm. These are short-time refinement results, not a satisfactory long-time convergence certificate. No puncture neighborhood is removed from the profile comparison.

Two fresh extensions target coordinate $t = 3 = 9M$. The $N = 257$ run stops at $t = 2.825$ when its scri numerator exceeds 10^{-2}. Its interior Hamiltonian maximum has already reached 3.19×10^4 near $r = 0.0672$. The $N = 513$ run fails earlier, at last accepted time $t = 2.726953125$, because the next RK stage produces $g = -5.91 \times 10^{-6}$ near $r = 0.09365$. A one-step postmortem replay reproduces that failure. The finer run's scri numerator remains below 0.0051, so raising the scri guard would not cure this failure. The last scheduled diagnostics precede a between-sample stage failure; manifests and terminal arrays retain their separate exact times.

Both runs retain small horizon-mass drift: the largest sampled changes relative to their numerical initial masses are 2.77×10^{-4} and 1.07×10^{-5}. Nevertheless, the loss of positive spatial metric makes the second run unusable. The failing region is far outside the lapse-floor radius, at most 7.32×10^{-6}. An outer-collar Jacobian diagnostic has negative spectral abscissae at the sampled times, but its artificial inner interface and exclusion of the bulk prevent a full-domain stability conclusion.




Figure 4: Duration probes with the original hyperbolic driver. Curves terminate at their actual saved diagnostic times; crosses identify failed runs. The $N = 1025$ trajectory is only a $3M$ probe. The horizon-exterior norms decrease with refinement, while interior metric breakdown still prevents continuation toward $100M$.




Figure 5: Lapse snapshots at the indicated times, retaining the telegrapher coupling and physical floor 10^{-10}. Different terminal times must not be interpreted as a convergence comparison. The floor region is several orders of magnitude closer to the puncture than the observed metric failure.

A bounded candidate adds $b\Omega^2\sqrt{\chi}$ to μ, with $b = 0.1$. It leaves the scri coefficient and incoming-mode count unchanged and gives

$$c_S^2 = 2c_L^2 + \frac{4b\Omega^2\sqrt{\chi}}{3g} > 2c_L^2 \quad (\Omega > 0,\ \chi, g > 0). \tag{17}$$

Before lapse flooring changes the leading AF scaling, the shift speed changes from $O(r^3)$ to $O(r)$. This is a gauge-transport hypothesis, not a cure established by the symbol. Three regular-center grids pass the same short gate, but the fresh $N = 257$ puncture trial fails at $t = 2.8078125$ when a stage metric becomes negative near $r = 0.0672$. This candidate therefore does not resolve the duration failure and is not the default.

One remaining mechanism to test is the collapsed-region background forcing. For smooth AF data with $\beta = b_1 r + O(r^2)$, the original driver gives, at continuum leading order,

$$\dot{b}_1 = b_1^2 - 1 - 2\xi_\beta(b_1 + 1). \tag{18}$$

At $\xi_\beta = 4$ this has a stable fixed point $b_1 = -1$. Thus the driver actively restores the inward reference shift even in the collapsed-lapse region. The added $b\Omega^2\sqrt{\chi}D = O(r^2)$ does not change this leading forcing. Its causal role in the observed compression remains a hypothesis; a lapse-adapted background source needs a separate derivation and controlled test.

The implementation now writes atomic progress records and bounds diagnostic spacing by $\Delta t_{\mathrm{report}} \le 0.025$. A diagnostic-only optimization omits constraint and horizon calculations during intermediate RHS evaluations while retaining them at reports; the native rate arrays agree bit for bit with diagnostics enabled. Full failed-stage arrays are preserved for newly instrumented failures. The original failed runs and elliptic reference remain unchanged.

7 Implementation route and reproducibility

A genuine 3D implementation should evolve Cartesian shift and auxiliary vectors in the interior and transform them consistently to shell frames. The spherical code evolves the full radial component, not a globally slaved β/r profile. Spherical symmetry necessarily fixes the central location; it is not a test of puncture motion. Constant and linear Cartesian shift modes must be included in the 3D driver tests. The reference source and restoring term can influence translations, so their effect on puncture tracking must be measured rather than assumed benign.

At a cubed-sphere outer face, compute s_i from the live regular metric and the analytic Ω_i. Eliminate the normal shift component after every stage, ghost fill, prolongation, restriction, and synchronization. Derive the corresponding auxiliary compatibility trace in that frame. Specify tangential coordinates only after counting the vector-sector characteristics. A normal nullness identity alone supplies no tangential gauge condition.

Before deployment, derive a direction-independent 3D version of the telegrapher coupling and speed coefficient, and audit all scalar, vector, and tensor eigenvectors for arbitrary positive metrics. The present radial g-dependent speed separation is not yet such a 3D prescription. AMR needs stage-consistent characteristic interface treatment, stable dissipation across refinement boundaries, and nullness reconstruction after interpolation; a boundary component should not be interpolated as an independent scalar. Shell interfaces additionally require tensor/connection transformation and reference-connection checks. Moving punctures require positive-variable interpolation, measured floor effects, and resolution studies of the near-puncture constraint and gauge fields.

The implementation is under `tst/hyperbolic_shift_1d/`; frozen inputs are under `inputs/hyperbolic_shift_1d/`. Each run records its command, source hashes, library hash, input values, stop reason,

histories, and profiles. Failed runs retain their actual outcomes. Portable exports are under `docs/hyperbolic-shift-1d/evidence/`; complete per-run source snapshots and libraries remain in the ignored local output tree. The original elliptic implementation is unchanged except for an additive native adapter with unchanged legacy entry points; all 24 independent $g = 1/\text{tensor}$ comparison cases still pass.

Evidence category	Established scope
Analytic identities	Nullness elimination, evolving-normal rate, scalar principal polynomial, selected exact eigenspaces, leading AF limits.
Algebraic numerics	Every tested stage/state satisfies spherical nullness within one machine epsilon; general 3D boundary identities have separate randomized tests.
Convergence evidence	Short regular-center refinement and three-grid puncture evidence through $3M$; no $100M$ convergence certificate.
Unresolved	Complete boundary well-posedness, uniform collapsed-lapse hyperbolicity, accurate puncture evolution, long-time robustness, and all 3D/AMR qualification.

The practical outcome is a reproducible experimental alternative with a working exact-nullness mechanism. It is not a replacement for the successful elliptic configuration.