

①


1. logical OR

$$Z_{in} = (0 \ 1 \ 1 \ 0 \ 1) \text{ for example}$$

$$\beta = (1 \ 1 \ 1 \ 1 \ 1) = \{1\}^0$$

$$b = -0.5 \text{ (to avoid exactly 0)}$$

activation function $f = \text{step function } \Theta$



$$\text{eg } Z' = Z_{in} \cdot \beta + b = (0 + 1 + 1 + 0 + 1) - 0.5 = 2.5$$

$$f(Z') = 1$$

2. masked logical OR

$$Z_{in} = (1 \ 0 \ 1) \quad \beta = c$$

$$c = (1 \ 0 \ 1) \quad b = -0.5$$

activation function $f = \Theta$

$$Z' = Z_{in} \cdot \beta + b = (1 + 0 + 1) - 0.5 = 1.5 \quad \Theta(1.5) = 1$$

3. perfect match

$$Z_{in} = (1 \ 1 \ 0) \text{ for example}$$

$$c = (1 \ 1 \ 0) \text{ for example}$$

$$\beta_i = \begin{cases} -1 & \text{if } c_i = 0 \\ +1 & \text{if } c_i = 1 \end{cases} = (1 \ 1 \ -1)$$

$$b = -\sum_{i=1}^D c_i + 1$$


activation function $f = \text{ReLU}$

$$Z' = Z_{in} \cdot \beta + b = (1 + 1 + 0) - 1 = 1 \quad f(1) = 1$$

$$X = (a, b) \quad M = 6$$

first layer $f(x) \rightarrow \{0, 1\}^6$

$$f(a, b) = \begin{cases} (100000) & \text{if } a < a_1 \text{ and } b < b_1 \\ (010000) & \text{if } a > a_1 \text{ and } b < b_2 \\ (001000) & \text{if } a > a_1 \text{ and } b > b_1 \text{ and } b < b_4 \\ (000100) & \text{if } a < a_2 \text{ and } b > b_4 \\ (000010) & \text{if } a > a_3 \text{ and } b > b_2 \text{ and } b < b_3 \\ (000001) & \text{else} \end{cases}$$



Second layer not necessary.

third layer has 3 Neurons

1. $z_{out1} = \text{masked OR}(z_{in}, 010100)$ red minus

2. $z_{out2} = \text{masked OR}(z_{in}, 001010)$ blue plus

3. $z_{out3} = \text{masked OR}(z_{in}, 100001)$ green circle

other option $M=7$ 7 neurons : one for $a > a_1$, one for $a > a_2 \dots$

$$f_1(a, b) = \Theta(a - a_1) \quad \text{so } \beta = (1, 0) : z_{in} = x = (1, b) \quad z' = z_{in} \beta + b = a - a_1$$

$$b = -a_1 \quad f = \Theta$$

$$f_2(a, b) = \Theta(a - a_2)$$

$$f_3(a, b) = \Theta(a - a_3)$$

$$f_4(a, b) = \Theta(b - b_1)$$

$$f_5(a, b) = \Theta(b - b_2)$$

$$f_6(a, b) = \Theta(b - b_3)$$


$$f_7(a, b) = \Theta(b - b_4)$$

examples:

this would be
(0000000)

this would be
(1111100)

this would be
(0001100)



(perfect match)

Second layer : as many Neurons as regions (4.5 = 20 here)

each neuron represents one Region

1. $z_{out} = \text{perfect match}(z_{in}, (0000000))$

2. ...

3. ...

third layer : 3 masked OR Neurons:



$z_{out1} = \text{masked OR}(z_{in}, \{0,1\}^{20})$ with 1 where region contains red minus

$z_{out2} = \text{masked OR}(z_{in}, \{0,1\}^{20})$ with 1 where region contains blue plus

$z_{out3} = \text{masked OR}(z_{in}, \{0,1\}^{20})$ with 1 where region contains green circle

third option

$$M = 3 = \text{ceil}(\log_2(\# \text{ Regions}))$$



For more dimensions you need more decision Regions and M gets larger. You always need M Neurons in the first layer mapping Features to distinct M -dimensional vectors. The second layer has as many Neurons as decision Regions and each M -dim vector gets mapped to a specific Neuron representing that region. The last layer has as many Neurons as there are classes. Using the masked OR all Neurons corresponding to a class are mapped to one Neuron representing that class.

This gets difficult because there will be a lot of decision Regions and a lot of necessary Neurons. Also overfitting will be a problem.

② a network with L layers

$$Z_0 = X$$

$$\tilde{Z}_l = Z_{l-1} \cdot B_l + b_l$$

$$Z_l = \phi_l(\tilde{Z}_l)$$

$$Z_L = Z_{L-1} \cdot B_L + b_L$$

$$= \underbrace{(Z_{L-2} \cdot B_{L-1} + b_{L-1})}_{\dots} \cdot B_L + b_L$$

$$= Z_{L-2} \cdot \underbrace{B_{L-1} \cdot B_L}_{\text{new } B} + \underbrace{b_{L-1} \cdot B_L + b_L}_{\text{new } b}$$

$$= Z_{L-2} B + b$$

... repeat for all L layers

$$= Z_0 B' + b'$$

same as one layer