

BIT 1204

Fundamentals of Website Development

FORMS IN HTML

HTML form

- An **HTML form** is *a section of a document* which contains controls such as text fields, password fields, checkboxes, radio buttons, submit button, menus etc.
- A webform, web **form** or **HTML form** on a web page allows a user to enter data that is sent to a server for processing.
- An HTML form is used to collect user input. The user input is most often sent to a server for processing

HTML Form

First Name :

Last Name :

Date of Birth :

Email id :

Mobile Number :

SUBMIT

RESET

The image displays two distinct user interface templates for login and registration, set against a solid blue background. Each template is contained within a light gray rectangular box.

Left Template (Login):

- At the top, there are two buttons: "SIGN IN" (light gray) and "SIGN UP" (blue).
- Below these are two social media login buttons: a blue button with a white "f" for Facebook and an orange button with a white "G" for Google.
- Following the social media buttons are two input fields: "E-mail" and "Password".
- At the bottom is a large blue button labeled "SIGN IN".

Right Template (Registration):

- At the top, there are two buttons: "SIGN IN" (blue) and "SIGN UP" (light gray).
- Below these are three input fields: "Username", "E-mail", and "Password".
- At the bottom is a large blue button labeled "SIGN UP".

Sample html form

Personal Information

Sex: ☐ Male ☐ Female

Birthday: Month: Date: 1975

State: Ohio

Country: United States

Site Registration

Username:

Password:

Retype password:

Email address:

Retype email address:

HTML form tags

- The HTML **<form>** tag is used to create an HTML form.
- The **<form>** element is a container for different types of input elements

It has following syntax:

- **<form>**
 - *form elements*
 - **</form>**

An HTML form contains form elements.

- **The `<input>` Element**
- The `<input>` element is the most important form element.
- The `<input>` element can be displayed in several ways, depending on the `type` attribute.

HTML Form Controls

- Text Input Controls
- Checkboxes Controls
- Radio Box Controls
- Select Box Controls
- Hidden Controls
 - Legend
 - fieldset
- File Select boxes/Upload
- Clickable Buttons
- Submit and Reset Button
- Validation
 - Required
 - Placeholder

Sr.No	Attribute & Description
1	type Indicates the type of input control and for text input control it will be set to text.
2	name Used to give a name to the control which is sent to the server to be recognized and get the value.
3	value This can be used to provide an initial value inside the control.
4	size Allows to specify the width of the text-input control in terms of characters.

Attributes

Attribute	Description
type	Indicates the type of input control and for text input control it will be set to text .
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
value	This can be used to provide an initial value inside the control.
Size	Allows to specify the width of the text-input control in terms of characters.
placeholder	

Text **Input** Controls

There are three types of text input used on forms:

- **Single-line text input controls** - This control is used for items that require only one line of user input, such as search boxes or names. They are created using HTML **<input>** tag.
- **Password input controls** - This is also a single-line text input but it masks the character as soon as a user enters it. They are also created using HTML **<input>** tag.
- **Multi-line text input controls** - This is used when the user is required to give details that may be longer than a single sentence. Multi-line input controls are created using HTML **<textarea>** tag.

Password input controls

- This is also a single-line text input but it masks the character as soon as a user enters it. They are also created using HTML **<input>** tag but type attribute is set to **password**.
- Password: `<input type="password" name="password" />`

placeholder attribute

- The **placeholder** attribute specifies a short hint that describes the expected value of an input field (e.g. a sample value or a short description of the expected format).
- The short hint is displayed in the input field before the user enters a value.

Multiple-Line Text Input Controls / textarea

- This is used when the user is required to give details that may be longer than a single sentence. Multi-line input controls are created using HTML `<textarea>` tag.
- `<textarea rows="5" cols="50" name="description"> Enter description here... </textarea> </form>`

Checkbox Control

- Checkboxes are used when more than one option is required to be selected. They are also created using HTML `<input>` tag but type attribute is set to **checkbox**.

checked

Set to *checked* if you want to select it by default.

Radio Button Control

- Radio buttons are used when out of many options, just one option is required to be selected. They are also created using HTML `<input>` tag but type attribute is set to **radio**

Select Box Control

- A select box, also called drop down box which provides option to list down various options in the form of drop down list, from where a user can select one or more options
- `<select name="dropdown"> <option value="Maths" selected>Maths</option> <option value="Physics">Physics</option> </select>`

File Upload Box

- If you want to allow a user to upload a file to your web site, you will need to use a file upload box, also known as a file select box. This is also created using the `<input>` element but type attribute is set to **file**.
- `<input type="file" name="fileupload" accept="image/*" />`

accept

Specifies the types of files that the server accepts.

Button Controls

- There are various ways in HTML to create clickable buttons. You can also create a clickable button using `<input>` tag by setting its type attribute to **button**. The type attribute can take the following values:

Button Controls

Type	Description
submit	This creates a button that automatically submits a form.
reset	This creates a button that automatically resets form controls to their initial values.
button	This creates a button that is used to trigger a client-side script when the user clicks that button.
image	This creates a clickable button but we can use an image as background of the button.

Fieldset and Legend Tag Elements

The <fieldset> tag is used to group related elements in a form.

The **<fieldset>** tag draws a box around the related elements.

The HTML **<legend>** element is found within the <body> tag. It is **used to provide a caption for the related items grouped in the <fieldset> tag**

Div Tag Element

- **The <div> tag defines a division or a section in an HTML document.**
The <div> tag is used as a container for HTML elements - which is then styled with CSS or manipulated with JavaScript.
- The <div> tag is easily styled by using the class or id attribute.

Example: Fieldset, Legend and div Tag Elements



Login Page

Enter your name:

Enter your email:

The Action Attribute

- The **action** attribute defines the action to be performed when the form is submitted.
- Normally, the form data is sent to a web page on the server when the user clicks on the submit button.
- `<form action="action_page.php">`

The Method Attribute

- The **method** attribute specifies the HTTP method (**GET** or **POST**) to be used when submitting the form data
- `<form action="action_page.php" method="get">`
- `<form action="action_page.php" method="post">`

When to Use GET or POST?

- The default method when submitting form data is GET.
- However, when GET is used, the submitted form data will be **visible in the page address field**:
- Always use POST if the form data contains sensitive or personal information. The POST method does not display the submitted form data in the page address field.
- POST has no size limitations, and can be used to send large amounts of data.

