

BIT 1204

Fundamentals of Website Development

HTML - Lists

HTML lists (Numbering & Bullets)

- HTML lists allow web developers to group a set of related items in lists
- HTML offers web authors three ways for specifying lists of information. All lists must contain one or more list elements. Lists may contain –
- **** – An unordered list. This will list items using plain bullets.
- **** – An ordered list. This will use different schemes of numbers to list your items.
- **<dl>** – A definition list. This arranges your items in the same way as they are arranged in a dictionary.

HTML List Example

An Unordered List:

- Machine Learning
- Artificial
- Intelligence
- Robotic Process
- Automation
- Blockchain.

An Ordered List:

1. Edge Computing.
2. Virtual Reality
3. Augmented Reality
4. Cyber Security
5. Internet of Things.

HTML Unordered Lists

- An unordered list is a collection of related items that have no special order or sequence. This list is created by using HTML **** tag. Each item in the list is marked with a bullet.
- **Example**
 - Machine Learning
 - Artificial
 - Intelligence
 - Robotic Process
 - Automation
 - Blockchain.

```
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>

  <body>
    <ul>
      <li>Machine Learning</li>
      <li>ArtificialIntelligence</li>
      <li>Robotic Process</li>
      <li>Automation</li>
    </ul>
  </body>

</html>
```

- Machine Learning
- ArtificialIntelligence
- Robotic Process
- Automation

The type Attribute

- You can use **type** attribute for tag to specify the type of bullet you like. By default, it is a disc. Following are the possible options –

```
<ul type = "square">
```

```
<ul type = "disc">
```

```
<ul type = "circle">
```

```
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>

  <body>
    <ul type = "square">
      <li>Machine Learning</li>
      <li>ArtificialIntelligence</li>
      <li>Robotic Process</li>
      <li>Automation</li>
    </ul>
  </body>

</html>
```

-
- Machine Learning
 - ArtificialIntelligence
 - Robotic Process
 - Automation

HTML Ordered Lists

- If you are required to put your items in a numbered list instead of bulleted, then HTML ordered list will be used.
- This list is created by using `<ol>` tag. The numbering starts at one and is incremented by one for each successive ordered list element tagged with `<li>`.

1. Edge Computing.
2. Virtual Reality
3. Augmented Reality
4. Cyber Security
5. Internet of Things.


```
<html>
  <head>
    <title>HTML Ordered List</title>
  </head>

  <body>
    <ol>
      <li>Edge Computing</li>
      <li>Virtual Reality</li>
      <li>Augmented Reality</li>
      <li>Cyber Security</li>
    </ol>
  </body>

</html>
```

-
1. Edge Computing
 2. Virtual Reality
 3. Augmented Reality
 4. Cyber Security

The type Attribute

- You can use **type** attribute for tag to specify the type of numbering you like. By default, it is a number.
- Following are the possible options –

```
<ol type = "1"> - Default-Case Numerals.  
<ol type = "I"> - Upper-Case Numerals.  
<ol type = "i"> - Lower-Case Numerals.  
<ol type = "A"> - Upper-Case Letters.  
<ol type = "a"> - Lower-Case Letters.
```

```
<html>
  <head>
    <title>HTML Ordered List</title>
  </head>

  <body>
    <ol type = "A">
      <li>Edge Computing</li>
      <li>Virtual Reality</li>
      <li>Augmented Reality</li>
      <li>Cyber Security</li>
    </ol>
  </body>
</html>
```

- A. Edge Computing
- B. Virtual Reality
- C. Augmented Reality
- D. Cyber Security

The start Attribute

- You can use **start** attribute for tag to specify the starting point of numbering you need. Following are the possible options –

<code><ol type = "1" start = "4"></code>	- Numerals starts with 4.
<code><ol type = "I" start = "4"></code>	- Numerals starts with IV.
<code><ol type = "i" start = "4"></code>	- Numerals starts with iv.
<code><ol type = "a" start = "4"></code>	- Letters starts with d.
<code><ol type = "A" start = "4"></code>	- Letters starts with D.