

Hobbeast — Üzleti kérés összefoglaló

Verzió: 1.23.0 Dátum: 2026-09-05

Added

****Self-healing entry points:** sources that point at a home page now find their own event calendar.**

Measured cause: of the 201 sources that run but extract nothing, ****97** have a wrong entry point** — the registry URL is the site's home page (or an unrelated path), not its event calendar. Fixing those by hand does not scale and breaks again when a site reorganises.

`findEventHubUrl()`: when a listing yields zero events, the worker looks for an event hub among the page's own links (`/programok`, `/aktualitasok/kiemelt-rendezvenyek`, ...), follows the shallowest one once, and scrapes that instead. Guards keep it honest: same host only, at most three path segments, the last segment must be a hub word, and long prose slugs that merely end in one (`/letoltheto-tervek-...-programok`) are rejected. Durable correction (`record_discovered_endpoint` RPC, service-role only): when the hub actually produces events, the registry URL is rewritten and the source is annotated, so the fix survives future runs. It never overwrites a source that is already producing.

Verified

Live on `bekescsaba.hu`: home page 0 events → hub discovered (`/aktualitasok/kiemelt-rendezvenyek`) → 3 events, correct URL reported back. 6 new unit tests cover nested hubs, prose-slug rejection, shallowest-first preference, host/self-link guards, depth limit and malformed input. Suite: 467 passed. Typecheck, build, performance budget clean.

Ez az összefoglaló 2026-09-05-én készült visszamenőleg, a `CHANGELOG.md` megfelelő bejegyzéséből származtatva, mert ehhez a verzióhoz eredetileg nem készült versioning-artefaktum. A tartalma a changeloból ellenőrizhető; nem a kiadás napján kelt dokumentum.