
Uncertainty-Aware Multi-Agent Ransomware Detection via Decision MLP Fusion, Score-Space Augmentation, and Bayesian Triage Policy Optimisation

Henry Kabuye Biju Issac Rahul Yumlembam Zahra Farzadpour Jeyamohan Neera

Department of Computer and Information Sciences, Northumbria University, Newcastle, UK

Framework Overview



Three specialised CNN agents each produce $(\hat{p}_i, \sigma_i)$ via MC Dropout. Peer Consultation substitutes an unreliable agent's probability before the score pool is fused by the Decision MLP into a calibrated risk $\hat{p}$. Bayesian TPE derives the four-threshold policy mapping $(\hat{p}, \sigma_{\max})$ to Auto-Contain, Escalate, or Allow; analyst corrections feed back via EWC-regularised incremental retraining.

Why Existing Detectors Fall Short

- **No principled uncertainty** — a deterministic softmax score cannot distinguish a confident-correct prediction from a confident-wrong one.
- **Heuristic modality fusion** — equal-weight averaging of static PE features and runtime telemetry discards per-modality reliability.
- **Binary triage** — alerting on every uncertain case overwhelms analysts; auto-containing every uncertain case risks business disruption.

Four Contributions

1. A **heterogeneous three-agent architecture** (Semantic, Behavioural, Knowledge CNNs), each producing a probability *and* an epistemic uncertainty via T=10 MC Dropout passes.
2. A **Decision MLP fusion** of the six-dimensional score pool, temperature-calibrated (ECE 0.027), with **CTGAN** score-space augmentation for class imbalance.
3. A **Bayesian TPE triage policy** over four jointly-optimised thresholds, cutting escalation from 58.3% → 30.6% while raising balanced accuracy 0.753→0.864.
4. **Peer Consultation** against knowledge collapse under concurrent execution, and an **Expert Feedback Loop** (EWC) for continual adaptation with negligible forgetting (ΔAUPRC=0.001).

Datasets

- **RDset**: 138,047 PE files (96,724 ransomware / 41,323 benign) — Semantic Agent.
- **RanSMAP**: 35,857 ten-second hypervisor telemetry windows, 1,776 sessions, 15 hardware configurations, six ransomware families — Behavioural Agent.
- **RansKnow** (ours): 718 ATT&CK-annotated threat-intelligence transcripts — Knowledge Agent.


RDset, RanSMAP, and RansKnow are independently collected: no executable appears in more than one dataset, so Semantic and Knowledge contribute a fixed, label-independent corpus-mean score during RanSMAP fusion — only the Behavioural Agent carries per-sample signal there.

Limitations & Future Work

- Concurrent benign+ransomware execution remains hard for the most adversarial pairing (SDelete+REvil); Peer Consultation partially recovers detection but the system still escalates rather than confidently contains.
- RanSMAP covers families through 2022; extension to Cl0p, BlackCat/ALPHV, LockBit 3.0 is future work.
- An adaptive attacker could in principle suppress $\sigma_{\max}$ while keeping $\hat{p}$ subthreshold; online Bayesian recalibration of triage thresholds under concept drift is likewise deferred to future work.

Triage Policy over $(\hat{p}, \sigma_{\max})$ Space

$$\pi(\hat{p}, \sigma_{\max}; \Theta) = \begin{cases} \textsc{Auto-Contain} & \hat{p} \geq \tau_{\text{high}} \wedge \sigma_{\max} \leq \kappa_{\text{low}} \\ \textsc{Escalate} & \hat{p} \geq \tau \vee \sigma_{\max} > \kappa \\ \textsc{Allow} & \text{otherwise} \end{cases}$$



Out-of-distribution samples from unseen families concentrate in the Escalate region (63%) due to elevated $\sigma_{\max}$, converting would-be silent misses into analyst review.

Calibration: Fusion is a Calibration Story, not an AUROC Story


Since Semantic/Knowledge contribute fixed corpus-mean scores on RanSMAP, the Decision MLP cannot exceed the Behavioural Agent's own AUROC here. Its honest value is uncertainty-gated triage: naive mean fusion is in fact better calibrated (ECE 0.017) than the Decision MLP (ECE 0.027).

Conclusion

A three-agent framework treating epistemic uncertainty as a **first-class control variable** for autonomous triage: strong in-distribution detection (AUROC 0.996 static / 0.963 behavioural), a 47% escalation reduction, and a Mondrian conformal wrapper giving distribution-free coverage guarantees where exchangeability holds.

`github.com/Henrinnes/Agentic_SABRE`


Detection Performance



System	Random	Temporal	Family	Hardware
Semantic (RDset)	**0.996**	–	–	–
Behavioural	**0.961**	**0.960**	**0.707**	**0.939**
Decision MLP	0.952	0.956	0.681	0.933


Family holdout is the one generalisation gap: AUROC falls to 0.707, but elevated σ_{beh} correctly routes most novel-family samples to escalation rather than silent miss.

Triage Policy Optimisation



Policy	Bal. Acc. ↑	Escalate (%) ↓	Auto-C (%) ↑
Fixed thresholds	0.753	58.3	16.0
Grid search	0.864	32.6	26.2
Bayesian TPE	**0.864**	**30.6**	**28.2**

Generalisation Across Four Splits



Random-stratified, temporal, and hardware holdout cluster tightly on every axis; family holdout collapses inward on all four — the same generalisation gap, not four independent weaknesses.

LaTeX TikZposter