

Custom Attribute Overview

The table describes special attributes that can be used in the HTML tab of HTML Layout Editor and HTML Editor.

Action Name	HTML Tag	Description	Typical Usage	Availability
Iterate	<code><htmltag data-flx-iterate="i,ListA,ListB">...</htmltag></code>	Duplicates the HTML block (including the tag containing the attribute).	Generation of multiple radio buttons and other repeatable elements.	Only inside a tag (must be a tag attribute).
Iterate children	<code><htmltag data-flx-iterate-children="i,ListA,ListB">...</htmltag></code>	Duplicates the HTML block (child nodes only).	Generation of combo box and other repeatable elements with the same parent.	Only inside a tag (must be a tag attribute).
Filter	<code><htmltag data-flx-filter="[condition]">...</htmltag></code>	Filters the HTML tags (tags that do not meet the filter condition).	▶ To cut a part of the HTML code ▶ May be used with Iterate to filter only specific elements of the list	Only inside a tag (must be a tag attribute). This cannot be used in containers containing standard Process Builder controls: User Inputs/Outputs, Business Controls, Sub-DFCs.
Attribute	<code><htmltag data-flx-attr="[attribute]"></htmltag></code>	The entire tag is changed to text (the attribute values may be Screen Interface input only). This is only used to ensure compatibility with HTML.	Boolean attributes (for example, checked).	Tags supporting Boolean attributes (checked, selected, and other)
Bind	<code><htmltag data-flx-bind="[OutputName]"></htmltag></code>	Binds the HTML Input value to the Screen Interface Output.	▶ To replace standard User Inputs ▶ To simplify routing (one Output is bound to many Inputs)	Inside input, button, textarea, select tags.

Dynamic Bind	<code><htmltag data-flx-dynamic-bind= "[OutputName]"></code> <code></htmltag></code>	Works the same way as Bind with an additional benefit of dynamically assigning output name.	▶ To replace standard user inputs ▶ To simplify routing (one output is bound to many Inputs) ▶ To dynamically assign Output name	Inside input, button, textarea, select tags.
Key	<code><htmltag data-flx-key= "[key_number]"></htmltag></code> or <code><htmltag data-flx-key= "[key_enumerable]"></htmltag></code> or <code><htmltag data-flx-key= "#[key_code]"></htmltag></code>	Calls click event after pressing the button. The value of the attribute is matched with a key located in the "KeyboardMapping" section of the Central Configuration file (for details see Central Configuration Documentation).	▶ View or DFC submit on key ▶ Pressing a button on key	Inside input, button, textarea, select tags.
Autoadvance	<code><htmltag data-flx-autoadvance= "[true/false]"...</htmltag></code>	Moves focus to the next Input when autoadvance conditions are met. For details, see Autoadvance .	▶ More convenient forms filling ▶ Automated autoadvance functionality to next control after scan action	Inside input, button, textarea, select tags. Specific for the select element: ▶ AutoSubmit when tabbing into drop-down menu or selecting an option with DOWN ARROW key and pressing ENTER is supported only on the Mozilla Firefox browser; other browsers that are supported submit a page on DOWN ARROW key pressed

				► Autoadvance after mouse click is not supported on the Google Chrome browser
Autofocus	<pre><htmltag data-flx-autofocus= "[true/false]"> </htmltag></pre>	If an attribute is set to true, the control is automatically focused when a page is loaded.	Automatic Input focusing after starting execution of a DFC.	Inside input, button, textarea, select tags.
Action	<pre><htmltag data-flx-action= "[action]"> </htmltag></pre>	Adds an "onclick" event with a callback to submit the view.	Enabling actions in offline mode.	Only in HTML View. Inside button, image, input tags.
Button	<pre><htmltag data-flx-button= "[actions]"> </htmltag></pre>	Adds specified action buttons.	Enabling actions in offline mode.	Only in HTML View.
Disable Button	<pre><htmltag data-flx-button-disabled= "[actions]"> </htmltag></pre>	Allows to disable specific buttons based on action names.	Disabling actions in offline mode.	Only in HTML View. Inside a tag with data-flx-button attribute.
Tab	<pre><htmltag data-flx-tab= "[actions]"> </htmltag></pre>	Adds specified action tabs.	Enabling tabs in offline mode.	Only in HTML View.
Tab Text	<pre><htmltag data-flx-tab-text= "[text]"> </htmltag></pre>	Allows to add custom text to tab headers.	Providing additional information, like the number of items available under the tab.	Only in HTML View. Inside a tag with data-flx-tab attribute.
Scan	<pre><htmltag data-scan-mode= "[text]"> </htmltag> <htmltag data-scan-type= "[text]"> </htmltag> <htmltag data-scan-length= "[text]"> </htmltag> <htmltag data-scan-format= "[text]"> </htmltag> <htmltag data-scan-sign-substitution= "[text]"> </htmltag> <htmltag data-scan-postfix= "[text]"> </htmltag> <htmltag data-scan-area-size= "[text]"> </htmltag></pre>	Allows to configure text inputs to receive data from the device's scanner.	Configuring code scanning behavior.	Only in input.
Validate	<pre><htmltag data-apr-validate= "[true/false]"> </htmltag> <htmltag data-apr-validate= "[true/false]" data-apr-validate-message= "[message]"> </htmltag></pre>	Displays inline validations.	Immediate error feedback during the user data entry.	Inside input and textarea tags.

