





Dynamic Bind

Dynamic Bind is used for binding an HTML element to a dynamically added Output. Name of the Output can be controlled using an Input.

\$Context can be used to access the value of the added Output.

```
<htmltag data-flx-dynamic-bind = " [Output name] "></htmltag>
```

Inputs	HTML Layout Editor/HTML Editor	Runtime												
► DFC Function Navigation:  ► HTML View:  <table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Default Value</th> <th>Test Value</th> </tr> </thead> <tbody> <tr> <td>Input</td> <td>Char</td> <td>Hello World!</td> <td>Hello World!</td> </tr> <tr> <td>OutputName</td> <td>Char</td> <td>DynamicOutput</td> <td>DynamicOutput</td> </tr> </tbody> </table>	Name	Type	Default Value	Test Value	Input	Char	Hello World!	Hello World!	OutputName	Char	DynamicOutput	DynamicOutput	HTML code  <pre> 1 <input type="text" value="{Input}" data-flx-dynamic-bind="{OutputName}"/> 2 3 <button onclick="alert({Context.outputs.{OutputName}})"Show Output value</button> 4 <button onclick="alert('{OutputName}')"Show Output name</button> </pre>	
Name	Type	Default Value	Test Value											
Input	Char	Hello World!	Hello World!											
OutputName	Char	DynamicOutput	DynamicOutput											

The Dynamic Bind converter cannot be used with the Complex data type.