

Function Properties

To Launch the Function Properties Tool Pane

1. In the Entity Explorer select a Function from the list, or select the Function in the diagram.
2. Choose one of the following options:
 - ▶ Choose **Properties** from the Function Navigation Right-Click Menu
 - ▶ Use the **F4** Keyboard Shortcut
 - ▶ Choose **View > Properties** from the [Main Menu](#)

General Tab

Field	Description
Name	The name of the Function (up to 40 characters long).
Description	The textual description of the entity.
Type	One of the available Function types (see Types of Functions).
Log Events	If Log Events is selected, the execution history of the Function will be logged in the TRANSACTION_HISTORY table provided that the following additional conditions are met: ▶ The LogTransactionHistory flag in Central Configuration is set to "True" ▶ In the Apriso Configuration Manager's BI - Disable XML Generation tab, Business Component XML generation is enabled for <i>FlexNet.FunctionInterpreter.BusinessFacade.DFCInterpreter.Interpret</i> ▶ Business Component XML generation is enabled for the Business Component(s) used by a given DFC ▶ The XMLs being generated are configured to be routed to the Transaction History Processor in the Apriso Configuration Manager's Routing Configurations tab If all four of the conditions have been met, TRANSACTION_HISTORY logging will be enabled even if the Log Events check box is not selected. However, selecting Log Events will ensure that more complete information is recorded, as Function Inputs and Outputs will also be logged.
Cache Results	If Cache Results is selected: ▶ the Function will be executed only once for specific (new) Function Inputs values and the Outputs will be stored in a Cache. ▶ the Function will not be executed for successive executions with the same Inputs and its Outputs will be returned from a Cache The option is available only for User Formula Function, SQL Query Function, Sub-DFC Function (Synchronous mode) and Screen Interface Function (Advanced tab). Cache Results can be configured with use of the "FunctionResultsCacheLimit" and "FunctionResultsCacheExpirationSpan" keys located in the "FunctionInterpreter" section of the Central Configuration file (for details, see Central Configuration Documentation).

Note that this functionality is for advanced users. Use it if you are sure that your data will not change. Otherwise a Function may return invalid results from cache instead of the actual data.