

Input Properties

Properties

General

Name

Input1

Description

Data Type

Char

☒ Char

☐ Integer

☐ Decimal

☐ Boolean

☐ DateTime

☐ Complex

☒ Scalar

☐ List

☐ List (Iterate)

☐ List (Duplicate)

☒ Use Source Value Copy

Input Source

Constant

Field	Description
Name	The name of the Input. It can be up to 255 characters long, must begin with a letter or an underscore, and the subsequent characters must be letters, numbers, or underscores. Input names are not case-sensitive. Including the word "password" in the input name will mask the input value in DELMIA Apriso logs, Job Scheduler, and Job Executor.
Description	The description of the Input (localizable).
Data Type	Data type of the Input. The list of valid data types is as follows: ▶ Char – character string, ▶ Integer – integer values (to know the range of this Input type, refer to <i>Int32 Struct</i> at Microsoft Docs), ▶ Decimal – decimal values (to know the range of this Input type, refer to <i>Decimal Struct</i> at Microsoft Docs), ▶ Boolean – true or false value, ▶ Date Time – date and time (to know the range of this Input type, refer to <i>DateTime Struct</i> at Microsoft Docs), ▶ Complex – an object that can contain any number of properties. Each property can be of a different type (all types are supported, e.g., Char, Integer, List Of). It is also possible that the Complex data type will not have a value (can be treated as null or undefined). You can combine the above types with the ones below:

	▶ Scalar – a single data value, ▶ List – a list of values, ▶ List (Iterate) – iterate through the elements of the list. It is marked with  in the Function Navigation Workspace (many DELMIA Apriso Business Components are not executed against lists; therefore, they must be configured to iterate through the list, one execution at a time.), ▶ List (Duplicate) – duplicate the value of Input during iterated invocation of the Function (it is marked with,  in Function Navigation Workspace). The List (Duplicate) type cannot be combined with the Complex data type.
Use Source Value Copy	When the checkbox is selected, the system passes a copy of the value to the Function. For simple data types this option cannot be changed. For more information see Complex Types Technical Architecture .
Input Source	Inputs may be obtained from one of several sources. The list of valid source is as follows: ▶ User ▶ Previous Function ▶ Session Variable ▶ Constant ▶ Machine ▶ System Parameter The Complex/List of Complex data type Input can be obtained only from Previous Function or Session Variable Input sources. For more information, see Input Source. Each Function Input source will render a property sheet specific to the Function Input source.