

HTML View Inputs

It is possible to insert values from HTML View Inputs into HTML.

```
<input type="text" value ="{Input}"/>
```

Note that Inputs are added automatically when typing a valid name in curly brackets inside the HTML tab, e.g., typing {test} will add an Input named "test" to the HTML View Inputs grid.

Inputs	HTML Editor	Runtime								
General HTML View Inputs <table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Default Value</th> <th>Test Value</th> </tr> </thead> <tbody> <tr> <td>Input1</td> <td>Char</td> <td>SomeValue</td> <td>SomeValue</td> </tr> </tbody> </table>	Name	Type	Default Value	Test Value	Input1	Char	SomeValue	SomeValue	CSS JavaScript HTML <pre>1 <input type="text" value ="{Input1}"/> 2</pre> HTML code	SomeValue
Name	Type	Default Value	Test Value							
Input1	Char	SomeValue	SomeValue							

For Inputs of the Integer, Decimal, and DateTime types, it is possible to format the value in HTML code using suitable .NET formats (refer to Formatting Overview article at Microsoft Docs) with the syntax {InputName:Format}. See the following examples:

Format	Input value	Displayed value	Description
{TestInteger:00000}	9	0009	Five digits
{TestDecimal:C}	99.99	\$99.99	Currency string
{TestDateTime:F}	1900-01-01 00:00:00	Monday, January 01, 1900 12:00:00 AM	Full date/time pattern (long time)