

Screen Flows Client Mode

These are some example improvements enabled through the client mode (as compared to the server mode): the validation of field values without a server round trip; the refreshing of only part of a screen and only when necessary; and the loading and initialization of all scripts only once per screen flow (FlexPart). The screen flows client mode helps to make DELMIA Apriso a solution with cutting-edge UI and UX that is resistant to network problems and that provides developers with a powerful tool to build functionality.

Switching to the Client Mode

To execute screen flow on the browser side, set its FlexPart as "client side," which will enable the client mode. In addition, build the screen flow with the client capabilities in mind.

The next section presents the set of supported functionalities and business controls that can be executed on the browser (the server is called asynchronously).

Client Mode Details

These are the differences between the client mode and the server mode:

- ▶ Only the [Grid 1.0](#), [Tree 1.0](#), [Visualization](#), [Quality Defects Visualization \(vQDT\)](#), and [Work Instructions](#) business controls are supported in the client mode (for details, see [Business Controls](#)).
- ▶ No [User Inputs](#) or [User Outputs](#) are supported in the client mode.

To use the File Picker User Input, add an `<input type="file"/>` element in the [HTML Layout Editor](#) (this is not supported in the server mode).

- ▶ The [Layout Editor](#) functionality for [DFCs of the View type](#) is not supported in client mode, so the UI steps must be converted to the [HTML Layout Editor](#).
- ▶ The Work Instructions Display Mode settings (only when linked to the step) are not supported, so you must use [Work Instructions Business Control](#).
- ▶ No task support.
- ▶ A new [JavaScript API](#) is provided in the client mode.
- ▶ The [Go to Screen](#) navigation action does not refresh the screen when the action does not have a screen linked (in the server mode, the [refresh](#) action is performed).
- ▶ Submitting the view does not refresh the screen when no action was returned from any view (in the server mode, the [refresh](#) action is performed).
- ▶ Displaying PDF files in pop-ups in Mozilla Firefox requires setting the Portable Document Format to Preview in Firefox (in Options > Applications).

Screen flows engine sends additional debugging data when running client mode FlexParts with the following roles: Process Functional Author, Process Technical Author, Process Tester, and Process User Interface Author. This might increase resources usage on DELMIA Apriso server.