

Screen Interface Overview

Action Name	HTML Tag	Description	Typical Usage	Availability
Screen Input	HTML: {InputName} , JavaScript: \$Context.inputs.InputName For example: <pre><input type="text" value="{ScreenInterfaceInput}"> <script> var value =\$Context.inputs.InputName; </script></pre>	Passing values	1. Passing (string replace) value to HTML A. {InputName} – for a scalar Input B. {InputName[i]} – for list Inputs 2. In scripts (HTML tab) A. \$Context.inputs.InputName	Everywhere
Screen Output	HTML (only with data-flx-bind): OutputName , JavaScript: \$Context.outputs.OutputName For example: <pre><input type="text" data-flx-bind="{ScreenInterfaceOutput}"> <script> \$Context.outputs.OutputName ='value'; </script></pre>	Gathering values	1. Gathering values from HTML A. data-flx-bind =" {ScreenInterfaceOutput} – for a scalar Output B. data-flx-bind =" {ScreenInterfaceOutput[i]} – for list Outputs 2. In scripts (HTML tab) A. \$Context.outputs.outputName	Bind or script tags
Local Literal	{@Literal name} For example: <pre> {@LiteralName} <script> var value = \$Context.literals.LiteralName; </script></pre>	Insertion of a Literal	1. Display translated string (text, labels, headers) A. {@LiteralName} 2. In scripts (HTML tab) A. \$Context.literals.LiteralName	Everywhere

To Add Screen Interface Elements

Use one of the following options:

- ▶ HTML Layout Editor Right-Click Menu and choose **Insert Input or Insert Literal**
- ▶ One of the Keyboard Shortcuts:
 - ▷ Ctrl+Shift+Space
 - ▷ in | ... + Tab
- ▶ Write the HTML code (the HTML element will appear in the Screen Interface Function Properties pane)
- ▶ Drag elements from the Screen Interface Properties pane (elements are available in the pane after adding them to the Screen Interface Function)