

Screen Model

The `$ScreenModel` variable is used to preserve context of a View/Screen in offline mode.

It is automatically added to HTML Views belonging to the Offline Module and unlike other Inputs it cannot be deleted. The default value of this variable cannot be changed.

It can be used in scripting context by typing `$ScreenModel` (similarly to `$Context`).

`$ScreenModel` can store any type of data. It is the Process Author's responsibility to keep `$ScreenModel` variable value consistent with what a given HTML View expects.

It is possible to override this variable in the HTML View but this breaks the separation between user interface and business logic.

It is not serialized or altered in any way so setting it as reference type allows you to change some other object (i.e., global variable `Apr.Model`). It is not stored in the Portal Session.

`$ScreenModel` variable is restored after any "back" Screen Flow Action (it is tied to the Screen Flow stack).

Setting the Variable

To set this variable, use `$ScreenModel` Output from an [Action Script](#), examples:

```
public static setOrderContext(){
return { $ScreenModel : Apr.Model.orders};
}
```

```
public static setCurrentOrder(orderId:number){
return { $ScreenModel : Apr.Model.orders.filter(function(o){ return o.orderNumber ==
orderId})[0] };
}
```

For more information on `Apr.Model`, refer to the "Offline Mode" section of the [API Documentation](#).

```
public static setDocumentOperations($ScreenModel:string, operationIndex:number){
return { $ScreenModel : ($ScreenModel as any).operations[operationIndex]};
}
```

Using the Variable in HTML/JavaScript Tabs

Assuming that `$ScreenModel` has the following structure:

```
[{
  "orderNumber": "100",
  "orderStatus": "new",
  "orderDescription": "Maintenance Order"
}, {
  "orderNumber": "200",
  "orderStatus": "new",
  "orderDescription": "Maintenance Order"
}, {
  "orderNumber": "300",
  "orderStatus": "new",
  "orderDescription": "Maintenance Order"
}]
```

You can use the following code to display a list of Orders:

```
<div class="order" data-id="{${ScreenModel[i].orderNumber}" data-flx-
iterate="i,$ScreenModel">
  <span class="status status-{{ScreenModel[i].orderStatus}}"></span>
  <span class="info">
    <div>Order: {{ScreenModel[i].orderNumber}</div>
    <br/>
    <div>{{ScreenModel[i].orderDescription}</div>
  </span>
</div>
```

For more information, refer to **Offline Mode Guide**.