

Submit Print Request Function

The Submit Print Request Function may be used to print reports or labels, or to reprint them. Inputs are pre-populated based on the report definition.

To Add the Submit Print Request Function

1. Drag the Submit Print Request Function from the [Toolbox](#) to the Function Navigation diagram, or double-click the Submit Print Request icon in the Toolbox.
2. The system automatically adds these four Inputs to the Function by default
 - ▷ StoreRequestHistory
 - ▷ NumberOfCopies
 - ▷ PrinterID
 - ▷ ReportID
3. Choose the type of print request: Report, Power Report, Label, or Reprint.
4. Choose the report or label from the drop-down list. Inputs will be populated based on the printing definition.

Optionally, choose the Delivery type and Execution mode

General

Name

DELMIA_Apriso_Sample_Inventory_Report1

Description

Type

Submit Print Request

☐ Log Events

Print request type

☐ Report
☒ Power Report
☐ Label
☐ Reprint

Power Report

DELMIA Apriso Sample Inventory Report

Delivery type

☐ File
☐ Printer
☒ Document

☒ Overwrite existing file

File format (effective only for Reports)

Portable Document Format (pdf)

Execution mode

☒ Synchronous
☐ Asynchronous

Pool name

DEFAULT

Input parameters mapping

Key	Value
ProductNo	ProductNo
Location	Location

Field	Description
Print request type	The user can choose one of the modes of printing: Report, Power Report, Label, or Reprint. It is possible to choose the report or label name from a drop-down list.
Delivery type	The user can choose the type of delivery: to a file, as a printout or as a document. It is possible to choose the file format from a drop-down list (this is only available for the Print request type of Report). If the delivery type is a file, it is possible to set the encoding using the Central Configuration file (default code page is set to UTF-8). For details, refer to the Printing Guide .
Execution mode	There are two types of Execution Modes to choose from: ▷ Synchronous – the printing is executed immediately, and further Functions will not be executed until it is finished ▷ Asynchronous – executes the DFC in Job Executor, and it is possible to choose the Pool name (different Pools can have

	different priorities)
Input parameters mapping	It is possible to map the Function Inputs to a label's or report's fields (parameters).

Submit Print Request Function Inputs and Outputs

Input/Output	Description
StoreRequestHistory	If set to true, the system stores the print request in the database for future reprint. This Input is mandatory.
NumberOfCopies	The user can choose the number of copies to be printed. This Input is mandatory.
PrinterID	This Input is mandatory. It is added when Delivery type is set to Printer.
ReportID	Overrides the report or label ID chosen in the drop-down list. If set to zero, the Input is ignored.
OriginalPrintRequestID	If the user chooses the option to reprint, a new OriginalPrintRequestID Input is added instead of the ReportID Input.
ExportDirectory	The name of the directory where the report or label file will be saved. If not specified, the default directory is used. This Input is available when the delivery type is set to File.
ExportFileName	The name of the report or label file. If the value is not specified, the system will generate a file name automatically. This Input is available when the delivery type is set to File.
FilePath	The file path where the printout is saved. This Output is automatically created when the delivery type is set to File.
SynchronizationQueue	The user-defined name of the synchronization queue, which guarantees that the printouts will be processed in the background in the same order that they were created. This Input is available when the Execution Mode is set to Asynchronous. When the Execution Mode is set to Asynchronous and the Print request type is set to Power Report, the SynchronizationQueue input is overridden by the PrinterID input. This ensures successful simultaneous printing.

The DOC report format is supported only by Crystal Reports, while the XML format is supported only by the Reporting Services printing engine.

Multi-value parameters are supported only for Power Reports.