

Types of Functions

Types of Function	Description
3DEXPERIENCE Message	Enables publishing messages from DELMIA Apriso to the 3DEXPERIENCE Platform using an ActiveMQ Message Broker. For more information, see 3DEXPERIENCE Message Function .
Apriso Message	Enables publishing messages within DELMIA Apriso to interact with other DELMIA Apriso elements. For more information, see Apriso Message Function .
Business Component	Invokes a Business Component. A complete list of Business Components are displayed in the Business Component Repository . For more information, see Business Component Function .
Business Control	Displays a Business Control, which is similar to a Business Component but with a User Interface. Additional configuration options are displayed depending on the chosen Business Control. For detailed information about Business Controls, please see Business Controls .
DAL Query	Invokes a DAL method to retrieve rows from the database. A complete list of DAL methods is displayed to the user. This query is portable between MS SQL and Oracle databases. For more information, see DAL Query Function .
Determination	Used to generate Outputs based on a combination of values from Inputs. For more information, see Determination Function .
Input to Output	Used to pass values from Inputs to Outputs, depending on the mapping between them. For more information, see Input to Output Function .
Local Determination	This is an expanded version of Determination. The Inputs, Outputs, and their values are defined for the whole system, not for a particular Function. It is possible to set date ranges for when particular values of Local Determination are valid. For more information, see Local Determination Function .
MDX Query	Executes a user-defined MDX query against the configured database. For more information, see MDX Query Function .
Message Broker	Enables publishing messages from DELMIA Apriso to an external message broker (Kafka, MQTT, or AMQP). For more information, see Message Broker Function .
Notification	Enables configuring push notifications that can be sent from the DELMIA Apriso server to the DELMIA Apriso mobile app. For more information, see Notification Function .
MIScript	Executes a script which operates on Machine Integrator data. For more information, see MIScript Function .
Show Message	The Show Message Function is used to define a set of messages that will be shown on the screen. It is typically used for error messages. For more information, see Show Message Function .
SQL Query	Executes a user-defined SQL query against the configured database. The Function Inputs can be used as parameters of the query, while the Outputs are populated with data from related query columns. For more information, see SQL Query Function .
Stored Procedure	Executes a Stored Procedure against the configured database. For more information, see Stored Procedure Function .
Sub-DFC	Executes a DFC. The DFC to be executed can be selected by name (and optionally revision) or determined by the FUID. For more information, see Sub- DFC Function .

Submit Print Request	Used to print reports or labels, or to reprint them. Inputs are populated based on the report or label definition. For more information, see Submit Print Request Function .
User Formula	This type of Function is used to perform computations using JScript, Visual Basic Script, or C# formulas. For more information, see User Formula Function .
Web Service	The Function invokes remote Web Service using the URL of an WSDL document. For more information, see Web Service Function .