

User Interface Controls for Function Input

Do not include colons in the Control's title. The appearance of colons is controlled in the style (CSS).

There are different types of Input Controls:

User Input Control	Supported Type of Function Input	Description
Text	String, Integer, Decimal, DateTime	Allows the user to write text in the box.
Long Text	String, Integer, Decimal	Allows the user to write text in the box. Virtual Keyboard Enter key starts a new line in the LongText (multiline) Input.
Masked Text	String, Integer, Decimal	Allows the user to write masked text in the box. Masked Text is used for a sensitive data, for example passwords. Values entered in the masked text box are cleared after refreshing the screen. In the Google Chrome browser, disable the option to save passwords. Otherwise, the saved passwords will be populated automatically.
Drop-Down List	String, Integer, Decimal, Boolean, DateTime	Allows the user to choose one value from the list.
Combo Box	String, Integer, Decimal, Boolean, DateTime	Allows the user to choose from the list of existing options.
Check Box	String, Integer, Decimal, Boolean, DateTime	Permits the user to make multiple selections from a number of options.
Button	String, Integer, Decimal, Boolean, DateTime	Adds a button.
Radio Button	String, Integer, Decimal, Boolean, DateTime	Allows the user to choose only one of a predefined set of options.
Date/Time Picker	DateTime	The displayed date format is based on employee UICulture (Personalization).

Date Picker	DateTime	When using the Date Picker Input in Process Builder with the Show Calendar option enabled, the displayed date format is based on UICulture (Personalization).
Time Picker	DateTime	The displayed time format is based on UICulture (Personalization).
File Picker	String	Allows the user to browse for a file. The file is uploaded to the server and the control returns the path to the file. The user is able to copy or move the file from the server to another location using the MoveFile business component. By default, uploading files is disabled. To enable uploading, edit the AllowedUploadedFileExtensions key in central configuration: set it to "*" to accept all file types, set it to a list of specific file types separated by semicolons to accept only the listed types, or leave it empty to block all file types.
Selection List	String, Integer, Decimal, Boolean, DateTime	Allows the user to choose one of the displayed options (in hyperlink format).
Spinner	Integer, Decimal, Boolean, DateTime	Allows the user to click on arrow buttons to change the value within its associated text box.

Properties

On the right hand side of the Layout Editor workspace, the system should display the properties of Inputs, Outputs and Grids. When the user selects an element in the central part of the screen, the system shows an appropriate editor in the properties pane. To see more information about the properties of Input Controls, see [Input Source: User](#).

The **Input Values...** button opens the [Input Values Editor](#). This option is not available for the File Picker Input Control type. Some of the Input Controls (Buttons, Check Boxes, Radio Buttons, Selection Lists) populated from static lists are visualized in the Layout Editor.