

View Action: General Tab

Properties

GeneralParametersRolesAdvanced

Name

VIEWACTION

☒ Show Title

Title

Code:

+

↺

↻

≡

Translation:

Tooltip

Code:

+

↺

↻

≡

Translation:

☒ Defined

Type

☒ Button (Primary)☐ Calculated☐ Tab

☐ Button (Secondary)☐ Numeric

Image

↕

Group Tag

On Action

☒ DFC☐ Action Script Function

Name

CAPA.Links.LinkWarehouseLocation_Action

Revision

APR.IMC.001.000

↺

↻

↻

≡

Action

Next Action

Portal Action

Go to Screen

Name

Revision

↺

↻

↻

≡

Open Pop-up View

Name

PortalPaging

Revision

APR.TPL.001.000

↺

↻

↻

≡

Availability mode

Always

Keyboard

FX key 8

Field	Description
Name	The unique name of the Action (use capital letters without blank spaces). Submitting an Action starting with the prefix "_" does not check the required fields (controls).
Show Title check box	If selected, the title (label) of the Action will be displayed on the Screen.

https://media.3ds.com/support/DELMIA-Apriso/2025/Online/ProcessBuilder/index.htm?_gl=1*109t8fz*_ga*MTk5OTg0NzQ3MS4xNzc3NjQ0NjA3*...

1/7

This section can be editable for Views that are in the active status. For details on how to enable it, see "Modifying Properties..." section of the [Entity Status Types](#) topic.

Title

The descriptive Action name that will be displayed on the Button or Tab.

- ▶ **Code** – the name of the Dictionary Item of the Action title; the following actions are available:
 - ▷  – adds the Dictionary Item (written in the text box) to the dictionary and links it to the Action title
 - ▷  – invokes the **Dictionary Items** suggestion lookup window, which lists the existing Dictionary Items from which the user may choose
 - ▶ When the user enters a part of the Dictionary Item name, the system suggests a list of matching entries from the database
 - ▶ The chosen Dictionary Item is linked to the Action title
 - ▷  – unlinks the previously added Dictionary Item (it is removed from the **Code** field)
 - ▷  – opens the Dictionary Translations screen in the context of linked Dictionary Items
 - ▶ For more information on this screen, refer to the [Dictionary Translations topic in the Dictionary Help](#)
- ▶ **Translation** – the translation of the Action's title according to the translation added in the **Dictionary Translations** screen

This section can be editable for Views that are in the active status. For details on how to enable it, see "Modifying Properties..." section of the [Entity Status Types](#) topic.

Tooltip

The tooltip text that will be displayed after hovering the Button with the mouse pointer.

- ▶ **Code** – the name of the Dictionary Item of the tooltip; the following actions are available:
 - ▷  – adds the Dictionary Item (written in the text box) to the dictionary and links it to the Action tooltip
 - ▷  – invokes the **Dictionary Items** suggestion lookup window, which lists the existing Dictionary Items from which the user may choose
 - ▶ When the user enters a part of the Dictionary Item name, the system suggests a list of matching entries from the database
 - ▶ The chosen Dictionary Item is linked to the Action tooltip
 - ▷  – unlinks the previously added Dictionary Item (it is removed from the **Code** field)

- ▷  – opens the Dictionary Translations screen in the context of linked Dictionary Items
 - ▶ For more information on this screen, refer to the [Dictionary Translations](#) topic in the [Dictionary Help](#)

This section can be editable for Views that are in the active status. For details on how to enable it, see "Modifying Properties..." section of the [Entity Status Types](#) topic.


Defined

If selected, the Action will not be editable on the Screen. It will be overwritten.

Type


The Action type determines what will trigger the Action:

▶ **Button (Primary)**



- ▷ Renders a Button on the View
- ▷ The Buttons are provided for primary Actions (e.g., OK, NEXT) – their purpose makes them more important than others, so they have to have a stronger visual weight
 - ▶ The primary Buttons need to stand out on the Screen, because they allow the user to navigate through the Screens to complete the task
- ▷ To render a primary Button, the PortalGenerateButtonList sub-DFC must be present in the DFC

▶ **Button (Secondary)**



- ▷ Renders a Button on the View
- ▷ This is a style for secondary actions (e.g., BACK, CANCEL, HELP) – these Buttons allow the user to process activities that are not in the main stream of the business logic, and they should have less visual weight than a primary Button and a different, more balanced style
- ▷ The business logic of the flow dictates which Button is primary or secondary
 - ▶ For example, CANCEL – in most cases this is a secondary Button, but when you can perform an Action that is permanent and irreversible, the CANCEL Button should be displayed as primary
- ▷ To render a secondary Button, the PortalGenerateButtonList sub-DFC must be present in the View DFC

▶ **Calculated**

- ▷ This Action type is designed to handle Screen behavior that cannot be displayed with a Button or Tab
- ▷ No particular UI element will be rendered for this Action

- ▷ In this case, the developer has to handle displaying the adequate UI control for this Action and also passing the Action name to an External Output of the View DFC (e.g., selecting a record on the grid or a drop-down Input)
- ▷ A common situation requires handling routing from a View DFC
 - ▶ The routing value can be added as a View Action, and then an appropriate Screen and/or **On Action DFC** is triggered

▶ **Numeric**

- ▷ For mobile devices, this renders a command prompt with the numeric option

Mobile and Text platforms are no longer supported.

▶ **Tab**



- ▷ Renders a Tab, which is a separate Panel in the Layout
 - ▶ For example, the image above presents two Panels: a small one at the top one for Tabs, and a bigger one below it with the actual Tab content
 - ▶ The **PortalTab Template** should be used to create Views that generate Tabs
- ▷ This View should be used in a pair with the GenericPortalTab or PortalTabNotification DFC

It is possible to switch the View Action Type between **Button (Primary)** and **Button (Secondary)** types for the View Actions that are in the active status. For details on how to enable it, see [Entity Status Types](#).



Sets preview background color. The button's background color can be changed on the **Advanced Tab** by setting the appropriate Inline Style.

Image

The image to be displayed on the UI element (applicable for Buttons or Tabs). The image has to be either on the DELMIA Apriso server or referenced as an HTML link. The relative path to the image should be pasted into this field (e.g., /images/action_accept.png).

	This option can be editable for Views that are in the active status. For details on how to enable it, see "Modifying Properties..." section of the Entity Status Types topic.
Group Tag	This can be used to group Actions (Buttons in a View or in a selected grid) and later to use the whole group instead of one particular Action. Buttons can be positioned in the following groups: TOP, BOTTOM, LEFT, RIGHT, TOP-LEFT, TOP-RIGHT, BOTTOM-LEFT, BOTTOM-RIGHT.
On Action	The On Action choice determines what will be executed when the respective Action is triggered and before the target Screen is loaded. The following options are available to select: ▶ DFC – only DFCs of action or initialize subtype can be linked (appear in the DFCs suggestion lookup window) This option is disabled for HTML View Actions in Offline Modules. ▶ Action Script Function – only default revisions of Action Scripts that are in the Active, Prototype or Development in Progress status can be linked (appear in the Action Script Functions lookup window) Name – the Action handler DFC or Action Script Function ▶ The DFC used here should end with <i>_Action</i> and be in the Prototype, Development in Progress, or Active status Revision – the revision of the View DFC The following actions are available: ▶  – invokes the DFCs lookup window, where the user can copy and link an Action handler DFC ▶  – invokes the DFCs or Action Script Functions lookup window, where the user can link an Action handler DFC or Action Script Function ▶  – unlinks the linked DFC or Action Script Function ▶  – invokes the workspace of the linked DFC or Action Script Manager. If there is more than one revision of that DFC, a pop-up listing all of the revisions will appear (to open one of the revisions, double-click it). In the case of PB Projects, the pop-up will display default revisions of the DFCs (of Action type) in the current Project.
Action	▶ Next Action – the Action to be used as the next Action ▶ Use Action from different View check box – is active if there is at least one View on another Panel in your Screen configuration. ▶ Portal Action – the Action in the Portal ▶ The available options are: ▶ Go to Screen – goes to the next Screen (identified in the Name and Revision fields below) ▶ If empty, then:

- ▶ no action is performed (in the [Screen Flows Client Mode](#))
- ▶ the current Screen is refreshed (in the [Screen Flows Server Mode](#)). For more information, see the [Refresh](#) option.
- ▶ **Back** – goes back to the previous Screen in a given Screen stack with the Portal Session Variable restored (internal Screen Flow action)
- ▶ **Close All** – closes all of the Screen stacks and exits to the DELMIA Apriso Portal
- ▶ **Exit** – closes top Screen stacks (Sub-Portal Session) and exits to the higher level Screen stack or the DELMIA Apriso Portal
- ▶ **Loop Close**
- ▶ **Loop Level 2 Close**
- ▶ **Loop Level 3 Close**
- ▶ **Pop-up Close (refresh screen)**
- ▶ **Pop-up Close**
- ▶ **Return** – goes back to the last Screen with a different Screen code
 - ▶ If there is no previous Screen, then it will exit to a higher level Screen Stack
- ▶ **Screen Close**
- ▶ **Help**
- ▶ **Refresh** – refreshes the current Screen
- ▶ **Replace Screen** – replaces the current Screen in the Screen Stack
- ▷ **Name** – the name of the Screen for the **Go to Screen** option
- ▷ **Revision** – the revision of the Screen for the **Go to Screen** option; the following actions are available:
 - ▶  – invokes the **Screen** lookup window, where the user can link a Screen
 - ▶  – unlinks the linked Screen
 - ▶  – invokes the workspace of the linked Screen.

In the case of PB Projects, the pop-up will display a default revision of the Screen in the current [Project](#).

- ▶ **Open Pop-up View** – opens a View in a [pop-up window](#)
 - ▷ **Name** – the name of the View to be displayed in the pop-up window
 - ▷ **Revision** – the revision of the View DFC; the following actions are available:
 - ▶  – invokes the **Views** lookup window, where the user can copy and link a View
 - ▶  – invokes the **Views** lookup window, where the user can link a View
 - ▶  – unlinks the linked View
 - ▶  – invokes the workspace of the linked View. If there is more than one revision of that DFC, a pop-up listing all of the revisions will appear (to open one of the revisions, double-click it).

	In the case of PB Projects, the pop-up will display default revisions of the DFCs (of the View type) in the current Project.
Availability Mode	This functionality is valid only for a Grid View. It provides the ability to configure read-only properties for toolbox Buttons in the grid. It can also be set directly in the grid. The Action will be available depending upon selection of the grid. The options are: ▶ Always ▶ At least two rows ▶ At least one row ▶ Single row only
Keyboard	The keyboard key used to trigger this Action. In addition to keyboard buttons, there are items that start with the "FX" prefix. These particular shortcuts can be configured with use of the keys located in the KeyboardMapping section of the Central Configuration file (for details, see Central Configuration Documentation).