

SOTWISE — Purchase Orders API (read-only)

Reference for consuming **Purchase Order (PO)** data from SOTWISE.

This integration is **read-only**. Your token can only **read** purchase orders. It cannot create, change or delete anything, and every other part of the API returns `403 Forbidden`.

Base URL	<code>https://sot.gssdatahub.com</code>
Endpoint	<code>GET /api/orders</code>
Format	JSON (UTF-8)
Transport	Server-to-server over HTTPS. There is no CORS, so browser calls from another origin are blocked.

1. Authentication

Send your token in the `Authorization` header on every request. It must start with `Bearer` followed by a space:

```
Authorization: Bearer <YOUR_TOKEN>
```

- The SOTWISE team gives you the token through a private channel. Keep it on your server only. Never put it in front-end code, a URL or a public repository.
- If the token leaks, tell the SOTWISE team. We will revoke it and issue a new one.
- A missing or wrong token returns `401` with a JSON body. The API never redirects to a login page.

2. Reading purchase orders — `GET /api/orders`

```
GET https://sot.gssdatahub.com/api/orders
Authorization: Bearer <YOUR_TOKEN>
```

The response is **always a list**, even when you filter down to one order, so the shape never changes with the filter.

2.1. Query parameters (all optional)

Parameter	Values	Default	Purpose
<code>po_number</code>	PO number (exact)	—	Read one specific order
<code>status</code>	see §3.1	—	Filter by order phase
<code>updated_since</code>	ISO 8601 with timezone, e.g. <code>2026-09-01T00:00:00Z</code>	—	Only orders changed since that moment (incremental sync)

Parameter	Values	Default	Purpose
order	asc desc (sorted by updated_at)	desc	Use asc to walk forward in time
limit	1–200	50	Page size
offset	≥ 0	0	Page offset
include	items	empty	Also return the order lines (Factory × Category). See §2.4
gss_id	GSS order id	—	Read an order by its GSS id. Only needed if you already work with GSS ids

Unknown parameters are ignored. An invalid value returns 400 , and issues[] names the parameter.

include=checklist is **not available** for this token and returns 403 .

2.2. Recommended usage — incremental sync

1. **Initial load:** page through everything, oldest first: GET /api/orders?order=asc&limit=200&offset=0 , then offset=200 , offset=400 , ... Stop when pagination.returned < limit .
2. **Store the highest updated_at** you received.
3. **Afterwards, fetch only what changed:** GET /api/orders?updated_since=<stored updated_at>&order=asc&limit=200 Page with offset the same way, then update the stored value.

Results are sorted by updated_at and then by id . The id breaks ties, so no order is skipped or repeated across pages.

updated_since includes the boundary, so the last order from the previous run can come back once. Upsert by id and the duplicate is harmless.

Important: updated_since **tracks the order itself, not its lines**. An order's updated_at changes when a header field or the order status changes. It does **not** change when only a line changes: a batch is assigned, loading_status changes, a line is added, or a batch changes status without changing the order status. If you use include=items , also run a **periodic full refresh of the lines**, for example once a day, walking all orders with include=items . To keep it small, run it once per active status (status=in_production , status=pre_loading , ...) and skip delivered and canceled .

Please keep polling reasonable. Every 15–30 minutes is plenty for this data.

2.3. Response 200

```
{
  "data": [
    {
      "id": "93cc8b37-1ace-43ca-a391-009e0640ffd0",    // SOTWISE internal id (UUID) – stable,
      // use as primary key
      "gss_id": null,                                // GSS order id (null if the order was
      // created in SOTWISE)
      "po_number": "1530",
      "status": "partially_shipped",
      "asap": false,
      "schedule_requested": "2026-08-24",
      "client_reference": "113-26",
      "date_po": "2026-08-03",
      "order_type": { "id": "1364838b-...", "name": "Sales",      "gss_id": "1" },
      "client": { "id": "d23e27e0-...", "name": "Impacto",      "gss_id": "28" },
      "business_unit": { "id": "f706396a-...", "name": "Moto Parts", "gss_id": "4" },
      "exporter": { "id": "bb07d9fa-...", "name": "Zenya",      "gss_id": "4" },
      "leader": { "id": "4b2b1608-...", "name": "Leonardo Pacce" },
      "requester": { "id": "4b2b1608-...", "name": "Leonardo Pacce" },
      "created_at": "2026-08-03T05:39:27.561+00:00",
      "updated_at": "2026-09-17T18:45:00.771298+00:00"
    }
  ],
  "pagination": { "limit": 50, "offset": 0, "returned": 1, "total": 71 }
}
```

Order fields

Field	Type	Description
<code>id</code>	UUID	SOTWISE internal id. Stable and unique. Use it as your primary key.
<code>gss_id</code>	string null	Order id in GSS (the master-data system). <code>null</code> when the order was created directly in SOTWISE.
<code>po_number</code>	string	Purchase order number. Unique in SOTWISE.
<code>status</code>	enum	Current phase of the order. See §3.1 .
<code>asap</code>	boolean	Urgency flag ("as soon as possible").
<code>schedule_requested</code>	date null	Requested schedule date.
<code>client_reference</code>	string null	Customer's own reference for the order.
<code>date_po</code>	date null	PO issue date.
<code>order_type</code>	object null	<code>{ id, name, gss_id }</code> , e.g. Sales.
<code>client</code>	object null	<code>{ id, name, gss_id }</code> , the customer.

Field	Type	Description
business_unit	object null	{ id, name, gss_id }
exporter	object null	{ id, name, gss_id }
leader	object null	{ id, name }, the SOTWISE user who leads the order.
requester	object null	{ id, name }, the SOTWISE user who requested it.
created_at	timestamp	When the order was created in SOTWISE (ISO 8601, UTC).
updated_at	timestamp	Last change to the order. This is the field updated_since filters on.

- Master-data objects (order_type , client , business_unit , exporter , and factory / category in the lines) carry the SOTWISE id , the display name and the gss_id . gss_id: null means that record is not linked to GSS yet.
- Any field can be null when it has not been filled in.
- total counts every order that matches the filter, ignoring pagination. returned is the size of this page.

2.4. include=items — order lines

GET /api/orders?include=items adds an items array to each order. Each line is one **Factory × Category** product of the order:

```
"items": [
  {
    "id": "18bd96d0-dd15-41a3-9f87-983603eeb8e3",
    "factory": { "id": "a40b67d9-...", "name": "Pengjie", "gss_id": "453" },
    "category": { "id": "28a8872e-...", "name": "Sealing", "gss_id": "34" },
    "ship_requirement": "2026-08-24",
    "loading_status": null,
    "batch": { "id": "0a69b3c4-...", "batch_number": ".02", "status": "in_production" }
  }
]
```

Field	Type	Description
id	UUID	Line id.
factory	object null	{ id, name, gss_id }, the supplier factory.
category	object null	{ id, name, gss_id }, the product category.
ship_requirement	date null	Required ship date for this line.

Field	Type	Description
loading_status	enum null	How much of the line was loaded: <code>total</code> , <code>partial</code> , <code>none</code> , or <code>null</code> (not informed yet).
batch	object null	The batch the line was grouped into: <code>{ id, batch_number, status }</code> . <code>null</code> means no batch yet. See §3.2 .

- `batch_number` (format `.NN`) is **only unique inside its order**, because numbering restarts for each order. To identify a batch globally, use `batch.id` or the pair `po_number` + `batch_number`.
- `items` adds extra database work. For a light sync, request it only when you need the lines. It is also always safe to fetch the lines of one order with `?po_number=...&include=items`.

3. Reference values

3.1. Order status

Listed in the normal lifecycle order:

Value	Meaning
<code>in_negotiation</code>	Order opened and under negotiation.
<code>in_production</code>	Confirmed; the factories are producing.
<code>partially_preloading</code>	Some of the order's batches are in pre-loading.
<code>pre_loading</code>	All batches are in pre-loading (being prepared for shipping).
<code>partially_shipped</code>	Some batches have shipped.
<code>shipped</code>	All batches have shipped.
<code>partially_delivered</code>	Some batches have been delivered.
<code>delivered</code>	Fully delivered.
<code>canceled</code>	Order canceled.

The order status is derived from the statuses of its batches.

3.2. Batch status

Value	Meaning
<code>in_negotiation</code>	Under negotiation.
<code>in_production</code>	In production.
<code>preloading</code>	In pre-loading.
<code>in_transit</code>	Shipped and in transit.
<code>delivered</code>	Delivered.

Value	Meaning
canceled	Canceled.

3.3. Data formats

Kind	Format	Example
Date	YYYY-MM-DD	2026-08-24
Timestamp	ISO 8601 with offset (UTC)	2026-09-17T18:45:00.771298+00:00
Id	UUID v4	93cc8b37-1ace-43ca-a391-009e0640ffd0

4. Errors

Every error returns a JSON body `{ "error": "message" }`. Validation errors also include `issues[]`, which lists each problem and the field it affects.

Code	When	What to do
200	Success, including when nothing matches (<code>data: []</code> , <code>total: 0</code>). There is no 404 for an empty filter.	—
400	Invalid query parameter: <code>status</code> not in the list, unknown <code>include</code> , <code>limit > 200</code> , <code>updated_since</code> not ISO 8601, etc.	Fix the request.
401	Missing token, wrong token, or missing <code>Bearer</code> prefix.	Check the header.
403	Your token is valid but not allowed to do this, e.g. <code>include=checklist</code> , a <code>POST</code> , or any endpoint other than <code>GET /api/orders</code> .	Stick to the scope of this document.
500	Unexpected error on the SOTWISE side.	Retry later with backoff. If it keeps happening, report it to the SOTWISE team with the <code>error</code> message.

Examples:

```
// 400
{ "error": "Invalid 'status': Invalid option: expected one of \"in_negotiation\"|...\", \"issues\": [ ... ] }

// 401
{ "error": "Invalid token" }

// 403
{ "error": "include=checklist is not available for this token." }
```

General rule: a **4xx** means review what you sent, and repeating the same call will not help. A **5xx** means the problem is on our side.

5. Quick test (cURL)

```
# Latest 5 orders
curl -s "https://sot.gssdatahub.com/api/orders?limit=5" \
-H "Authorization: Bearer $SOTWISE_TOKEN"

# One PO with its lines
curl -s "https://sot.gssdatahub.com/api/orders?po_number=1530&include=items" \
-H "Authorization: Bearer $SOTWISE_TOKEN"

# Incremental: what changed since a given moment
curl -s "https://sot.gssdatahub.com/api/orders?updated_since=2026-09-
01T00:00:00Z&order=asc&limit=200" \
-H "Authorization: Bearer $SOTWISE_TOKEN"
```

6. Notes

- **Deleted orders do not appear.** If an order you synced stops coming back when you query it directly by `po_number`, it was removed in SOTWISE.
- **Scope may grow.** Other data, such as pre-loadings and shipments, may be opened later on the same base URL with the same token. The fields documented here will not change meaning. New fields may be added, so ignore any field you do not recognize.
- **Contact:** questions, a new token, or incident reports go to the SOTWISE team.