SimpleGrid 3×3: 2 possible goals per problem (4 problems, pinned evidence)

Method	Possible goals	Runs	CNF variables	CNF clauses	Runs over 1 min	Failed at 15 min	Mean time (s)	Max time (s)	True goal among top scorers	True goal is the sole top scorer	Mean P(true goal)
max-term	2	16	141	819–820	0	0	11.9	13.2	16/16	0/16	0.500
sharpsat-td	2	16	141	819–820	0	0	15.8	17.2	9/16	7/16	0.500
mc-sat	2	16	141	819–820	0	0	14.4	15.7	8/16	8/16	0.511
addmc	2	16	141	819–820	0	0	9.2	9.7	9/16	7/16	0.500

Each run is one problem, one pinned evidence file (the first N drives of a plan) and one recognize.sh `--counter` method. CNF size is the instantiated problem plus evidence that every method starts from (max-term adds its own soft clauses); it depends on the problem and evidence, not the method. Times are wall-clock, 8 runs in parallel (ADDMC: 2), each first limited to 1 minute and rerun with 15 minutes if it timed out; a 15-minute rerun is counted in "Runs over 1 min" and its time is that of the rerun. "Top scorers" are the hypotheses sharing the highest posterior, so a tie counts as among them but not as sole.