SimpleGrid 8×8, 5 observed actions

7 possible goals per problem; 4 problems; pinned evidence

Method	Runs	CNF variables	CNF clauses	Mean time (s)	Max time (s)	True goal among top scorers	True goal is the sole top scorer	Mean P(true goal)
max-term	28	3,808–4,096	28,566–30,758	61.6	69.7	28/28	0/28	0.155
sharpsat-td	5 of 28	3,808	28,566	–	–	0/5	0/5	–
mc-sat	4 of 28	3,808	28,566	–	–	0/4	0/4	–

Each run is one problem, one pinned evidence file (the first N drives of a plan) and one recognize.sh `--counter` method. CNF size is the instantiated problem plus evidence that every method starts from (max-term adds its own soft clauses); it depends on the problem and evidence, not the method. Times are wall-clock, 8 runs in parallel, each limited to 20 minutes of awake time (sleep not counted); 9 runs did not finish; each counts as a miss in the top-scorer columns and is left out of the times and mean P(true goal). "Top scorers" are the hypotheses sharing the highest posterior, so a tie counts as among them but not as sole. sharpsat-td was stopped after 34 runs, of which 0 finished, and not run on the rest; mc-sat was stopped after 32 runs, of which 0 finished, and not run on the rest. 5 of the unfinished runs were stopped by FiFO's 600 s limit on a single solver call (one exact count), not by the run's own limit.