

Design Document

for the ninth Object Oriented homework

Attention

The sequence of all classes are arranged by alphabetical order. All classes' attribute are public except the class MapException.

Content

Design Document.....	1
一、 ChangelIndex.....	3
二、 Index.....	3
三、 Light_ctl.....	4
四、 Map.....	4
五、 MapException.....	7
六、 Passenger_Monitor.....	8
七、 Passenger.....	8
八、 PassengerQuene.....	10
九、 Schedule.....	10
十、 Taxi_main.....	11
十一、 Taxi.....	11
十二、 Traffic_light.....	13
十三、 Types.....	14

一、 ChangeIndex

1. Overview

Record the change of indexes.

2. Process Specifications

```
public boolean repOK() {  
    /*  
    * Requires: Nothing.  
    * Modifies: Nothing.  
    * Effects: Return the true if the rep variant holds for this.  
    otherwise return false.  
    */  
}
```

(The repOK method in all class have the same specification so only write once here)

```
public ChangeIndex(Index index, int change)  
    /*  
    * Requires: Two Index variables.  
    * Modifies: Nothing.  
    * Effects: Construct a ChangeIndex.  
    */  
  
public Index getIndex()  
    /*  
    * Requires: Nothing.  
    * Modifies: Nothing.  
    * Effects: Return the index.  
    */  
  
public int getChange()  
    /*  
    * Requires: Nothing.  
    * Modifies: Nothing.  
    * Effects: Return the change.  
    */  
}
```

3. Indicated Object

```
private Index index  
private int change
```

4. Abstract Function

$AF(c) = (\text{index}, \text{change path}), \text{ where } \text{index} = c.\text{index}, \text{change path} = c.\text{change}.$

5. Invariance

$c.\text{index} \neq \text{null} \ \&\& \ 0 \leq \text{change} \leq 3$

二、 Index

1. Overview

Record the index.

2. Process Specifications

```

public int getX()
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the x.
     */
public int getY() {
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the y.
     */
public Index(int x, int y) {
    /*
     * Requires: Two integer.
     * Modifies: Nothing.
     * Effects: Construct a index.
     */

```

3. Indicated Object

```

private final int x
private final int y

```

4. Abstract Function

$AF(c) = (x,y)$, where $x = c.x$, $y = c.y$.

5. Invariance

$c.x \in R \ \&\& \ c.y \in R$

三、 Light_ctl

1. Overview

Control all the traffic lights on the simulative road.

2. Process Specifications

```

public Light_ctl(Traffic_light[][] light) {
    /*
     * Requires: two-dimensional array of Traffic_light.
     * Modifies: Nothing.
     * Effects: Initialize the light..
     */

```

3. Indicated Object

```

private Traffic_light[][] light

```

4. Abstract Function

$AF(c) = (light)$, where $light = c.light$.

5. Invariance

$c.light \neq null$

四、 Map

1. Overview

Simulate the roads and traffic lights.

2. Process Specifications

```
public Map()
/*
 * Requires: Nothing.
 * Modifies: Nothing.
 * Effects: Initialize the flows, map_p, changeIndex, map
 */
public static boolean isConnect(Index a, Index b)
/*
 * Requires: Two indexes which is border upon.
 * Modifies: Nothing.
 * Effects: check this two indexes whether border upon.
 */
public static Vector<Passenger> findPasg(int x, int y)
/*
 * Requires: Two integers which is an index.
 * Modifies: Nothing.
 * Effects: Find all the passengers near the index which passed
in then return a Vector contains them.
 */
public static Vector<Integer> shortestPath(int x1, int y1, int x2, int y2)
/*
 * Requires: Four integers which are two indexes.
 * Modifies: Nothing.
 * Effects: Find the shortest path of this two indexes.
 */
public static int shortestPath2(int x1, int y1, int x2, int y2)
/*
 * Requires: Four integers which are two indexes.
 * Modifies: Nothing.
 * Effects: Find the first step of the shortest and least car flow
path of this two indexes and return.
 */
public static void addReq(int x, int y, Passenger p)
/*
 * Requires: Two integers which is an index and a passenger.
 * Modifies: Nothing.
 * Effects: Map the passenger into the map_p.
 */
public static void deleteReq(int x, int y, Passenger p)
/*
 * Requires: Two integers which is an index and a passenger.
```

```

        * Modifies: Nothing.
        * Effects: delete the passenger in the map_p.
    */
private boolean init_map()
    /*
        * Requires: Nothing.
        * Modifies: Nothing.
        * Effects: Initialize the map by Map.txt.
    */
private void init_lights()
    /*
        * Requires: Nothing.
        * Modifies: Nothing.
        * Effects: Initialize the light.
    */
private int countConnect(int i, int j)
    /*
        * Requires: Two integers.
        * Modifies: Nothing.
        * Effects: Get the number of connected path.
    */
public synchronized static boolean deletePath(Index co, int num)
    /*
        * Requires: An index in map which needs to be changed to the
num.
        * Modifies: Nothing.
        * Effects: Delete a path in the map..
    */
public synchronized static void recoverPath(int i)
    /*
        * Requires: A number which is a index of changeIndex.
        * Modifies: Nothing.
        * Effects: Recover a path in map.
    */
public static Vector<ChangeIndex> getChanged()
    /*
        * Requires: Nothing.
        * Modifies: Nothing.
        * Effects: Return the changeIndex.
    */
public static void addFlow(int x, int y, int direction)
    /*
        * Requires: An Index and a direction..
        * Modifies: flows.
    */

```

```

        * Effects: Add the flow in corresponding edge.
        */
    public static void minusFlow(int x, int y, int direction)
    /*
        * Requires: An Index and a direction..
        * Modifies: flows.
        * Effects: Minus the flow in corresponding edge.
        */
    public static int getFlow(int x, int y, int direction)
    /*
        * Requires: An Index and a direction..
        * Modifies: Nothing.
        * Effects: Return the flow in corresponding edge.
        */
    public static boolean haslight(int x, int y)
    /*
        * Requires: Two integers.
        * Modifies: Nothing.
        * Effects: Return the light[x][y].isHas().
        */
    public static boolean canPass(int x, int y, int di)
    /*
        * Requires: Three integers.
        * Modifies: Nothing.
        * Effects: Return the whether can pass.
        */

```

3. Indicated Object

```

private static final int [][] map
private static final int [][] connect
private static final Traffic_light [][] light
private static Vector<Passenger> [][] map_p
private static Vector<ChangeIndex> changeIndex
private static AtomicIntegerArray flows

```

4. Abstract Function

AF(c) = (map, connect, light, map_p, changeIndex, flows), where map = c. map, connect = c. connect, light = c. light, map_p = c. map_p, changeIndex = c. changeIndex, flows = c. flows.

5. Invariance

c. map != null && c. connect != null && c. light != null && c. map_p != null && c. changeIndex != null && c. flows != null

五、 MapException

1. Overview

An user-defined exception.

2. Process Specifications


```
public MapException(String msg)
```

```
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Nothing
*/
```

3. Indicated Object


```
private static final long serialVersionUID
```

4. Abstract Function


```
nothing
```

5. Invariance


```
nothing
```

六、 Passenger_Monitor

1. Overview

Simulate the passenger.

2. Process Specifications


```
private void addPSG(Index loc, Index des)
```

```
/*
    * Requires: Two Index variables which indicate the passenger
    location and destination.
    * Modifies: Nothing.
    * Effects: Construct a passenger and then add the passenger
    request into the passengers.
*/
```

```
public Passenger_Monitor(Taxi[] taxis)
/*
    * Requires: An array of Taxi
    * Modifies: this.taxis
    * Effects: set the taxis
*/
```

3. Indicated Object


```
private Taxi [] taxis
```
4. Abstract Function

AF(c) = (taxis), where taxis = c. taxis.
5. Invariance


```
c. taxis!= null
```

七、 Passenger

1. Overview

A fake Passenger ☺.
2. Process Specifications


```
public Passenger(Index location, Index destination)
```



```

    /*
    * Requires: Two Indexes.
    * Modifies: Nothing.
    * Effects: Initialize the passenger.
    */
    public boolean addTaxi(Taxi taxi)
    /*
    * Requires: A taxi.
    * Modifies: Nothing.
    * Effects: Add the taxi into taxis.
    */
    public Taxi selectTaxi()
    /*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Arrange a taxi to serve this passenger.
    */
    public Index getLocation()
    /*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Return the location.
    */
    public Index getDestination()
    /*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Return the destination.
    */
    public String toString()
    /*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Return the passenger's string.
    */

```

3. Indicated Object

```

private Index location
private Index destination
private Vector<Taxi> taxis

```

4. Abstract Function

AF(c) = (location, destination, taxis), where taxis = c. taxis, destination = c. destination, location = c. location.

5. Invariance

c. taxis != null && c. location != null && c. destination != null

八、 PassengerQuene

1. Overview

A container of all the fake passengers.

2. Process Specifications

```
public static void pushPassenger(Passenger p)
/*
    * Requires: A passenger.
    * Modifies: Nothing.
    * Effects: if passengers' size less than 400 then add the
passenger into passengers.
*/
public static Passenger pullPassenger()
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Push a passenger and return.
*/
public static int getsize()
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Return the passengers' size now..
*/
```

3. Indicated Object

```
private static Vector<Passenger> passengers
private static int size
```

4. Abstract Function

AF(c) = (passengers, size), where passengers = c. passengers, size = c. size.

5. Invariance

c. size >= 0

九、 Schedule

1. Overview

Schedule the passenger.

2. Process Specifications

3. Indicated Object

```
private static int i = 0
```

4. Abstract Function

Nothing.

5. Invariance

c.i >= 0

十、 Taxi_main

1. Overview

Initialize all the classes and make this program running.

2. Process Specifications

```
public static void main(String[] args)
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Initialize all the classes and make this program
running.
*/
```

3. Indicated Object

4. Abstract Function

5. Invariance

十一、 Taxi

1. Overview

Simulate the taxi.

2. Process Specifications

```
public Taxi(int id)
/*
    * Requires: Taxi id.
    * Modifies: Nothing.
    * Effects: Initialize a taxi.
*/

public void setPassenger(Passenger passenger)
/*
    * Requires: A passenger.
    * Modifies: this.passenger and credit.
    * Effects: Allocate a passenger to this taxi.
*/

private void runTaxi(int di)
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: run the taxi.
*/

public int getID()
/*
    * Requires: Nothing.
    * Modifies: Nothing.
    * Effects: Return the taxi'ID.
*/
```

```

public int getCredit()
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the taxi' credit.
     */
public int getState()
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the taxi' state.
     */
public int getNow_x()
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the taxi' x now.
     */
public int getNow_y() {
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the taxi' y now.
     */
public int getTime() {
    /*
     * Requires: Nothing.
     * Modifies: Nothing.
     * Effects: Return the time.
     */

```

3. Indicated Object

```

private int now_x
private int now_y
private int state
private int ID
private int credit
private Passenger passenger
private int Direction
private int exDirection
private int time
private int rest_count

```

4. Abstract Function

AF(c) = (now_x, now_y, state, ID, credit, passenger, Direction, exDirection, time, rest_count), where now_x = c. now_x, now_y = c. now_y, state = c. state, ID = c. ID,

credit = c. credit, passenger = c. passenger, Direction = c. Direction, exDirection = c.
exDirection, time = c. time, rest_count = c. rest_count.

5. Invariance

$0 \leq \text{now_x} < 80 \ \&\& \ 0 \leq \text{now_y} < 80 \ \&\& \ 4 \leq \text{state} \leq 7 \ \&\& \ 0 \leq \text{ID} < 100 \ \&\& \ \text{credit} \geq 0 \ \&\& \ -1 \leq \text{Direction} \leq 3 \ \&\& \ -1 \leq \text{exDirection} \leq 3 \ \&\& \ \text{time} \geq 0 \ \&\& \ 0 \leq \text{rest_count} \leq 200$

十二、 Traffic_light

1. Overview

Simulate the traffic light.

2. Process Specifications

```
public Traffic_light(boolean has)
/*
 * Requires: A boolean.
 * Modifies: Nothing.
 * Effects: Initialize a traffic light.
 */

public boolean isHas()
/*
 * Requires: Nothing.
 * Modifies: Nothing.
 * Effects: Return the has.
 */

public int getL_r()
/*
 * Requires: Nothing.
 * Modifies: Nothing.
 * Effects: Return the l_r.
 */

public int getU_d()
/*
 * Requires: Nothing.
 * Modifies: Nothing.
 * Effects: Return the u_d.
 */

public void change()
/*
 * Requires: Nothing.
 * Modifies: Nothing.
 * Effects: Change the light status..
 */
```

3. Indicated Object

```
private boolean has
private int l_r
private int u_d;
```

4. Abstract Function

$AF(c) = (has, l_r, u_d)$, where $has = c.has$, $l_r = c.l_r$, $u_d = c.u_d$.

5. Invariance

$|c.l_r| == 1 \ \&\& \ |c.u_d| == 1$

十三、Types

1. Overview

Define all the base types in this project.

2. Process Specifications

3. Indicated Object

```
public static final int UP = 0
public static final int DOWN = 1
public static final int LEFT = 2
public static final int RIGHT = 3
public static final int size = 80
public static final int WAIT = 4
public static final int GETPSG = 5
public static final int SERVING = 6
public static final int REST = 7
public static final long BASE_TIME = 100
public static final long CALL_TIME = 3000
public static final int WAIT_TIME = 200
public static final int REST_TIME = 10
```

4. Abstract Function

5. Invariance