

NexECMRtx

Hardware platform supported list

ECAT Slave devices testing list

Manual Rev.: 1.3

Revision Date: May, 11th, 2015

Part No:

Revise note:

Date	Ver	Description
2014/12/8	1.0	Create this document 1. Add tested platforms for NexECMRtx 2. Add supported NIC RTX drivers 3. Add tested EtherCAT servo drivers
2015/4/7	1.1	1. Add support platform Nise3640, Nise2310
2015/5/4	1.2	1. Update NIC support list, Intel I210
2015/12/11	1.3	1. Update servo drives List, Maxon- MAXPOS

Tested Nexcom hardware platforms:

NexECMRtx is tested and optimized for NEXCOM Industrial Computing Platforms. The following table lists the hardware platforms which have been proved to support RTX Ethernet drivers:

Models	EtherCAT Port Numbers	Total Ethernet Port Numbers
Industrial Fanless Computer		
NISE3600 Series	1	2
NISE3640	1	4
NISE4000 Series	1	4
NISE104 Series	1	2
NISE3140 Series	1	2
NISE3500 Series	1	2
NISE2310	1	4
PBOX Rack Mount System (PICMG 1.0/1.3 SBC)		
PEAK872	1	2
Industrial Motherboard		
NEX609	1	2
NEX980	1	2
Industrial Panel PC		
APPC 1530T	1	2

Other Nexcom platform or standard x86 PC/IPC with more than one Ethernet ports could also be compatible with NexECMRtx. You can check which network interface cards / chips (NIC) are equipped within the platform. Supported NICs are listed in following table:

NIC	VendorID	DeviceID	NexECMRtx Version	Comment
Intel 82574L	0x8086	0x10D3	2.0.2.1 and later	
Intel 82583V	0x8086	0x150C	2.0.2.1 and later	
Intel I210	0x8086	0x1533	2.5.1.3 and later	

Tested EtherCAT CoE servo drives / DC servo drives List:

Vendor	Modal Name	Tested / Common
Yaskawa	Sigma-5	Yes
Omron	R88D-KN-ECT	Yes
Schneider	LXM32MU45M2	Yes
Panasonic	Minas A5B,	Yes
Hiwinmikro	D1	Yes
Hiwinmikro	D2	Yes
Delta	ASDA A2-E	Yes
Servotronics	CDHD	Yes
SanyoDenki	RS2E01A0KL4	Yes
MiControl	mcDSA-E65 (DC brush/brushless motor)	Yes
Maxon	MAXPOS	Yes

Testing Items as follow:

Master cycle time = 1 ms

1. ESI file import (NexCAT)
2. ENI file output (NexCAT)
3. EtherCAT state transition, (Can be switch to OP state)
4. PDO (ProcessData) access
5. SDO access, Read/Write CoE objects
6. CoE State Machine can be switched (Servo ON & Servo Off)
7. Cyclic Sync Position (CSP) mode test (With DC enable)
8. Profile Position (PP) mode test
9. Profile Velocity (PV) mode test
10. Home mode (HM) test