Sparse hard oblique forests for jet classification

26 October 2026

Abstract

We study compact classifiers built from shallow oblique trees with linear leaves. Tree Alternating Optimization updates their cuts and leaf functions against a common forest loss. To reduce the number of coefficients, we select support with an L1 penalty, freeze it, and refit without shrinkage (Select–Freeze–Refit). In a jet-classification application, three depth-four trees with 418 nonzero coefficients achieve 56.20% signal efficiency at 1% background acceptance, compared with 55.48% for a 100-tree XGBoost reference with 3,099 scalar parameters. The results motivate sparse oblique forests as candidates for resource-constrained inference.

1 Introduction

Fast classification under hardware resource constraints motivates models that combine predictive accuracy with a small arithmetic workload. An axis-aligned decision tree tests one feature at each node; an oblique tree tests a linear combination. Oblique cuts can describe correlated decision boundaries within shallow trees. Linear leaf functions add first-order variation inside each region. Their coefficients also introduce a cost: a general affine function requires several multiplications and additions.

We investigate this tradeoff using additive forests of hard oblique trees. Tree Alternating Optimization (TAO) revisits the cuts of an existing tree, rather than fixing each cut in a single top-down construction [1]. Sparse oblique trees have also been used to analyze learned feature representations [2]. Here we optimize a shared classification loss for all forest members and study L1 regularization followed by fixed-support refitting. This separates coefficient selection from shrinkage, following the motivation of post-selection methods such as relaxed Lasso [3].

Our application distinguishes quark/gluon jets from W, Z and top jets using 16 high-level input features. The intended implementation context is FPGA inference for the CMS Phase-II Level-1 trigger. We compare floating-point classification performance, coefficient counts and arithmetic bounds, providing a basis for subsequent quantization and synthesis studies.

2 Oblique forests

2.1 Cuts, paths and leaf functions

An event is represented by a feature vector $x \in \mathbb{R}^F$ and a class label $y \in \{0, \dots, K-1\}$. A forest contains T binary trees of depth D, where depth counts decisions on a full root-to-leaf path. We label a node by its path p from the root: $p = \varnothing$ denotes the root, L its left child, R its right child, and RL the left child of R. Internal paths have length $|p| < D$; leaf paths have length D. Appending L or R identifies the two children. This notation describes the tree independently of storage.

At internal node p of tree $t \in \{1, \dots, T\}$, an affine function

$$h_{tp}(x) = w_{tp}^{\mathsf{T}} x + b_{tp}, \qquad p \longrightarrow \begin{cases} pR, & h_{tp}(x) > 0, \\ pL, & h_{tp}(x) \le 0, \end{cases} \tag{1}$$

determines the next branch. Here $w_{tp} \in \mathbb{R}^F$ is the cut's feature weight vector and $b_{tp} \in \mathbb{R}$ its bias. Routing is hard: each event follows exactly one branch. A cut is axis-aligned when only one component of w_{tp} is nonzero, and oblique when it combines several features.

A complete depth-D tree has $I = 2^D - 1$ internal nodes and $L_D = 2^D$ leaves. Its effective topology can be smaller. If $w_{tp} = 0$, the bias determines a constant route, and the other child and its descendants are unreachable for *every* input. For example, $w_{tp} = 0, b_{tp} = 0$ always chooses the left child by Eq. (1). Such branches can be removed without changing the function. A branch merely unused by a finite data sample is not necessarily unreachable.

Let $\ell_t(x)$ be the leaf path reached in tree t. With class $K - 1$ as a reference of zero logit, a linear leaf stores $K - 1$ affine functions

$$f_{t\ell k}(x) = a_{t\ell k}^{\mathsf{T}} x + c_{t\ell k}, \qquad k = 0, \dots, K - 2, \tag{2}$$

where $a_{t\ell k} \in \mathbb{R}^F$ and $c_{t\ell k} \in \mathbb{R}$ are the leaf weights and biases. A constant leaf restricts $a_{t\ell k} = 0$. The forest logits and probabilities are

$$z_k(x) = \sum_{t=1}^{T} f_{t,\ell_t(x),k}(x), \quad z_{K-1}(x) = 0, \qquad P(y = k \mid x) = \frac{\exp z_k(x)}{\sum_{q=0}^{K-1} \exp z_q(x)}. \tag{3}$$

Thus tree logits are added before applying softmax. Linear leaves allow first-order dependence within a region, but do not enforce continuity across its boundaries. The forest is affine on each intersection of its trees' leaf regions; adding trees refines this partition.

For the binary application, class 0 is background and class 1 is signal. The signal margin and probability are

$$m(x) = -z_0(x), \qquad P(y = 1 \mid x) = \frac{1}{1 + \exp[-m(x)]}. \tag{4}$$

A larger margin therefore corresponds to a more signal-like event.

2.2 Parameter and arithmetic counts

Counting scalar weights and biases gives

$$P_{\text{dense}} = T\big[(2^D - 1)(F + 1) + 2^D B(K - 1)\big], \qquad B = \begin{cases} F + 1, & \text{linear leaves}, \\ 1, & \text{constant leaves}. \end{cases} \tag{5}$$

This is the allocated coefficient count for a complete topology. We separately report P_{nz}, the number of coefficients exactly different from zero, and P_{reach}, the nonzero count after removing algebraically unreachable branches. These counts include biases and exclude feature indices, connectivity and preprocessing metadata.

For $F = 16, K = 2, D = 4$, one linear-leaf tree has $15 \cdot 17 + 16 \cdot 17 = 527$ coefficient slots, while three have 1,581. A single dense tree may therefore have a similar *nonzero* count to a more strongly regularized forest of three trees, despite its smaller allocated count.

A dense binary forest with linear leaves needs at most $TF(D + 1)$ feature multiplications and TD comparisons along a selected path. Bias additions are not multiplications. Evaluating all internal functions and leaves instead uses $TF(2^{D+1} - 1)$ multiplications. Sparse functions reduce these counts according to their retained feature weights. They are arithmetic bounds; latency also depends on parallelism, multiplier reuse, precision and memory.

3 Tree Alternating Optimization

3.1 A common forest objective

For training events (x_i, y_i), $i = 1, \dots, N$, let $v_i \geq 0$ be event weights and $W = \sum_i v_i > 0$. All results below use $v_i = 1$. We minimize

$$J(\theta) = \frac{1}{W} \sum_{i=1}^{N} v_i \, \mathrm{CE}(y_i, z(x_i)) + \lambda_s \sum_{t,p} \left(\|w_{tp}\|_1 + |b_{tp}| \right) + \lambda_\ell \sum_{t,\ell,k} \|a_{t\ell k}\|_1 , \qquad \mathrm{CE}(y, z) = \log \sum_{k=0}^{K-1} e^{z_k} - z_y. \tag{6}$$

Here θ denotes all cut and leaf parameters, $\lambda_s \geq 0$ penalizes cuts and $\lambda_\ell \geq 0$ penalizes leaf feature weights. Leaf biases are unpenalized; cut biases are penalized. For constant leaves, λ_ℓ has no effect. Every subproblem retains the full training-weight denominator W, so a penalty has the same normalization at different depths and node occupancies.

TAO alternates optimization blocks while other parameters are fixed [1]. An *epoch* visits every tree, updates its leaves and then its internal nodes from the bottom up, and finally refits all forest leaves jointly. Other trees contribute fixed logit offsets during each individual-tree update. Their offsets are refreshed before updating the next tree. Earlier trees remain trainable; the procedure does not freeze them as later trees are added.

3.2 Leaf optimization

Fix every cut, so the leaf reached by each training event is fixed. For leaf ℓ of tree t, define its event set $\mathcal{I}_{t\ell} = \{i : \ell_t(x_i) = \ell\}$. Introduce the leaf basis $\phi(x) = (x_1, \dots, x_F, 1)^\mathsf{T} \in \mathbb{R}^B$ for linear leaves and $\phi(x) = 1$ for constant leaves. Let $\beta_{t\ell k}$ collect the coefficients of that basis: it is $(a_{t\ell k}, c_{t\ell k})$ for a linear leaf and just $c_{t\ell k}$ for a constant leaf. For $i \in \mathcal{I}_{t\ell}$,

$$z_{ik} = o_{ik} + \phi(x_i)^\mathsf{T} \beta_{t\ell k}, \qquad o_{ik} = \sum_{s \neq t} f_{s,\ell_s(x_i),k}(x_i), \qquad k < K - 1, \tag{7}$$

with $z_{i,K-1} = o_{i,K-1} = 0$. Thus the other trees enter as a fixed offset, not as an additional target to be fitted.

Terms in Eq. (6) from other leaves and all cuts are constant in this update. Removing them leaves the subproblem

$$J_{t\ell}(\beta) = \frac{1}{W} \sum_{i \in \mathcal{I}_{t\ell}} v_i \, \mathrm{CE}(y_i, z_i(\beta)) + \lambda_\ell \sum_{b=1}^{B} \sum_{k=0}^{K-2} \rho_b |\beta_{t\ell k,b}|, \tag{8}$$

where $\rho = (1, \dots, 1, 0)$ for a linear leaf and $\rho = 0$ for a constant leaf. In particular, the bias is unpenalized and the denominator remains W, not the weight sum in $\mathcal{I}_{t\ell}$.

Write $\pi_{ik} = \exp(z_{ik}) / \sum_{j=0}^{K-1} \exp(z_{ij})$ for the current class probabilities, and let $\mathbf{1}[A]$ equal 1 when statement A holds and 0 otherwise. Differentiating the cross-entropy gives

$$\frac{\partial \, \mathrm{CE}(y_i, z_i)}{\partial z_{ik}} = \pi_{ik} - \mathbf{1}[y_i = k], \qquad \frac{\partial L_{t\ell}}{\partial \beta_{t\ell k,b}} = \frac{1}{W} \sum_{i \in \mathcal{I}_{t\ell}} v_i \phi_b(x_i) (\pi_{ik} - \mathbf{1}[y_i = k]), \tag{9}$$

where $L_{t\ell}$ denotes the unpenalized term in Eq. (8). Different leaves of this tree involve disjoint event sets, so they can be fitted separately while its other-tree offset is held fixed.

The joint forest leaf refit has the same form, but includes every tree in one design matrix. Index its columns by (t, ℓ, b) and define

$$A_{i,(t,\ell,b)} = \mathbf{1}[\ell_t(x_i) = \ell] \, \phi_b(x_i), \qquad \Theta_{(t,\ell,b),k} = \beta_{t\ell k,b}. \tag{10}$$

Here $A \in \mathbb{R}^{N\times(TL_DB)}$ and $\Theta \in \mathbb{R}^{(TL_DB)\times(K-1)}$. Thus $z_{ik} = (A\Theta)_{ik}$ for $k < K-1$, with the reference logit zero. If $q = (t, \ell, b)$ indexes a design column and $\rho_q = \rho_b$, its objective and smooth gradient are

$$J_{\text{leaf}}(\Theta) = \underbrace{\frac{1}{W}\sum_i v_i \,\text{CE}(y_i, z_i(\Theta))}_{L(\Theta)} + \lambda_\ell \sum_{q,k} \rho_q |\Theta_{qk}|, \tag{11}$$

$$\nabla_\Theta L = \frac{1}{W} A^\mathsf{T} R, \qquad R_{ik} = v_i(\pi_{ik} - \mathbf{1}[y_i = k]), \quad k < K-1. \tag{12}$$

Cross-entropy is convex in its logits, the logits are affine in the leaf coefficients, and the L1 term is convex. Both the individual-leaf and joint problems are therefore convex. The joint parameters need not be unique: different trees can contribute compensating logits.

To handle L1 with a smooth bound-constrained solver, flatten the coefficients being fitted into scalars ϑ_r, and let λ_r be their penalty strength ($\lambda_\ell\rho_b$ for a leaf coordinate). For each penalized coordinate, write $\vartheta_r = u_r^+ - u_r^-$ with $u_r^+, u_r^- \geq 0$. This is an exact reformulation because

$$\min_{u^+,u^-\geq 0:\ u^+-u^-=\vartheta} \lambda_r(u^+ + u^-) = \lambda_r|\vartheta|. \tag{13}$$

Coordinates with $\lambda_r = 0$ are optimized directly as unconstrained real variables. For either smooth leaf loss L, the auxiliary objective and its penalized-coordinate derivatives are

$$\widetilde{J} = L(\vartheta(u)) + \sum_{r:\lambda_r>0} \lambda_r(u_r^+ + u_r^-), \qquad \frac{\partial \widetilde{J}}{\partial u_r^+} = g_r + \lambda_r, \quad \frac{\partial \widetilde{J}}{\partial u_r^-} = -g_r + \lambda_r, \tag{14}$$

where $g_r = \partial L/\partial\vartheta_r$ is obtained from Eq. (9) or (12). The free-coordinate derivative remains g_r. We minimize this differentiable objective using a bound-constrained quasi-Newton solver and reconstruct the stored coefficients as $\vartheta_r = u_r^+ - u_r^-$.

At a finite iteration budget, both parts can remain positive. Define the actual coefficient objective as $J_{\text{actual}} = L(\vartheta) + \sum_r \lambda_r|\vartheta_r|$. The auxiliary objective exceeds it by the explicit gap

$$\widetilde{J} - J_{\text{actual}} = \sum_{r:\lambda_r>0} \lambda_r(u_r^+ + u_r^- - |u_r^+ - u_r^-|) = 2\sum_{r:\lambda_r>0} \lambda_r \min(u_r^+, u_r^-) \geq 0. \tag{15}$$

Canonical parts $\max(\vartheta_r, 0)$ and $\max(-\vartheta_r, 0)$ remove this gap without changing any logit. We evaluate the candidate with the actual L1 norm and accept it only if its leaf objective does not increase. Since the omitted terms are fixed, this also ensures nonincrease of the full objective in Eq. (6).

3.3 Decision-node optimization

Let $\mathcal{R}_{tp}$ be the training events reaching node p in tree t. Nodes with no reaching events are left unchanged; the following update assumes $\mathcal{R}_{tp} \neq \varnothing$. Keep its ancestors, descendants, leaf functions and all other trees fixed. Ancestors determine $\mathcal{R}_{tp}$, so changing this cut cannot affect any event outside that set. For $i \in \mathcal{R}_{tp}$, let $g_L(x_i)$ and $g_R(x_i)$ be the fixed logit vectors predicted by its two subtrees, and o_i the logit sum from the other trees. The two possible losses are

$$C_i^L = \text{CE}(y_i, o_i + g_L(x_i)), \qquad C_i^R = \text{CE}(y_i, o_i + g_R(x_i)), \qquad \Delta_i = C_i^L - C_i^R. \tag{16}$$

Write $r_i(w, b) = \mathbf{1}[w^\mathsf{T}x_i + b > 0]$ for the proposed right-branch decision. All other penalties and all outside-event losses are constant, so Eq. (6) reduces to

$$Q(w, b) = \frac{1}{W}\sum_{i\in\mathcal{R}_{tp}} v_i[(1 - r_i(w, b))C_i^L + r_i(w, b)C_i^R] + \lambda_s(\|w\|_1 + |b|). \tag{17}$$

Define a preferred-branch label $q_i = \mathbf{1}[\Delta_i > 0]$ and an effective weight $\gamma_i = v_i|\Delta_i|$. For either decision $r \in \{0, 1\}$,

$$(1 - r)C_i^L + rC_i^R = \min(C_i^L, C_i^R) + |\Delta_i|\,\mathbf{1}[r \neq q_i]. \tag{18}$$

Subtracting the first, cut-independent term gives the equivalent weighted misrouting objective

$$Q(w, b) - \frac{1}{W}\sum_{i\in\mathcal{R}_{tp}} v_i \min(C_i^L, C_i^R) = \frac{1}{W}\sum_{i\in\mathcal{R}_{tp}} \gamma_i \mathbf{1}[r_i(w, b) \neq q_i] + \lambda_s(\|w\|_1 + |b|). \tag{19}$$

Thus the reduced labels describe preferred branches, even when the original forest classifies more than two classes. A large $|\Delta_i|$ makes a wrong branch expensive. Events with $\gamma_i = 0$ are indifferent or have zero training weight and give no information for this cut.

Logistic proposal. The discrete misrouting term has no useful ordinary gradient in (w, b). When both branch labels occur among active events, we form a smooth proposal by assigning the right branch probability $\sigma(h_i)$, where $h_i = w^\mathsf{T} x_i + b$ and $\sigma(h) = 1/(1 + e^{-h})$. The Bernoulli negative log-likelihood for branch label q_i is

$$-q_i \log \sigma(h_i) - (1 - q_i) \log[1 - \sigma(h_i)] = \log(1 + e^{h_i}) - q_i h_i. \tag{20}$$

This gives the weighted proposal objective

$$S(w, b) = \underbrace{\frac{1}{W}\sum_{i\in\mathcal{R}_{tp}:\gamma_i>0} \gamma_i\big[\log(1 + e^{h_i}) - q_i h_i\big]}_{L_{\log}(w,b)} + \lambda_s(\|w\|_1 + |b|), \tag{21}$$

with smooth derivatives

$$\nabla_w L_{\log} = \frac{1}{W}\sum_i \gamma_i[\sigma(h_i) - q_i]x_i, \qquad \frac{\partial L_{\log}}{\partial b} = \frac{1}{W}\sum_i \gamma_i[\sigma(h_i) - q_i], \tag{22}$$

where these sums run over the same active events as Eq. (21). The L1 penalty includes the bias and can be handled by the positive/negative parameterization above. Let $(\widehat{w}, \widehat{b})$ denote the resulting approximate minimizer. A decrease in S does not imply a decrease in the hard loss Q, so the proposal must be checked against Eq. (17).

Threshold search and acceptance. Let $(w^{(0)}, b^{(0)})$ be the current cut. We consider directions

$$\mathcal{D} = \{w^{(0)}, \widehat{w}, 0\} \cup \{(1 - \eta)w^{(0)} + \eta\widehat{w} : \eta \in \{0.25, 0.5, 0.75\}\}. \tag{23}$$

For a fixed direction $d \in \mathcal{D}$, set $s_i = d^\mathsf{T} x_i$ and $\tau = -b$, so right routing means $s_i > \tau$. Let $a_1 < \cdots < a_M$ be the distinct projected scores of events in $\mathcal{R}_{tp}$. The intervals

$$I_0 = (-\infty, a_1), \qquad I_m = [a_m, a_{m+1}) \ (1 \leq m < M), \qquad I_M = [a_M, \infty) \tag{24}$$

exhaust the possible routings along d. The half-open convention follows from sending equality left. Equal scores move together; the endpoints include all-right and all-left routing.

To evaluate every interval, start with all events on the right and define

$$U = \sum_{i\in\mathcal{R}_{tp}} v_i C_i^R, \qquad B_m = \sum_{i\in\mathcal{R}_{tp}:s_i\leq a_m} v_i(C_i^L - C_i^R), \qquad B_0 = 0. \tag{25}$$

The values B_m are obtained by sorting the scores once and accumulating whole tied groups. For $\tau \in I_m$, the objective is

$$Q(d, -\tau) = \frac{U + B_m}{W} + \lambda_s \|d\|_1 + \lambda_s|\tau|. \tag{26}$$

Only the bias penalty varies within an interval. We therefore choose its representable finite threshold nearest zero,

$$\tau_m^* \in \arg\min_{\tau \in I_m \cap \mathbb{F}} |\tau|, \tag{27}$$

where $\mathbb{F}$ is the set of finite numbers in the working floating-point format; empty intersections are discarded. This is zero if zero belongs to the interval, the included lower endpoint for an entirely positive interval, and the representable predecessor of the open upper endpoint for an entirely negative interval. The two outer intervals use the same rule. When $\lambda_s = 0$, every threshold in an interval has the same loss; we keep this representative convention.

For each direction d, let $m(d)$ minimize Eq. (26) over its nonempty intervals. We compare the resulting pairs $(d, -\tau^*_{m(d)})$, the raw logistic pair $(\widehat{w}, \widehat{b})$, and the unchanged cut. Each of these proposed cuts is reevaluated using actual hard routing, including both weight and bias penalties. We update only when the best candidate satisfies

$$Q(w^{\text{new}}, b^{\text{new}}) < Q(w^{(0)}, b^{(0)}). \tag{28}$$

Because all omitted terms are fixed, this strictly decreases the full forest objective. The threshold search is exhaustive for each proposed direction; the finite direction set does not exhaust all hyperplanes. In fixed-support refitting, directions must preserve frozen-zero weights, and a frozen-zero bias permits only $\tau = 0$ rather than unrestricted threshold search.

A lower-bound certificate and one-sided labels. During unpenalized fixed-support refitting, $\lambda_s = 0$ and Eq. (19) gives the bound

$$Q(w,b) \geq Q_{\text{lb}} := \frac{1}{W} \sum_{i \in \mathcal{R}_{tp}} v_i \min(C_i^L, C_i^R), \qquad Q(w,b) - Q_{\text{lb}} = \frac{1}{W} \sum_i \gamma_i \mathbf{1}[r_i(w,b) \neq q_i]. \tag{29}$$

The last sum is over $\mathcal{R}_{tp}$. If the current cut chooses the preferred child for every event with $\gamma_i > 0$, the gap is zero. It already minimizes this node's hard subproblem, even over all feasible cuts, so an auxiliary logistic fit is unnecessary. This is a local certificate with subtrees and other trees fixed, not a statement about the full forest optimum.

When active events contain only one branch label, we skip the logistic fit and retain only the current and zero directions in the threshold search. The zero direction gives a constant route whenever the allowed bias permits it. If all $\gamma_i = 0$, any route has the same data loss; the current cut already attains the unpenalized lower bound. These cases introduce no third branch and do not require a finite optimum of a one-class logistic problem.

3.4 Initialization and numerical stopping

Fresh trees are initialized by greedy axis-aligned classification trees fitted to bootstrap draws from the training sample. Subsequent TAO updates use the full training sample. Leaf class counts receive a 0.5 pseudocount before conversion to reference-class log odds; each tree's initial logits are divided by T. Early terminal nodes can be embedded in a complete topology using constant left-routing cuts, which explains some unreachable branches. The sparsity study below continues an existing trained forest.

We distinguish an optimizer iteration, an epoch of alternating tree updates, and convergence of the full run. Reaching an iteration cap alone is not convergence. For fixed routes, let g_q be the gradient of normalized unpenalized cross-entropy with respect to leaf coordinate θ_q, and let λ_q equal λ_ℓ for a penalized feature weight and zero for a bias. The leaf stationarity residual is

$$r_q = \begin{cases} 0, & q \text{ frozen}, \\ |g_q + \lambda_q \operatorname{sign}(\theta_q)|, & q \text{ free}, \ |\theta_q| > \delta, \\ \max(|g_q| - \lambda_q, 0), & q \text{ free}, \ |\theta_q| \leq \delta, \end{cases} \qquad r_{\text{KKT}} = \max_q r_q, \tag{30}$$

with numerical zero tolerance $\delta = 10^{-10}$. Here KKT denotes the Karush–Kuhn–Tucker stationarity conditions. Frozen coordinates are subject to equality constraints and do not require zero gradients. The tolerance δ is used only for this residual; support selection uses exact zeros.

We require $r_{\mathrm{KKT}} \leq 10^{-6}$, successful inner solves, relative objective gain at most 10^{-5} and a routing-change fraction at most 10^{-4} for three consecutive epochs, after at least five epochs. An event counts as rerouted if its leaf changes in any forest member. The relative gain is $\max(0, (J_{\mathrm{before}} - J_{\mathrm{after}})/\max(|J_{\mathrm{before}}|, 10^{-12}))$; increases above 10^{-8} are rejected. These conditions concern numerical stationarity of leaf fits and the available cut proposals. They do not establish global optimality of the forest.

4 Selecting support and refitting

4.1 Select–Freeze–Refit

L1 regularization both removes coefficients and shrinks surviving values. Once a coefficient will be retained, shrinkage can unnecessarily reduce accuracy. Motivated by post-selection refitting [3], we use the following procedure, termed Select–Freeze–Refit (SFR):

1. **Select.** Follow split-only, leaf-only or joint L1 paths using converged terminal fits as warm starts. Choose a support strategy on validation.
2. **Freeze.** Copy the selected parent, fix its topology, and record $M_q = \mathbf{1}[\theta_q \neq 0]$ for every coefficient, including biases.
3. **Refit.** Remove both L1 penalties. First optimize the surviving leaf coefficients with cuts fixed; then optionally alternate cut and leaf updates while preserving the original masks.

Let $\mathcal{C}$ denote coordinates of input-independent cuts and $\theta_{\mathcal{C}}^{\mathrm{parent}}$ their parent values. The full refit minimizes

$$\frac{1}{W}\sum_i v_i \,\mathrm{CE}(y_i, z(x_i;\theta)) \quad \text{subject to } \theta_q = 0 \text{ if } M_q = 0, \quad \theta_{\mathcal{C}} = \theta_{\mathcal{C}}^{\mathrm{parent}}. \tag{31}$$

Free coefficients may change sign or pass through zero; their masks are not reselected. Frozen-zero coefficients cannot regrow. Cuts that were already input-independent retain their parameters and constant decision. A frozen-zero cut bias also remains zero during threshold search. This differs from simply lowering L1 on an unrestricted forest, which could restore removed parameters.

Each stage begins with a joint fixed-route leaf fit; the full stage repeats it after each epoch of cut updates. Model selection uses the declared validation working point among eligible saved fits. A run that eventually converges can have its best validation score at an earlier epoch; the selected snapshot need not itself be stationary.

4.2 Separation and cut-scale ambiguity

Unpenalized logistic fits can exhibit complete or quasi separation, with the loss approaching an infimum as coefficients diverge. With routes fixed, logits are linear in free leaf coordinates. We search for a free direction d such that every true-class margin against another class has a nonnegative change and at least one has a positive change:

$$\frac{d}{d\alpha}\left[z_{y_i}(x_i;\theta+\alpha d) - z_k(x_i;\theta+\alpha d)\right] \geq 0 \quad (v_i > 0,\ k \neq y_i). \tag{32}$$

These are linear inequalities in d. A box-constrained linear program fixes the scale of the direction and searches for a positive summed improvement. A positive feasible result indicates a separating direction; an ambiguous result or timeout is held as inconclusive. Such stages are excluded from

selection, while a separately completed leaf-only stage can remain eligible. This diagnostic does not establish uniqueness of the fitted coefficients.

Cut scale presents a separate issue. For any $c > 0$, in exact arithmetic,

$$\mathbf{1}[w^{\mathsf{T}}x + b > 0] = \mathbf{1}[cw^{\mathsf{T}}x + cb > 0], \qquad \|cw\|_1 + |cb| = c(\|w\|_1 + |b|). \tag{33}$$

The hard-routing loss is unchanged by positive rescaling, while raw-coefficient L1 decreases as c decreases. The logistic proposal fixes a scale within its smooth subproblem, but the outer hard objective remains scale-ambiguous. Thus L1 is an empirical sparsity control in this alternating procedure, not an invariant measure of tree size. Small nonzero cut coefficients cannot simply be discarded: their ratios may still define an important boundary. Explicit rescaling before quantization requires verification near boundaries. An input-independent cut can instead be replaced by its Boolean branch choice.

5 Jet-classification study

5.1 Data and comparison protocol

We use 16 high-level jet features from the dataset catalogued as OpenML 42468 [4]. Class 0 combines quark and gluon jets; class 1 combines W, Z and top jets. The fixed partitions contain 531,200 training, 132,800 validation and 166,000 test events, using split seed 42. Validation contains 52,511 background and 80,289 signal events. Each feature is standardized by its training mean μ_f and standard deviation $s_f > 0$:

$$x_f = (r_f - \mu_f)/s_f, \qquad f = 1, \ldots, F, \tag{34}$$

where r_f denotes the unstandardized feature. All models use the same partitions, labels and feature order.

The primary metric is signal efficiency ϵ_s at background efficiency $\epsilon_b = 0.01$, interpolated on the empirical receiver operating characteristic (ROC). AUC denotes its area. Both use the predicted signal probability. For a threshold τ, the operating efficiencies are the fractions of signal and background events accepted by a score above τ. Interpolation can give a point not exactly realized by a strict threshold. With the validation sample here, a realizable threshold accepting at most 1% background permits at most $\lfloor 0.01 \cdot 52{,}511 \rfloor = 525$ background events.

All oblique scans, SFR choices and results below use validation, with AUC secondary to the low-background working point. The test partition was used in an earlier XGBoost reproduction check, but not to select the oblique models or penalties. Reported uncertainties consequently concern validation and condition on the selected fitted models.

The XGBoost reference is an additive ensemble of axis-aligned trees with constant leaves, trained using gradient/Hessian information for greedy splits and regularized leaf updates [5]. It has 100 trees, maximum depth 4, learning rate 0.1, row and feature subsampling 0.8, histogram-based splits, binary logistic objective and random seed 42. Its realized structure contains 1,499 thresholds, 1,599 leaf values and one base bias: 3,099 scalar parameters. Feature indices and topology are excluded, consistently with the oblique count.

5.2 Selected models and fixed-support study

Table 1 compares three oblique configurations and XGBoost. All oblique entries use depth-four trees and linear leaves. We call the 418-coefficient three-tree model *Compact refit*; the 837-coefficient model is the *higher-efficiency* alternative. A one-tree reference illustrates the distinction between allocated and retained parameters. Figure 1 shows the corresponding ROCs.

Table 1: Validation comparison. Layout gives tree count and maximum depth (D4 means depth four). Dense and nonzero counts include biases. CPU is median bulk time per event in microseconds, measured as described in the text.

Model	Layout	P_{dense}	P_{nz}	ϵ_s [%]	AUC	CPU [μs]
Compact refit	3 × D4	1581	418	56.20	0.92733	0.974
Higher efficiency	3 × D4	1581	837	57.12	0.92967	1.131
One-tree reference	1 × D4	527	452	55.63	0.92704	0.412
XGBoost	100 × D4	3099	—	55.48	0.92056	1.083

The Compact refit uses 49% fewer allocated scalars than XGBoost and about half the nonzero coefficients of the higher-efficiency oblique model. These are different comparisons: a coefficient slot is not necessarily nonzero, and an oblique feature weight does not have the same hardware cost as an axis-aligned threshold. The one-tree reference has fewer allocated slots but more nonzero coefficients than Compact refit.




Figure 1: Validation ROCs of the four selected models. The right panel resolves low background acceptance; dots mark the interpolated 1% background point.

For Compact refit, a converged three-tree parent was continued along a split-penalty path $\lambda_s = 3{\cdot}10^{-5}, 10^{-4}, 3{\cdot}10^{-4}, 10^{-3}, 3{\cdot}10^{-3}$, with $\lambda_\ell = 10^{-5}$. The terminal fit at the final penalty supplied 418 coefficients. Leaf-only refitting raised validation efficiency from 54.59% to 54.81%. Full alternating refitting converged after 15 epochs at 55.98%; its best saved validation snapshot was epoch 8 at 56.20%. The selected model is this earlier snapshot, with the same 418 coefficients. The one-tree reference was trained without L1 and without SFR.

Table 2 and Fig. 2 summarize ten parent supports. Six full refits completed, two were held for separation and two for an inconclusive linear-program timeout. The higher-efficiency model is a completed leaf-only refit at 57.12%, improving its own parent by about 0.21 percentage points. Its full stage was held and is excluded from selection. Stronger penalization does not consistently improve the accuracy–size tradeoff; refitting cannot restore a direction removed by support selection.

Table 2: Fixed-support refitting study. Efficiencies are percentages at 1% background. All models have three depth-four trees except the starred one-tree case. Parent and leaf columns are terminal stage results; best is the best eligible saved leaf/full refit. Held full stages contribute no candidates. The support budget is the parent's exact nonzero count.

λ_s/λ_ℓ	Support	Parent	Leaf	Best	Full stage
0.0001/0.0001	520	55.58	55.82	56.49	complete
0.0003/1e-5	675	56.98	56.74	56.74	timeout
1e-5/3e-5	837	56.91	57.12	57.12	timeout
0.0003/0.0003	394	54.48	54.85	54.85	separated
1e-5/1e-5*	403	55.20	55.06	55.08	complete
0.001/1e-5	561	56.06	56.32	56.46	complete
3e-5/3e-5	777	56.62	56.75	56.75	complete
1e-5/1e-5	889	56.40	56.45	56.74	complete
0.003/1e-5	418	54.59	54.81	56.20	complete
0.001/0.001	317	51.27	52.52	52.52	separated




Figure 2: L1-selected terminal parents and their best eligible fixed-support refits. Each vertical segment keeps the support budget fixed. Only refits from eligible stages contribute; the penalty settings are given in Table 2.

5.3 Uncertainty and inference cost

A paired class-stratified bootstrap with 1,000 replicates, seed 20261025, recomputes the interpolated working point in each replicate. Table 3 gives percentile intervals for the difference from XGBoost. The Compact interval includes zero. These intervals condition on the selected models and account for neither hyperparameter/checkpoint selection nor training-seed variation; they are not independent test claims.

Table 3: Conditional validation efficiency difference from XGBoost, in percentage points (pp), with paired 95% percentile intervals.

Model	Difference [pp]	Interval [pp]
Compact refit	+0.72	[-0.43, +1.52]
Higher efficiency	+1.63	[+0.65, +2.55]
One-tree reference	+0.15	[-1.08, +0.97]

Table 4 gives sparse arithmetic bounds. For comparison, a dense three-tree depth-four linear forest has 240 selected-path or 1,488 all-node feature multiplications and 12 path decisions. The CPU timings in Table 1 use 132,800-event validation batches, one thread, nine repeats and the median wall time per event. They compare a NumPy oblique traversal with compiled XGBoost and are bulk-throughput measurements. Parameter and operation counts motivate implementation studies; FPGA cost requires a numeric format, device, clock and synthesis strategy.

Table 4: Sparse arithmetic bounds after removing input-independent unreachable branches. Path counts bound one selected route; all-node counts evaluate every reachable affine function. Bias additions are excluded from multiplications.

Model	P_{reach}	Path mult.	All-node mult.	Path decisions
Compact refit	379	80	327	12
Higher efficiency	837	163	744	12
One-tree reference	452	65	421	4

6 An example learned tree

Actual cuts illustrate the mixture of axis-aligned, oblique and constant nodes. In Compact refit, using the standardized feature indices of Table 5, the first tree contains

$$h_{1,\varnothing}(x) \simeq x_4 + 0.4216204 \tag{35}$$

$$h_{1,L}(x) = 0 \tag{36}$$

$$\begin{aligned} h_{1,R}(x) \simeq\ & 0.088106595x_4 + 0.0025365055x_6 + 0.17735909x_{11} \\ & + 0.031223362x_{15} + 0.10064081x_{16} + 0.019058664 \end{aligned} \tag{37}$$

Coefficients marked $\simeq$ are rounded to eight significant digits. At the root an event goes right if $x_4 > -0.4216204$. Otherwise it reaches L, whose constant cut sends it left again. Hence the entire LR subtree is unreachable. The root's right child combines five input features.

For the second tree, another learned cut is

$$h_{2,L}(x) \simeq -2.3776136 \cdot 10^{-11} x_{16} - 3.1703281 \cdot 10^{-11} \tag{38}$$

Its small scale does not make it uninformative: it routes right approximately when $x_{16} < -1.3334$. Setting both coefficients to zero would turn it into a constant left route. This example motivates distinguishing exact sparsity from coefficient magnitude before quantization.

7 Discussion

Shallow oblique forests with linear leaves provide competitive validation performance with fewer coefficients than the axis-aligned reference in this application. Compact refit reaches 56.20%

signal efficiency at 1% background acceptance, with 418 nonzeros in 1,581 allocated slots. The higher-efficiency alternative reaches 57.12% with 837 nonzeros. The conditional uncertainty on the Compact–XGBoost difference includes zero, so the principal result is a compression point at comparable validation performance.

Fixed-support refitting recovers accuracy lost to shrinkage without restoring removed coefficients. Its benefit depends on the selected support: aggressive L1 can remove useful directions that refitting cannot recover. Separation, cut-scale ambiguity and the distinction between a converged terminal model and a validation-selected earlier snapshot remain relevant to interpreting training results. Axis-aligned cuts are contained in the oblique family, but this does not imply that three shallow trees can represent every function of a hundred-tree ensemble.

The next step is to quantify how the reduced arithmetic workload translates into hardware. This requires explicit feature, coefficient and accumulator formats, verification of routing changes near cut boundaries, calibration of a realizable working-point threshold, and synthesis measurements at a specified device and clock. Further model choices should be completed before additional test evaluation, retaining disclosure of the earlier XGBoost-only test check.

References

[1] Miguel Á. Carreira-Perpiñán and Pooya Tavallali. Alternating optimization of decision trees, with application to learning sparse oblique trees. In *Advances in Neural Information Processing Systems*, volume 31, 2018. URL https://proceedings.neurips.cc/paper_files/paper/2018/hash/185c29dc24325934ee377cfda20e414c-Abstract.html.

[2] Suryabhan Singh Hada, Miguel Á. Carreira-Perpiñán, and Arman Zharmagambetov. Sparse oblique decision trees: A tool to understand and manipulate neural net features. arXiv:2104.02922, 2021. URL https://arxiv.org/abs/2104.02922. First posted in 2021; revised manuscript and journal version in 2023.

[3] Nicolai Meinshausen. Relaxed lasso. *Computational Statistics & Data Analysis*, 52(1):374–393, 2007. doi: 10.1016/j.csda.2006.12.019. URL https://people.math.ethz.ch/~nicolai/relaxo.pdf.

[4] OpenML. hls4ml_lhc_jets_hlf, dataset 42468. Dataset catalogue. URL https://www.openml.org/d/42468. The project uses its archived feature arrays and fixed splits, rather than a new split from the catalogue.

[5] Tianqi Chen and Carlos Guestrin. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 785–794, 2016. doi: 10.1145/2939672.2939785. URL https://arxiv.org/abs/1603.02754.

A Input feature order

Table 5 defines the coordinates r_f of the archived feature vector, using the source dataset's feature names. All displayed cuts use their standardized counterparts x_f from Eq. (34).

Table 5: Feature-coordinate convention. Names identify columns in the high-level jet dataset [4].

f	Dataset feature	f	Dataset feature
1	`zlogz`	9	`d2_a1_b1_mmdt`
2	`c1_b0_mmdt`	10	`d2_a1_b2_mmdt`
3	`c1_b1_mmdt`	11	`m2_b1_mmdt`
4	`c1_b2_mmdt`	12	`m2_b2_mmdt`
5	`c2_b1_mmdt`	13	`n2_b1_mmdt`
6	`c2_b2_mmdt`	14	`n2_b2_mmdt`
7	`d2_b1_mmdt`	15	`mass_mmdt`
8	`d2_b2_mmdt`	16	`multiplicity`