



Metal Roof

Swimming Pool

Water Tank

Cable Trench

Lift Pit

Bitumen Membrane

Epoxy Flooring

Weather Proofing

Expansion Joint

Pressure Grouting








Heat Reflection Coating

Rehabilitation Works

Painting & Tiles

Building Constructions also

MATERIAL BROCHURE



Office: Panruti Main Road, Opp. Thenkuthu Road, Abatharanapuram, Vadalur-607 303, Tamilnadu, India.

Co-ordinate Office: 212/F1, Trinity Church Street, Golden George Nagar, Mogappair East, Chennai - 600 107. Tamilnadu, India.

Customer Care Number : +91 74183 11972 | Email: pmawaterproofing@gmail.com | Website: www.pmawaterproofing.com

LEAK MAGIC ACRYLIC

PRODUCT DESCRIPTION:

Two pack polymer modified Acrylic based cementitious leak magic coating system

USAGE:

Providing waterproof coating by application of the mixed material by brush or trowel.

FEATURES:

- Form highly flexible film
- Excellent water resistance
- Excellent weather ability hence suitable for exterior application
- Excellent adhesion to concrete and other substrate
- Provides a tough, durable and flexible film and protects concrete from corrosive salts and atmospheric gases
- Coating is breathable, allowing transmission of water vapour from interior of the building Nontoxic and easy to apply
- Fills holes, cracks in concrete | LEED compliant.

LEAK MAGIC ELASTOMERIC S S

PROPERTIES:

Method of application : Brush/Trowel
Pot life : 20-25min @30 Deg
Application Temp. : Not less than 10 C
Colours available : Grey
Coverage : 25 sq. Mt/kit/1mm Thickness

SURFACE PREPARATION:

Remove loose plaster, if any. All the cracks above 0.7mm width should be properly sealed. The surface should be structurally sound and free from oil, grease and loose particles.

METHOD OF APPLICATION:

1. Application of Primer Coat Prepare primer by mixing LEAKCRETE: CEMENT: WATER in the ratio of 1; 1; 4 and apply by brush on prepared surface. 2. Top Coat Prepare the LEAK MAGIC ELASTOMERIC mortar by using LEAK MAGIC ELASTOMERIC 'I' 10 KG and LEAKMAGIC 'B' 25 KG. Mix the contents slowly while continuously stirring manually or mechanically till power is dispersed into a homogeneous pastry brush able mass. Apply it over primed surface by means of stiff brush to get dry film thickness of 1mm per coat.

LEAK MAGIC SET PLUG

APPLICATION INSTRUCTIONS:

SURFACE PREPARATION:

All substrate should be clean and free lose material and contamination. All areas to be patched should be cut back to a minimum depth of 20 mm.

USAGE:

Leak Magic Plug is used for patching water leaks in concrete structures such as; tunnel lining, sewage plants, basements, water tanks, foundations and concrete segment.

PACKAGING:

25kg & 5kg Packing.

STORAGE:

Protect from frost and store under dry warehouse conditions at a temperature between 10 C and 30 C. SHELF LIFE 6 month in unopened bags and stored under good conditions.

LEAK MAGIC WALL SHIELD PREMIUM PLUS

PRODUCTION DESCRIPTION:

Single component, High Quality Acrylic cum polymer based exterior wall water proofing Coating, Highly durable and resistance to fungus on vertical surfaces.

FEATURES:

- High resistance to U.V & Whether Forms as a hard film with elongation property which is High protection to water proofing and Cracks in the wall.

USES:

- Exceptional coating for external walls, Protects the dampness and water penetration as a tough barrier.
- The elongation property of this coat provides a Perfect cover for the cracks

LEAK MAGIC WALL SHIELD PREMIUM

PRODUCTION DESCRIPTION:

Single component, High Quality Acrylic cum polymer based exterior wall water proofing Coating, Highly durable and resistance to fungus on vertical surfaces.

FEATURES:

- High resistance to U.V & Whether
- Forms as a hard film with elongation property which is High protection to water proofing and Cracks in the wall.

USES:

- Exceptional coating for external walls, Protects the dampness and water penetration as a tough barrier.
- The elongation property of this coat provides a Perfect cover for the cracks

LEAK SHIELD HI BUILD PREMIUM PLUS

PREPARATION:

Surface preparation is a very vital issue and this influences the integrity of the waterproofing system. Hence, care must be exercised when the preparation is done. This is very important when re- roofing over an existing old roof.

INSTRUCTIONS TO CARRIED OVER STRICTLY:

1. All surfaces to be smooth, clean, dry and free from dust, rust and loose mortar.
2. Concrete and cementations substrates must be well compacted with a wood float type finish, be at least 28 days old and well dried. Uncured concrete surface will have moisture trapped inside and will turn gaseous when temperature rises. This will lead to blistering and even delaminating from the surface.
3. Wooden or metal panels to be firmly fixed in position.
4. Terrazo roof tiles: Clean and repair damaged joints. Ensure that the tiles are firmly grouted. Remove all loose material.

Metal Roofs: Wire brush to remove moss, mildew, loose paint, and rust areas, then clean surfaces with a broom before priming. High pressure water brooming may be used, if necessary.

LEAK SHIELD HI BUILD PREMIUM

PREPARATION:

Surface preparation is a very vital issue and this influences the integrity of the waterproofing system. Hence, care must be exercised when the preparation is done. This is very important when re-roofing over an existing old roof.

Instructions should be followed strictly.

1. All surfaces to be smooth, clean, dry and free from dust, rust and loose mortar.
2. Concrete and cementations substrates must be well compacted with a wood float type finish, be at least 28 days old and well dried. Uncured concrete surface will have moisture trapped inside and will turn gaseous when temperature rises. This will lead to blistering and even delamination from the surface.
3. Wooden or metal panels to be firmly fixed in position.
4. Terrazo roof tiles: Clean and repair damaged joints. Ensure that the tiles are firmly grouted. Remove all loose material.

Metal Roofs: Wire brush to remove moss, mildew, loose paint, and rust areas, then clean surfaces with a broom before priming. High pressure water brooming may be used, if necessary.

SUNPROOF COOL COATING PREMIUM PLUS

PRODUCT DESCRIPTION:

PMA cool coat, liquid applied, single component, ultra violet rays and weather resistant membrane for all types of exposed roof slabs(new and old) The low thermal conductivity and high reflective glossy white colour of the membrane reduces the heat considerably.

USES:

All Concrete Roofs as better & Metal Sheet Roofs Exterior PVC Water Tang

Features

- High solar reflectance index
- Easy to apply
- Ultra violet rays and weather resistant

SURFACE PREPARATION:

Remove loose plaster, if any. All the cracks above 0.7mm width should be properly sealed. The surface should be structurally sound and free from oil, grease and loose particles.

METHOD OF APPLICATION:

1. **Application of Primer Coat:** Prepare primer by mixing cool coat with WATER in the ratio of 300 ml: 1 litre and apply by brush on prepared surface.
2. **Top Coat:** Prepare 1st coat by mixing cool coat with WATER in the ratio of 150 ml : 1 litre and apply by brush on prepared surface . Prepare Final Coat by applying directly cool coat prepared surface.