Two small piano models: notes and measurements

Hermes Reisner

November 2026

These notes collect what was built, how it was trained and what was measured for the two models in this repository. They are a record of one project, not a study: the test sets are small, there is one training run per setting, and nothing was rated by listeners. Every number comes from the scripts in the repository or from the training logs.

1 The two models

v1 is a GPT-2 decoder (12 layers, width 768, 12 heads, 87.0M parameters) trained from scratch on MAESTRO v3 [1]. It continues a piano passage given as MIDI. **v2** is an RWKV-7 [3] (12 layers, width 768, head size 64, 93.4M parameters) trained on Aria-MIDI [2]. It was built for background music in a game: it has to play for as long as the game runs, follow a density and a loudness setting every five seconds, and cost little enough per token to run on a laptop next to the game.

2 Data and tokens

v1. The 1,276 MAESTRO files are split at random by file (seed 42) into 1,148 training, 63 validation and 65 test files. This is not MAESTRO's official split, so related performances can land on both sides, which flatters the validation loss. Each training file is also transposed by -3 to $+3$ semitones when every note stays within the piano's range, which gives 7,569 training sequences. Tokens are MidiTok's REMI [4, 5] with 32 velocity levels, sustain pedal, tempo and time signature, 423 tokens in all.

v2. The pruned, de-duplicated Aria-MIDI release has 820,944 files, 4.59 billion tokens and 1.52 billion notes in Aria's tokenization (`ariautils`). 1 % of the recordings are held out for validation, chosen by a hash of the recording id. Files shorter than 1,025 tokens are skipped, which leaves 757,367 training and 7,621 validation files. The 2,144 Aria tokens that occur in the data are kept; 15 control tokens are added.

Aria tokens are timed absolutely: every note has an onset in milliseconds within the current five seconds, and a `<T>` token starts each new five seconds. After every `<T>`, v2 sees two control tokens for the coming five seconds (Table 1). In training they are computed from the real notes; they are inputs only and never predicted. 15 % of the segments get a "none" token for both, so the model also learns to play without controls, which classifier-free guidance needs.

Control	Measured over the next 5 s	Levels
Density	notes per second	8: below 0.5, 1.5, 3, 5, 8, 12, 18, and above
Loudness	mean velocity of the notes	5: below 45, 55, 65, 75, and above

Table 1: Control levels.



Figure 1: The same three notes in both tokenizations, as the tokenizers write them.

3 Training

v1. The original v1 was trained in fp32 on an M1 Max with PyTorch's MPS backend and reached a validation loss of 1.43 after two epochs (1.53 after four). Its weights were lost. The released weights are a retraining with the same recipe on a Radeon RX 9060 XT in bf16, using 8 windows times 2 accumulation steps instead of 2 times 8, which gives the same updates. Like the original, it did best after the second epoch (1.4131) and got worse after that, so the released weights are from epoch 2.

v2, two different GPUs. Each card runs its own process; after each step the gradients are summed through host memory (gloo), because RCCL did not work on this pair. The faster card does 20 of the 32 micro-batches per step, the slower 12. Two changes to flash-linear-attention 0.5.2 [6] were needed on these AMD cards. Its WKV kernel is tuned for chunks of 64 tokens; chunks of 16 were 4 to 6 times faster here. And under fp16 the WKV output grew past fp16's maximum of 65,504 (up to 335,000 on about 1 % of windows after 6,000 steps). On the fp16 card that made the loss non-finite, and every such step halved the loss scale, until after about 165 of them the scale reached zero and every step from 9,590 on was lost. The fix runs that kernel in fp32, lets a rank with a non-finite step sit it out while the other's gradient is rescaled to a full step, and leaves the loss scale alone after a non-finite forward pass. Training resumed at step 9,823 and logged no non-finite step after that.

v2, second pass. The first pass ended at a validation loss of 1.7929, still falling by 0.014 per 2,000 steps before its learning-rate decay. The second pass started from the checkpoint before that decay (step 14,007, weights and optimizer) and ran the same 17,509-step schedule over the same data again.

	v1	v2
Window	2,048 tokens, stride 1,024	1,024 tokens, drawn at random, weighted by file length
Batch	16 windows (32,768 tokens)	256 windows (262,144 tokens)
Optimizer	AdamW, weight decay 0.01	AdamW, $\beta = (0.9, 0.99)$, weight decay 0.1, clip 1.0
Learning rate	$2 \cdot 10^{-4}$, 1,000 warmup, cosine	$6 \cdot 10^{-4}$, 500 warmup, constant, $1 - \sqrt{\cdot}$ decay over the last 20 %
Length	4 epochs, best epoch kept	2 passes of 17,509 steps
Hardware	RX 9060 XT, bf16	RX 9060 XT (bf16) and Radeon VII (fp16), gradients summed over gloo
Speed	about 20k tokens/s	about 29k tokens/s, 44 h per pass

Table 2: Training settings of the released weights.

4 Results

4.1 Validation loss

Token kind	First pass, before decay	First pass, final	Second pass, final
note (pitch and velocity)	2.537	2.441	2.369
onset	1.744	1.692	1.657
duration	1.325	1.288	1.263
<T>	0.446	0.374	0.362
mean	1.855	1.793	1.749

Table 3: v2 validation loss (nats per token) on the 256 windows the training log uses. The second-pass column was evaluated in fp16 with the released code (1.7491; the training log has 1.7493 in bf16).

Notes carry most of the remaining loss: which pitch comes next is where the music is decided.

v1's validation loss, over the 2,048-token windows of the 63 validation files, was 1.501, 1.413, 1.448 and 1.478 after epochs one to four, while its training loss kept falling to about 1.10.

4.2 Following the controls

Tested on the first-pass model, sampling with temperature 1 and top-p 0.95. "Fresh start" asks for each density level from an empty state; the long stream runs 15 minutes and switches the density target every 30 seconds. Guidance runs a second stream with "none" controls and uses $\ell_a + \gamma(\ell_a - \ell_b)$.

γ	Fresh start	Minutes 0–4 / 10–14	Notes/s late, targets 3–5 / 8–12	Malformed per 1,000
0	0.93	0.92 / 0.88	4.2 / 10.3	0.00
0.5	0.94	0.95 / 0.99	3.9 / 9.9	0.00
1	0.99	0.99 / 0.97	3.9 / 10.0	0.01
1.5	1.00	0.99 / 0.99	3.8 / 9.8	0.02
2	1.00	0.99 / 0.99	3.8 / 10.1	0.03

Table 4: Share of 5-s segments in the asked density band.

Without guidance the music follows every switch within the first 5-s segment after it, and the mean velocity is 33 at the softest setting and 91 at the loudest. The one gap is dense music late

in a long stream: 80 % of those segments land in their band without guidance, 98 % at $\gamma = 0.5$. The small test models (Section 5) drifted away from "dense" after 10 to 30 minutes; this model, trained with hidden controls, does not. So the default is no guidance, which keeps the cost at one model call per token.

4.3 Comparison with real playing

96 recordings from v2's validation split (one file each, no silent five seconds in the first minute) supply the first 20 seconds; each model continues for 40 seconds without controls or guidance, two samples per piece. A logistic regression on 22 features of seconds 20 to 60 tries to tell the real continuation from the model's. The features include key fit, notes outside the key, interval, pitch-class and rhythm variety, leaps, range, loudness spread, note density, polyphony and how often a short figure repeats. It is scored by five-fold cross-validation grouped by piece (`eval/compare.py`). To check that the test separates damage from quality, damaged copies of the real pieces go through the same test.

	AUC	95 % interval	Model rated more real
v2, second pass	0.64	0.59–0.69	30 %
v2, first pass	0.68	0.63–0.72	24 %
v2, step 2,000 of the second pass	0.69	0.65–0.73	22 %
5 % of notes moved by 1–2 semitones	0.62	0.59–0.66	
15 % of notes moved	0.79	0.75–0.84	
pitches shuffled	0.89	0.85–0.93	
random timing	0.99	0.99–1.00	
random pitches	1.00	1.00–1.00	

Table 5: How well a classifier tells each system from real playing. 0.5 would mean it cannot. Intervals are bootstrap intervals over pieces (500 resamples). The last column is the share of pieces where the model's version scores as more real than the real one.

The second pass is the closest to real playing. Its lead over the first pass is 0.044 AUC with a paired interval of −0.002 to 0.094 over pieces: probably real, not certain with 96 pieces. What still separates it from real playing is variety, each by about a third of a standard deviation: fewer different intervals, flatter loudness, less varied note timing and fewer pitch classes. Key fit, notes outside the key, leaps and range do not stand out any more. The early checkpoint repeats short figures far too often (0.76 standard deviations above real playing). None of this measures whether the music is pleasant.

4.4 Speed and memory

Music needs about 30 Aria tokens per second on average and 83 in the busiest 1 % of one-second windows, so the target is about 12 ms per token when generating a second or two ahead. A transformer's growing cache did not compile for the Neural Engine with Core ML's own stateful API at any size tried, and passing the cache in and out by hand cost about 13 ms per token (89M parameters, 512-token window). RWKV-7 does the same fixed-shape step for every token.

5 Small test runs

Before the main run, runs of about 28M parameters and 250M tokens chose the architecture and the recipe. They had no control dropout, so their guidance was contrastive (a second stream




Figure 2: Memory per stream in fp16: the GPT-2 key-value cache grows by 36.9 kB per token (12 layers, keys and values of width 768); the RWKV-7 state is 1.2 MB at any length.

Backend	Weights	1 stream	2 streams	Top-1 = fp32
Neural Engine, Core ML (mains power, 5 Nov)	int8	2.86	5.73	127/128
Neural Engine, Core ML (battery, 26 Oct)	int8	4.03	7.84	502/512
Neural Engine, Core ML (battery, 26 Oct)	fp16	5.95	11.84	506/512
CPU, Core ML (battery, 26 Oct)	int8	6.62	13.2	
AMX, C + Accelerate (battery, 26 Oct)	fp32	10.42	12.88	512/512
PyTorch CPU, eager	fp32	19.1		reference

Table 6: Median time per v2 step in ms on an M1 Pro (2021 MacBook Pro), Low Power Mode off except for the PyTorch row. The 26 Oct rows used the first-pass weights; the step model is the same.

with a contrasting control).

Question	Result
RWKV-7 or GPT with RoPE	validation loss 2.172 against 2.258; at 39M tokens 3.04 against 3.86. A GPT with learned positions was far worse.
Density control from a fresh state	asked level hit in 69–97 % of segments
Loudness control	mean velocity 32 (soft) against 99 (loud)
A 35-minute stream without guidance	“dense” drifts from 9 to about 5 notes/s after 10–30 minutes in both architectures
The same with guidance	$\gamma = 1$ holds “dense” at 11 notes/s at minute 15; $\gamma = 2$ overshoots
Distillation from Aria (658M)	at most 0.05 nats better at equal tokens and 2.7 times slower: not used
Two GPUs against one, 94M	29.7k against 20.5k tokens/s

Table 7: Results of the small runs.

6 Things that went wrong

- The fp16 overflow in the WKV kernel (Section 3) did not crash anything: from step 9,590 the run simply stopped learning. It was stopped at step 9,823 and resumed with the fix the next morning.
- Core ML’s stateful key-value cache never compiled for the Neural Engine. The RWKV-7

step compiled only once its per-head norm and sums used rank-3 tensors; with rank-4 tensors Core ML moved it to the CPU without an error.

- The RX 9060 XT hung twice under an undervolting profile. The run resumed from its 10-minute checkpoint, and the card has run at stock settings since.

7 Limitations

- Neither model plans long-form structure; themes do not come back on their own.
- v2's controls act every five seconds. Faster changes need a layer outside the model.
- Aria-MIDI is transcribed from audio and carries transcription errors, and both datasets are mostly classical piano.
- The comparison with real playing uses note statistics and 96 pieces; no listener has rated the music.
- Inference in fp16 on long streams may meet the same overflow as training; the 128-step check does not cover it.
- The speed numbers are model steps on one laptop. Running next to a game has not been measured.

References

[1] C. Hawthorne et al., "Enabling Factorized Piano Music Modeling and Generation with the MAESTRO Dataset," ICLR 2019.

[2] L. Bradshaw and S. Colton, "Aria-MIDI: A Dataset of Piano MIDI Files for Symbolic Music Modeling," ICLR 2025.

[3] B. Peng et al., "RWKV-7 'Goose' with Expressive Dynamic State Evolution," arXiv:2503.14456, 2025.

[4] Y.-S. Huang and Y.-H. Yang, "Pop Music Transformer: Beat-based Modeling and Generation of Expressive Pop Piano Compositions," ACM Multimedia 2020.

[5] N. Fradet et al., "MidiTok: A Python Package for MIDI File Tokenization," ISMIR 2021, late-breaking demo.

[6] S. Yang and Y. Zhang, flash-linear-attention, `https://github.com/fla-org/flash-linear-attention`.