

INFO1113 Object-Oriented Programming

Week 2A: Control Flow, Loops and Static Methods

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).


The material in this communication may be subject to copyright under the Act.
Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

- Control flow (s. 3)
- While loop (s. 16)
- For loop (s. 21)
- Static methods (s. 30)


Loops

Remember flow control diagrams?



Loops

Remember flow control diagrams?



What if we changed `i` to **5**?

What would be the output of this program?

4 types of loops we can write within Java.

- while
- do-while
- for
- for-each

The constructs are part of the language's syntax and typically follow a similar pattern.

Syntax: `while` (*condition*) statement

As with if statements, for this branch to start and *continue* execution the *condition* must be **true**.

```
while(condition) {  
  
}
```

Syntax: `while` (*condition*) statement

As with if statements, for this branch to start and *continue* execution the *condition* must be **true**.

```
while(condition) {  
  
}
```

A boolean expression is evaluated here and is checked on every iteration.

Syntax: `while` (*condition*) statement

As with if statements, for this branch to start and *continue* execution the *condition* must be **true**.

```
while(condition) {  
    doWork()  
}
```

A boolean expression is evaluated here and is checked on every iteration.

The body of the loop. It will execute the following body until the condition is no longer met.

Syntax: `while` (*condition*) statement

As with if statements, for this branch to start and *continue* execution the *condition* must be **true**.

```
while (i < 40) {  
    doWork();  
    i += 1;  
}
```

A boolean expression is evaluated here and is checked on every iteration. The following `i < 40` is perfectly valid expression

The body of the loop. It will execute the following body until the condition is no longer met.

Syntax: `do {} while(condition) statement`

Similar to the while loop but it will always execute the block at least **once** and *continue* execution if condition is **true**.

```
do {  
  
    doWork();  
  
} while (condition)
```

Loops

Syntax: `do {} while(condition) statement`

Similar to the while loop but it will always execute the block at least **once** and *continue* execution if condition is **true**.

do {

`doWork();`

} **while** (condition)

The loop scope is defined by the curly braces. The **do** keyword must be followed by the **while** keyword after the block definition.

A boolean expression is evaluated here and is checked on every iteration.

Loops

Syntax: `do {} while(condition) statement`

Similar to the while loop but it will always execute the block at least **once** and *continue* execution if condition is **true**.

do {

`doWork();`

} **while** (condition)

The loop scope is defined by the curly braces. The **do** keyword must be followed by the **while** keyword after the block definition.

A boolean expression is evaluated here and is checked on every iteration.

Note: **do-while** is known to be discouraged in many style guides

Let's write some loops!

Syntax: `for([variable]; [condition]; [update]) statement`

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( [variable]; [condition]; [update] )  
{  
  
    doWork();  
  
}
```

Loops

Syntax: `for([variable]; [condition]; [update]) statement`

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( [variable]; [condition]; [update] ) {  
  
    doWork();  
  
}
```


We are able to create and initialise variables for our loop here. They will be restricted to the loop's scope.

Loops

Syntax: `for([variable]; [condition]; [update]) statement`

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; [condition]; [update] ) {  
  
    doWork();  
  
}
```



A common variable is a counter for our for loop.

Loops

Syntax: `for([variable]; [condition]; [update])`
statement

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; [condition]; [update] ) {  
  
    doWork();  
  
}
```

The boolean expression to the inputted here. No different than a while loop

Loops

Syntax: `for([variable]; [condition]; [update]) statement`

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; i < 10; [update] ) {  
    doWork();  
}
```

Let's say we wanted
to loop 10 times

Loops

Syntax: `for([variable]; [condition]; [update])` statement

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; i < 10; [update] ) {  
  
    doWork();  
  
}
```

This is the update component. Were we update any variables defined within the **variable** section (or variables defined in the outer scope_

Loops

Syntax: `for([variable]; [condition]; [update]) statement`

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; i < 10; i += 1) {  
    doWork();  
}
```

So we can increment by 1, similar to the while loop.

Loops

Syntax: `for([variable]; [condition]; [update])` statement

for loops are broken up into 3 separate sections. **Variables**, **Conditions** and **Updates** sections.

```
for( int i = 0; i < 10; i += 1) {  
  
    doWork();  
  
}
```

So we can increment by 1, similar to the while loop.

Regardless you can always rewrite a **for** loop as a **while** loop.

Using a for-loop!

Okay, what about for-each?

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( binding : collection ) {  
  
    doWork(binding);  
  
}
```

Loops

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( binding : collection ) {  
  
    doWork(binding);  
  
}
```

A collection is an object that **aggregates** other objects.

A binding in this case is just some variable that will represent an **element** of the **collection**.

Loops

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( String str : strings ) {  
  
    System.out.println(str);  
  
}
```

This is our collection type here. Containing our strings

Declaration of a **String** variable that will be an element in the collection.

Loops

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( String str : strings ) {  
  
    System.out.println(str);  
  
}
```

String[],
ArrayList<String>,
List<String>,
Set<String>,
Deque<String>
...

What kind of object **aggregates** other objects?
Anything that implements **hasNext()**, **next()**, and optionally **remove()**

Loops

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( String str : strings ) {  
  
    System.out.println(str);  
  
}
```

What information are we missing by using a **for**-each loop?

Loops

Syntax: `for(binding : collection) statement`

for-each loops involve the use of **iterators** (exception being arrays).

```
for( String str : strings ) {  
  
    System.out.println(str);  
  
}
```

What information are we missing by using a **for**-each loop? **an array index**

Using a for-each loop

Syntax:

```
static [final] return_type name ([parameters])
```

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static int addThree(int a, int b, int c) {  
    return a+b+c;  
}
```


Static Methods

Binds the method to the class. Without **static** it is an instance method.

Syntax:

```
static [final] return_type name ([parameters])
```

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static int addThree(int a, int b, int c) {  
    return a+b+c;  
}
```

Static Methods

Binds the method to the class. Without **static** it is an instance method.

Return type of the method.

Syntax:

`static` [`final`] `return_type` `name` ([`parameters`])

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static int addThree(int a, int b, int c) {  
    return a+b+c;  
}
```

Static Methods

Binds the method to the class. Without **static** it is an instance method.

Return type of the method.

Method identifier, the name we use to call it.

Syntax:

`static` [`final`] `return_type` `name` ([`parameters`])

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static int addThree(int a, int b, int c) {  
    return a+b+c;  
}
```

Static Methods

Binds the method to the class. Without **static** it is an instance method.

Return type of the method.

Method identifier, the name we use to call it.

Arguments of the method. Aka input.

Syntax:

`static` [`final`] `return_type` `name` ([`parameters`])

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static int addThree(int a, int b, int c) {  
    return a+b+c;  
}
```


Syntax:

```
static [final] return_type name ([parameters])
```

A method is a stored set of instructions bound to an object. In the case of a static method, the object is the class which it is defined in.

Example:

```
public static return_type addThree(int a, int b, int c)
{
    return a+b+c;
}
```



The return type can be any **primitive type**, **reference type** or **void**

Return types

Java can use any primitive or reference type as a **return** type. The compiler will check and ensure that any assignment to the return value of a method is correct.

There is a special return type that you **may** or **may not** have encountered: **void**.

void does not return any value and any void method is typically used for manipulating passed data or output.

Returning data from a method is generally used for **querying** or object **creation**.

Static methods


Call Stack

Java is a stack-based language so when a method is executed it is put onto a **call-stack**.

The method being executed at the top of the stack is the most recently called method.

A method finishes executing once it has reached a return state or for **void** method, once it has reached the end of method scope.

Latest being executed




Call Stack

Each method executed gets a **Frame** allocated and a **frame** will hold data, partial results, return values and **dynamic linking**.

A **Frame** is created when a method is invoked at runtime by the java virtual machine.

Latest being executed



Let's break down the call stack

See you next time!