

Packet Tracer - Use the ipconfig Command

Objectives

- Use the **ipconfig** command to identify incorrect configuration on a PC.

Background / Scenario

A small business owner cannot connect to the internet with one of the four PCs in the office. All the PCs are configured with static IP addressing using 192.168.1.0 /24 network. The PCs should be able to access **www.cisco.pka** webserver. Use the **ipconfig /all** command to identify which PC is incorrectly configured.

Instructions

Part 1: Verify Configurations

- a. Access the **Command Prompt** on each PC and enter the command **ipconfig /all** at the prompt.
- b. Examine the IP address, subnet mask, and default gateway configuration for each PC. Be sure to record this IP configuration for each PC to help identify any PCs that are incorrectly configured.

Part 2: Correct Any Misconfigurations

- a. Select the PC that is incorrectly configured.
- b. Click the **Desktop** tab > **IP Configuration** tab to correct the misconfiguration.

PC4

FastEthernet0 Connection:(default port)
Connection-specific DNS Suffix...:
Physical Address.....: 0050.0FC6.0C67
Link-local IPv6 Address.....: FE80::250:FFF:FEC6:C67
IPv6 Address.....: ::
IPv4 Address.....: 192.168.1.104
Subnet Mask.....: 255.255.255.0
Default Gateway.....: ::192.168.1.1
DHCP Servers.....: 0.0.0.0
DHCPv6 IAID.....:
DHCPv6 Client DUID.....: 00-01-00-01-4C-67-1C-24-00-50-0F-C6-0C-67
DNS Servers.....: ::192.15.2.5

PC3

FastEthernet0 Connection:(default port)
Connection-specific DNS Suffix...:
Physical Address.....: 0000.0CB5.0933
Link-local IPv6 Address.....: FE80::200:CFF:FEB5:933
IPv6 Address.....: ::
IPv4 Address.....: 192.168.1.103
Subnet Mask.....: 255.255.255.0
Default Gateway.....: ::192.168.1.1
DHCP Servers.....: 0.0.0.0
DHCPv6 IAID.....:
DHCPv6 Client DUID.....: 00-01-00-01-39-E4-AB-C2-00-00-0C-B5-09-33
DNS Servers.....: ::192.15.2.5

PC2

Wireless0 Connection:(default port)
Connection-specific DNS Suffix...:
Physical Address.....: 0004.9ADD.3D59
Link-local IPv6 Address.....: FE80::204:9AFF:FEDD:3D59
IPv6 Address.....: ::
IPv4 Address.....: 192.168.10.102
Subnet Mask.....: 255.255.255.0
Default Gateway.....: ::192.168.1.1

DHCP Servers.....: 0.0.0.0
DHCPv6 IAID.....: 11728
DHCPv6 Client DUID.....: 00-01-00-01-00-B3-73-B0-00-04-9A-DD-3D-59
DNS Servers.....: ::192.15.2.5

PC1

Wireless0 Connection:(default port)
Connection-specific DNS Suffix...:
Physical Address.....: 0090.210A.70A5
Link-local IPv6 Address.....: FE80::290:21FF:FE0A:70A5
IPv6 Address.....: ::
IPv4 Address.....: 192.168.1.101
Subnet Mask.....: 255.255.255.0
Default Gateway.....: ::192.168.1.1
DHCP Servers.....: 192.168.1.1
DHCPv6 IAID.....: 11940
DHCPv6 Client DUID.....: 00-01-00-01-D2-06-CD-3B-00-90-21-0A-70-A5
DNS Servers.....: ::192.15.2.5