

Packet Tracer - Verify IPv4 and IPv6 Addressing

Addressing Table

Device	Interface	IP Address / Prefix		Default Gateway
R1	G0/0	10.10.1.97	255.255.255.224	N/A
		2001:db8:1:1::1/64		
	S0/0/1	10.10.1.6	255.255.255.252	N/A
		2001:db8:1:2::2/64		
		fe80::1		
R2	S0/0/0	10.10.1.5	255.255.255.252	N/A
		2001:db8:1:2::1/64		
	S0/0/1	10.10.1.9	255.255.255.252	N/A
		2001:db8:1:3::1/64		
		fe80::2		
R3	G0/0	10.10.1.17	255.255.255.240	N/A
		2001:db8:1:4::1/64		
	S0/0/1	10.10.1.10	255.255.255.252	N/A
		2001:db8:1:3::2/64		
		fe80::3		
PC1	NIC	10.10.1.100	255.255.255.224	10.10.1.97
		2001:DB8:1:1::A		FE80::1
PC2	NIC	10.10.1.20	255.255.255.240	10.10.1.17
		2001:DB8:1:4::A		FE80::3

Objectives

Part 1: Complete the Addressing Table Documentation

Part 2: Test Connectivity Using Ping

Part 3: Discover the Path by Tracing the Route

Background

Dual-stack allows IPv4 and IPv6 to coexist on the same network. In this activity, you will investigate a dual-stack implementation including documenting the IPv4 and IPv6 configuration

for end devices, testing connectivity for both IPv4 and IPv6 using **ping**, and tracing the path from end to end for IPv4 and IPv6. Complete the Addressing Table Documentation

Step 1: Use ipconfig to verify IPv4 addressing.

- Click **PC1** and open the **Command Prompt**.
- Enter the **ipconfig /all** command to collect the IPv4 information. Fill-in the **Addressing Table** with the IPv4 address, subnet mask, and default gateway.
- Click **PC2** and open the **Command Prompt**.
- Enter the **ipconfig /all** command to collect the IPv4 information. Fill-in the **Addressing Table** with the IPv4 address, subnet mask, and default gateway.

Step 2: Use ipv6config to verify IPv6 addressing.

- On **PC1**, enter the **ipv6config /all** command to collect the IPv6 information. Fill-in the **Addressing Table** with the IPv6 address, subnet prefix, and default gateway.
- On **PC2**, enter the **ipv6config /all** command to collect the IPv6 information. Fill-in the **Addressing Table** with the IPv6 address, subnet prefix, and default gateway.

Part 2: Test Connectivity Using Ping

Step 1: Use ping to verify IPv4 connectivity.

- From **PC1**, ping the IPv4 address for **PC2**.

Question

Was the result successful? yes

- From **PC2**, ping the IPv4 address for **PC1**.

Question

Was the result successful? yes

Step 2: Use ping to verify IPv6 connectivity.

- From **PC1**, ping the IPv6 address for **PC2**.

Question

Was the result successful? yes

From **PC2**, ping the IPv6 address of **PC1**.

Question

Was the result successful? yes

Part 3: Discover the Path by Tracing the Route

Step 1: Use tracert to discover the IPv4 path.

- From **PC1**, trace the route to **PC2**.

PC> **tracert 10.10.1.20**

Question

What addresses were encountered along the path? 10.10.1.97, 10.10.1.5, 10.10.1.10 , 10.10.1.20

With which interfaces are the four addresses associated: R1G0/0, R2S0/0/0, R3S0/0/1, PC2NIC

b. From **PC2**, trace the route to **PC1**.

What addresses were encountered along the path? 10.10.1.17, 10.10.1.9, 10.10.1.6, 10.10.1.100

With which interfaces are the four addresses associated?: R3G0/0, R2S0/0/1, R1S0/0/1, PC1 NIC

Step 2: Use tracert to discover the IPv6 path.

a. From **PC1**, trace the route to the IPv6 address for **PC2**.

PC> **tracert 2001:db8:1:4::a**

What addresses were encountered along the path?

2001:DB8:1:1::1

2001:DB8:1:2::1

2001:DB8:1:3::2

2001:DB8:1:4::A

With which interfaces are the four addresses associated? R1G0/0, R2S0/0/0, R3S0/0/1, PC2NIC

b. From **PC2**, trace the route to the IPv6 address for **PC1**.

What addresses were encountered along the path?

2001:DB8:1:4::1,

2001:DB8:1:3::1,

2001:DB8:1:2::2

2001:DB8:1:1::A

With which interfaces are the four addresses associated? **R3G0/0, R2S0/0/1, R1S0/0/1, PC1NIC**